



GIG VISION **GEN<i>i>CAM**



sensor information

sensor	Sony ICX274
type	1/1.8" interline progressive scan CCD
resolution	1624 × 1236 px
exposure time	0,004 ... 60000 ms
pixel size	4.4 × 4.4 μm

acquisition formats

image formats, frame rate max.	Full Frame HQ, 1624 × 1236 px, max. 8,0 fps
	Full Frame, 1624 × 1236 px, max. 16,0 fps
	Binning 2×2 HQ, 812 × 618 px, max. 15,0 fps
	Binning 2×2, 812 × 618 px, max. 29,0 fps
	Binning 1×2 HQ, 1624 × 618 px, max. 15,0 fps
	Binning 1×2, 1624 × 618 px, max. 29,0 fps
	Binning 2×1 HQ, 812 × 1236 px, max. 8,0 fps
Binning 2×1, 812 × 1236 px, max. 16,0 fps	

pixel formats	Mono8
	Mono12
	Mono12 Packed

image pre-processing

analog controls	Gain (0 ... 20 dB)
	Offset (0 ... 255 LSB 12 Bit)

color models	Mono
--------------	------

interfaces and connectors

data interface	Gigabit Ethernet, Transfer rate 1000 Mbits/sec, Connector: M12 / 8 pins, Screw lock type
----------------	---

process interface	M8 / 4 pins
-------------------	-------------

power supply	M8 / 3 pins
--------------	-------------

mechanical data

material	housing: aluminum
lens mount	C-mount
diameter	65 mm
depth	50 mm
weight	≤ 360 g

electrical data

voltage supply	8 ... 30 V DC
range +Vs	

power consumption	approx. 6,0 W
-------------------	---------------

environmental conditions

operating temperature	+5 ... +50 °C
-----------------------	---------------

humidity	10 ... 90 % (non-condensing)
----------	------------------------------

protection class	IP 67
------------------	-------

dimension drawing

