



GIG VISION **GEN<i>i</i>CAM**



sensor information

sensor	Sony ICX274
type	1/1.8" interline progressive scan CCD
resolution	1624 × 1236 px
exposure time	0,004 ... 60000 ms
pixel size	4.4 × 4.4 μm

acquisition formats

image formats, frame rate max.	Full Frame HQ, 1624 × 1236 px, max. 8,0 fps
	Full Frame, 1624 × 1236 px, max. 16,0 fps
	Binning 2×2 HQ, 812 × 618 px, max. 15,0 fps
	Binning 2×2, 812 × 618 px, max. 29,0 fps
	Binning 1×2 HQ, 1624 × 618 px, max. 15,0 fps
	Binning 1×2, 1624 × 618 px, max. 29,0 fps
pixel formats	Mono8
	Mono12 Packed

image pre-processing

analog controls	Gain (0 ... 20 dB) Offset (0 ... 255 LSB 12 Bit)
-----------------	---

color models	Mono
--------------	------

interfaces and connectors

data interface	Gigabit Ethernet, Transfer rate 1000 Mbits/sec, Connector: 8P8C Modular Jack (RJ45), Screw lock type
process interface	M8 / 4 pins
power supply	via 8P8C Modular Jack (RJ45)

mechanical data

material	housing: aluminum
lens mount	C-mount
width	36 mm
height	36 mm
depth	58 mm

mechanical data

weight	≤ 110 g
--------	---------

electrical data

voltage supply range +Vs	20 ... 57 V DC
power consumption	approx. 4,3 W

environmental conditions

operating temperature	+5 ... +50 °C
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

dimension drawing

