

# Absolute encoders - SSI

Ex approval Ex II 2D/2G (ATEX)

Optical single and multiturn encoders

Singleturn 14 bit, Multiturn 13 bit ST / 12 bit MT

## X 700 - SSI



X 700 with clamping flange

### Features

- Encoder single- or multiturn / SSI / ATEX
- Optical sensing method
- Resolution: singleturn 14 bit, multiturn 13 + 12 bit
- Clamping flange with solid shaft  $\varnothing 10$  mm
- Explosion protection per Ex II 2D/2G (ATEX)
- Device class 2 / zone 1 (gas), zone 21 (dust)
- Electronic setting of zero point
- Counting direction input
- Maximum resistant against magnetic fields

### Technical data - electrical ratings

Reverse polarity protection	Yes
Consumption w/o load	$\leq 50$ mA (24 VDC)
Initializing time typ.	20 ms after power on
Interface	SSI
Steps per turn	16384 / 14 bit
Absolute accuracy	$\pm 0.025^\circ$
Sensing method	Optical
Code	Gray or binary
Code sequence	CW/CCW coded by connection
Inputs	SSI clock Control signals UP/DOWN and zero
Output stages	SSI data: linedriver RS485 Diagnostic outputs push-pull
Interference immunity	DIN EN 61000-6-2
Emitted interference	DIN EN 61000-6-4
Diagnostic functions	Self-diagnosis Multiturn sensing

### X 700 - Singleturn

Voltage supply	10...30 VDC
Function	Singleturn

### X 700 - Multiturn

Voltage supply	10...30 VDC 5 VDC $\pm 10\%$
Function	Multiturn
Number of turns	4096 / 12 bit

### Technical data - mechanical design

Size (flange)	$\varnothing 70$ mm
Shaft type	$\varnothing 10$ mm solid shaft (clamping flange)
Flange	Clamping flange
Protection DIN EN 60529	IP 67
Operating speed	$\leq 6000$ rpm (mechanical) $\leq 6000$ rpm (electric)
Starting acceleration	$\leq 1000$ U/s <sup>2</sup>
Starting torque	$\leq 0.4$ Nm (+25 °C)
Admitted shaft load	$\leq 60$ N axial $\leq 50$ N radial
Materials	Housing: stainless steel Flange: stainless steel
Operating temperature	-25...+60 °C
Relative humidity	95 % non-condensing
Resistance	DIN EN 60068-2-6 Vibration 10 g, 16-2000 Hz DIN EN 60068-2-27 Shock 200 g, 6 ms
Explosion protection	Ex II 2G Ex d IIC T6 Ex II 2D
Weight approx.	1300 g
Connection	Cable

# Absolute encoders - SSI

Ex approval Ex II 2D/2G (ATEX)

Optical single and multiturn encoders

Singleturn 14 bit, Multiturn 13 bit ST / 12 bit MT

X 700 - SSI

## Part number

### Singleturn

X 700. **A** **1** **12** **02**

**Connection**  
12 Cable 2 m, axial

**Voltage supply / signals**  
0 10...30 VDC / gray code 13 bit  
2 10...30 VDC / binary code 13 bit  
4 10...30 VDC / gray code 14 bit  
5 10...30 VDC / binary code 14 bit

**Flange / Solid shaft**  
1 Clamping flange / ø10 mm, IP 67

**Design**  
A Singleturn

### Multiturn

X 700. **M** **1** **02**


**Connection**  
12 Cable 2 m, axial  
14 Cable 5 m, axial  
16 Cable 10 m, axial  
19 Cable 20 m, axial  
21 Cable 70 m, axial  
22 Cable 6 m, axial  
23 Cable 40 m, axial

**Voltage supply / signals**  
1 10...30 VDC / gray code 13 + 12 bit  
2 10...30 VDC / binary code 13 + 12 bit  
4 10...30 VDC / gray code 12 + 12 bit  
5 5 VDC / binary code 12 + 12 bit

**Flange / Solid shaft**  
1 Clamping flange / ø10 mm, IP 67

**Design**  
M Multiturn

## Data transfer



Clock frequency f	62.5...1500 kHz
Duty cycle of T	40...60 %
Delay time tv	150 ns
Monoflop time tm	26 µs + T/2
Clock interval tp	30 µs

# Absolute encoders - SSI

Ex approval Ex II 2D/2G (ATEX)

Optical single and multiturn encoders

Singleturn 14 bit, Multiturn 13 bit ST / 12 bit MT

## X 700 - SSI

Terminal significance	
UB	Encoder voltage supply.
GND	Encoder ground connection relating to UB.
Data+	Positive, serial data output of differential linedriver.
Data-	Negative, serial data output of differential linedriver.
Clock+	Positive SSI clock input. Clock+ together with clock- forms a current loop. A current of approx. 7 mA towards clock+ input means logic 1 in positive logic.
Clock-	Negative SSI clock input. Clock- together with clock+ forms a current loop. A current of approx. 7 mA towards clock- input means logic 0 in positive logic.
Zero setting	Input for setting a zero point anywhere within the programmed encoder resolution. The zero setting operation is triggered by a High impulse and has to be in line with the selected direction of rotation (UP/DOWN). Connect to GND after setting operation for maximum interference immunity. Impulse duration >100 ms.
$\overline{\text{DATAVALID}}$	Diagnostic output. An error warning is given at level Low. Important: Interferences must be drained by the downstream electronics.
$\overline{\text{DATAVALID MT}}$	Diagnostic output for monitoring the multiturn sensor voltage supply. Upon dropping below a defined voltage level the $\overline{\text{DV MT}}$ output is switched to Low.
$\overline{\text{UP/DOWN}}$	$\overline{\text{UP/DOWN}}$ counting direction input. This input is standard on High. $\overline{\text{UP/DOWN}}$ means ascending output data with clockwise shaft rotation when looking at flange. $\overline{\text{UP/DOWN}}$ -Low means ascending values with counterclockwise shaft rotation when looking at flange.

Terminal assignment	
Core colour	Assignment
brown	UB
white	GND
green	Clock+
grey	Data+
blue	Zero setting
pink	Data-
yellow	Clock-
black	$\overline{\text{DATAVALID}}$
red	$\overline{\text{UP/DOWN}}$
violet	$\overline{\text{DATAVALID MT}}$

Trigger level	
<b>SSI</b>	<b>Circuit</b>
SSI-Clock	Optocoupler
SSI-Data	Linedriver RS485

Control inputs	Input circuit
Input level High	>0.7 UB
Input level Low	<0.3 UB
Input resistance	10 k $\Omega$

Diagnostic outputs	Output circuit Push-pull circuit-proof
Output level High	>UB -3.5 V (I = -20 mA)
Output level Low	<0.5 V (I = 20 mA)
Load High / Low	<20 mA

# Absolute encoders - SSI


Ex approval Ex II 2D/2G (ATEX)

Optical single and multiturn encoders

Singleturn 14 bit, Multiturn 13 bit ST / 12 bit MT

X 700 - SSI

## Dimensions



# Absolute encoders - SSI

Ex approval Ex II 2D/2G (ATEX)

Optical single and multiturn encoders

Singleturn 14 bit, Multiturn 13 bit ST / 12 bit MT

X 700 - SSI

## Check list for EX-approval

In compliance with EU standards 94/9/EG for potentially explosive areas it is imperative that the present checklist is duly completed and that all pending questions relating to explosion protection and application are clarified.

Company: \_\_\_\_\_

Address: \_\_\_\_\_

Division: \_\_\_\_\_

In charge: \_\_\_\_\_

Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

e-mail: \_\_\_\_\_

Product name:	Version:	Resolution (ppr / code):	Supply voltage:

Kind of e-connection:	Length of cable (m):	Output circuit:	Special options:

### Responsibility

- Our customer will receive all relevant information to verify a correct application.
- Our customer has to clarify all relevant criterions and characteristics.
- The operator shall be responsible for not exceeding the maximum performance limits of our devices (see data sheet).

**Device utilization/application** (E.g.: Lacquering line, manufacturing tech., gas storing vessel etc.)

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

### Device group, device category and zone classification

<b>Device group</b>	please tick
Device group I	<input type="checkbox"/>
Device group II	<input type="checkbox"/>

<b>Category / Zone</b>	<b>Ex-atmosphere prevailing</b>	
Category 1 (= Zone 0/20)	... permanently, long-term or frequently	<input type="checkbox"/>
Category 2 (= Zone 1/21)	... only now and then	<input type="checkbox"/>
Category 3 (= Zone 2/22)	... rarely or seldom	<input type="checkbox"/>

<b>Zone classification</b>		
G (gases)	Zone 0, zone 1, zone 2	<input type="checkbox"/>
D (dusts)	Zone 20, zone 21, zone 22	<input type="checkbox"/>

# Absolute encoders - SSI

## Ex approval Ex II 2D/2G (ATEX)

### Optical single and multiturn encoders

#### Singleturn 14 bit, Multiturn 13 bit ST / 12 bit MT

X 700 - SSI

## Check list for EX-approval

### Ignition protection

please tick

Ex d	Flameproof (pressure-proof capsule)	<input type="checkbox"/>
Ex ia	Intrinsic safety	<input type="checkbox"/>
Ex ib	Intrinsic safety	<input type="checkbox"/>

### Gas explosion group

Gases are classified into explosion groups. Danger increases from group II A to II C. please tick

II A	Propane	<input type="checkbox"/>
II B	Ethylene	<input type="checkbox"/>
II C	Hydrogen, Acetylene	<input type="checkbox"/>

### Temperature classes and groups of explosion

Temperature class	Max. surface temperature of operating equipment (°C)	Max. ignition temperature of combustible substances (°C)	please tick
T1	450	> 450	void
T2	300	>300...< 450	void
T3	200	>200...< 300	void
<b>T4</b> (on request)	135	>135...< 200	<input type="checkbox"/>
T5	100	>100...< 135	void
<b>T6</b>	85	> 85...< 100	<input type="checkbox"/>

### Information on ambient and operating temperature

Expected operating temperature:	to be clarified
Field ambient temperature:	to be clarified

### Mechanical strain

Rotation speed (rpm)	
Axial shaft load (N)	
Radial shaft load (N)	
Ambient impacts (salt, lye, etc.)	

Date	Signature
------	-----------

Stamp:

Date	Release EExB / trained sales
------	------------------------------