

MS-I8


MS - Expansion unit

- 8 digital inputs
- 4 test outputs for sensor monitoring
- Connection to MS-1 master via MS-SC proprietary bus
- MS-SC connector included



Safety instructions

All the installation, connection and safety regulations, as per our technical information, have to be strictly adhered to.
The set-up of the products have to be made by skilled staff, only.
Repair exclusively made by di-soric.



TECHNICAL INFORMATION (typ.)	+20°C, 24 V DC
Safety level	SIL 3 (IEC 61508), SILCL 3 (IEC 62061), PL e - Cat. 4 (EN ISO 13849-1)
Mounting	rail fastening according to EN 50022-35 standard
Operating principle	Input expansion unit
Size	99 x 22.5 x 114.5 mm (Dimensions)
Safety inputs	8
Service voltage	19,2 ... 28,8 V DC
Test outputs	4
Display	LED for input / output status and failure diagnosis
Ambient temperature	-10 ... +55 °C
Protection class	IP 20 for housing, IP 2X for terminal blocks
Casing material	polyamide (with locking latch mounting made of metal)
Connection	removable terminal blocks, screw contacts
Communication	5-way high-speed bus 5.0
Scope of delivery	multi-language installation sheet, MS - Connector MS-SC