SAFEMASTER W

Emergency stop wireless system -Work wirelessly

In automated manufacturing systems, safety devices ensure that the operator does not come too close to the hazardous area during automatic operation, Frequently, however, operators must work in hazardous areas in special machine operating modes during reviews, programming, or maintenance. In such situations, the **wireless emergency stop system** from the **SAFEMASTER W** family by DOLD offers the safety you need. It is the wireless solution for mobile applications in extended or complex facilities with hazardous zones.

With the wireless emergency stop system, you can safely be closer to what's happening. Besides the safety function, the handheld transmitter has a button and switch which can be freely configured for user-specific control tasks for convenient operation. Independent of the user's location, it facilitates secure operation and makes it possible to switch off facilities in dangerous situations. It can be used universally, providing maximum mobility and safety.

An electronic key allows rights to be allocated to individuals. The optional design of the system with infrared transmitter and infrared receiver serves to securely (re)start machines from pre-defined start zones in the field of view.

Advantages and customer benefit

- Maximum mobility and flexibility with the highest level of security
- For security applications up to cat. 4 / PL e or SIL CL 3, TÜV certified
- Ergonomic handheld transmitter for fatigue-free work
- Comfortable one-handed operation
- Maximum freedom of movement due to the cordless design
- 2-stage push button with tactile switching points
- Clearly arranged control panel, can be configured individually
- Protection from accidentally pressing the button
- Quick charging and high capacity transmitter battery

DOLD

Wireless emergency stop system **Technical features** Safe transmission path User-friendly, compact handheld transmitter -For wireless safety module BI 5910 Comfortable, one-handed operation Available if desired with 4 freely configurable buttons or knobs for control functions With tactile switching points for the 2-stage button With label fields beside the buttons Protection from accidentally operating the buttons Quick charging and high capacity transmitter battery Wireless safety module BI 5910 Possible to quickly adjust frequency Optional belt or chest bag for the handheld transmitter Key safety-related data Performance Level (PL) e and category 4 in accordance with EN ISO 13849-1:2008 Safety Integrity Level (SIL 3) in accordance with IEC/EN 61508 Handheld transmitter RE 5910 **Order information** Standard type: BI 5910.22/00MF9 DC 24V Item number: 0059002 Standard type: RE 5910/001 Item number: 0060610 **Examples of** This example of application shows the wireless emergency Areas of application stop system SAFEMASTER W in combination with the safety application Extended mobile danger zones switch and key transfer system SAFEMASTER STS. If the Fully automated fork lifts handheld transmitter is removed from the station and started, Gantry cranes the wireless emergency stop and additional control functions Automated high-bay warehouses activate (1). After activating the wireless emergency stop, Robotic cells access to the safety door is granted by SAFEMASTER STS Automated assembly lines (2) as soon as dangerous movements (8) have been switched off. Maintenance door SAFEMASTER STS

Further information

SAFEMASTER W



www.dold.com

E. DOLD & SÖHNE KG P.O. Box 1251 • 78114 Furtwangen • Germany Tel. +49 7723 6540 • Fax +49 7723 654356 dold-relays@dold.com • www.dold.com

FE27 / 0146