

## Safety relay OA 5623

With 8 forcibly guided contacts  
monostable

**DOLD** 

In safety-critical applications in which relays with forcibly guided contacts (in accordance with DIN EN 61810-3) are used, a compact size and shape are especially important, as is a high level of switching reliability. In addition, this relay stands out for its good vibration and shock resistance.

The OA 5621 and OA 5622 safety relays have enjoyed great success on the market for many years. Now, our existing relay family with 4 and 6 poles is growing adding new designs. The **8-pin OA 5623 safety relay** responds to the need for more contacts in an even more compact design. With a short overall height of just 15.8 mm and a small base area, it can be easily installed in safety switching devices with only 22.5 mm width.

Reducing the coil voltage makes it possible to lower the holding power to a quarter of rated power. The relay is wash proof (RT III), has a temperature range of up to 75° C, and is available with contact materials of silver tin oxide (AgSnO<sub>2</sub>) and silver-nickel (AgNi), as well as hard gold plating.

### Advantages and customer benefit

- ▶ Compact size, short overall height 15.8 mm
- ▶ Optionally available with contact opening 1.0 mm in fault free condition
- ▶ Low rated and holding power
- ▶ Safe separation between all circuits;  
for applications at contamination level: 2; with rated insulation voltage 250 V
- ▶ Addition to the OA 5621 relay family (4 contacts) and OA 5622 (6 contacts) with 8 contacts
- ▶ Common pin arrangement for relays OA 5621, OA 5622 and OA 5623
- ▶ Wide temperature range
- ▶ Optionally available with offset pins for optimized spacing and a simpler layout design
- ▶ Wash-proof design

**Our experience. Your safety.**

# Safety relay OA 5623

Technical features	OA 5621	OA 5622	OA 5623
Overall height	▶ 15.5 mm	15.5 mm	15.8 mm
Base area	▶ 46.5 x 22 mm	55 x 22 mm	67 x 22 mm
Rated consumption	▶ 0.6 W	0.8 W	1.2 W
Switching current	▶ 10 mA to 8 A	10 mA to 8 A	10 mA to 8 A
Contacts	▶ 4 2NO/2NC; 3NO/1NC	6 3NO/3NC; 4NO/2NC; 5NO/1NC	8 7NO/1NC; 6NO/2NC; 5NO/3NC; 4NO/4NC;
Contact material	▶ AgSnO <sub>2</sub> , AgNi, AgNi + hard gold plating		
Temperature range	▶ - 40 ... + 80° C	- 40 ... + 80° C	- 40 ... + 75° C
Approvals	▶ cRUus, TÜV	cRUus, TÜV	cRUus, TÜV



OA 5621



OA 5622



OA 5623

**Order information**

The contact materials AgSnO<sub>2</sub>, AgNi and AgNi + hard gold plating are available. Double contacts are also available upon request. When used with our popular mini crown, currents from 10 mA to 8 A can be switched reliably. Since almost all coil voltages between 6 V and 110 V are available, you will receive a safety relay designed for your specific application.

**Please feel free to ask any questions you may have.**

**Areas of application**

- ▶ Railway and signaling technologies
- ▶ Automation
- ▶ Medical devices
- ▶ Radio and remote control technology
- ▶ Firing technology
- ▶ Process technology
- ▶ Elevator technology

The right relay for every safety-critical application. Safety relays from DOLD are available in a wide range of contact variations, shapes, and sizes. We also produce customer-specific designs.

And what can we do for you?

## Safety relays with high switching capacity



OA 5601




OA 5602



OA 5603



OA 5611



OA 5612

## Safety relays in compact design



OA 5642



OA 5643



OA 5644



OA 5667



OA 5669



OA 5670

## Further information

OA 5623

Start

[www.dold.com](http://www.dold.com)



**E. DOLD & SÖHNE KG**  
 P.O. Box 1251 • 78114 Furtwangen • Germany  
 Tel. +49 7723 6540 • Fax +49 7723 654356  
 dold-relays@dold.com • www.dold.com