

## Safety relays OA 5642/43/44

With forcibly guided contacts -  
only 10.3 mm height

**DOLD** 

In many safety-related applications where relays with forcibly guided contacts (in accordance with DIN EN 61810-3) are used special attention is paid to a compact design, apart from the high switching reliability.

With the new **safety relays OA 5642, OA 5643** and **OA 5644** DOLD provides an extremely flat relay range setting new standards. Only **10.3 mm in height**, these 2-, 3- and 4-pole relays are among the flattest safety relays on the market. They are ideal for the realisation of compact safety switching devices (only 15 mm in width) and for applications where little space in height is available. Besides compactness, the design of the relays also allows an arrangement of SMD components between board and relay.

For applications where the power consumption is critical, energy saving was particularly taken into account by nominal power values of only 0.4 W, 0.5 W and 0.65 W and a lowering of the holding power to about a third of the pickup power. The relay, which is wash-tight (RT III) and temperature-stable up to 85° C in its standard version, can be especially well processed in leadfree solder processes.

### Advantages and customer benefit

- ▶ Smallest height of 10.3 mm while requiring a minimum of area
- ▶ Low nominal and holding power
- ▶ Protective separation between all circuits;  
for applications with pollution severity 2; and design insulation voltage of 250 V
- ▶ Relay range with consistent connection pinning
- ▶ Contact combinations for your specific application (on request)
- ▶ Wide temperature range
- ▶ High resistance to shock and vibration
- ▶ Wash-tight
- ▶ Low weight

**Our experience. Your safety.**

# Safety relays OA 5642, OA 5643, OA 5644

Technical features	OA 5642	OA 5643	OA 5644
Height	▶ 10,3 mm	10,3 mm	10,3 mm
Area	▶ 26,6 x 25 mm	34,2 x 25 mm	41,7 x 25 mm
Nominal consumption	▶ 0,4 W	0,5 W	0,65 W
Breaking current	▶ 10 mA to 8 A	10 mA to 8 A	10 mA to 8 A
Contacts	▶ 2 1NO/1NC	3 2NO/1NC	4 2NO/2NC; 3NO/1NC
Contact material	▶ AgSnO <sub>2</sub> , AgNi, AgNi + hard gold plating		
Temperature range	▶ - 40 ... + 85° C		
Approvals	▶ cRUus, TÜV		



OA 5642



OA 5643



OA 5644

**Notes on ordering**

For all relay models, the contact materials AgSnO<sub>2</sub>, AgNi and AgNi + 5 µm hard gold plating are possible. In combination with the proven mini-crown, currents from 10 mA up to 8 A can be reliably switched. As almost all coil voltages between 6 V and 110 V are available, the customer can get a safety relay tailored to his specific application.


**Please ask us.**

**Applications**


- ▶ Railway technology and signalling
- ▶ Automation
- ▶ Medical devices
- ▶ Radio technology and telecontrol
- ▶ Firing technology
- ▶ Process technology
- ▶ Elevators and hoists

The right relay for each safety-related application. Safety relays by DOLD are available in a wide variety of contact versions and designs. Also in custom designs. What can we do for you?


**Safety relays with high switching capacity**




OA 5601




OA 5602



OA 5603




OA 5611




OA 5612


**Safety relays in compact design**




OA 5667




OA 5669



OA 5670



OA 5621



OA 5622

**Further information**

Start

[www.dold.com](http://www.dold.com)



**E. DOLD & SÖHNE KG**  
 P.O. Box 1251 • 78114 Furtwangen • Germany  
 Tel. +49 7723 6540 • Fax +49 7723 654356  
 dold-relays@dold.com • www.dold.com