




- According to DIN EN 61810-1, DIN EN 61810-3
- With forcibly guided contacts
- Clearance and creepage distances:
contact - contact $\geq 5,5$ mm
- Low rated power consumption and holding power
- High mechanical service life
- High temperature range
- High thermal continuous current
- Height: 15.8 mm

Applications

- Railway and signalling applications
- Automation
- Medical devices
- Radio- and telecontrol applications
- Fuel applications
- Process applications
- Elevator applications

Approvals and Markings



Technical Data

Relay type		OA 5623
1.0 Coil		
1.1 Nominal voltage	DC V	6, 12, 24, 48, 60, 110 (others on request)
1.2 Nominal consumption	W	approx. 1.2
1.11 Voltage range	U_N	0.8 ... 1.2
1.13 Holding Power (at 0.5 x U_N)	W	0.3
2.0 Contacts		
2.1 Contact arrangement		7 NO / 1 NC 6 NO / 2 NC 5 NO / 3 NC 4 NO / 4 NC
2.2 Contact material		AgSnO ₂ + 0.2 μ m Au; AgNi + 0.2 μ m Au, AgNi + 5 μ m Au
2.3 Rated insulation voltage	AC V	250
Switching voltage min./max	V	AC/DC 10 / DC 250, AC 400 (AC/DC 2 V / 60 V) ³⁾
2.4 Limiting continuous current I_{th}	A	7 x 8 ⁶⁾ (see Operating voltage limit curve)
Switching current min./max	A	10 mA ⁴⁾ / 8 (2 mA / 0,3 A) ³⁾
2.5 Switching power min./max	VA	0.1 ⁴⁾ / 2000 (10 mVA / 12 VA) ³⁾
Switching power min./max	W	0.1 ⁴⁾ / 200 (10 mW / 12 W) ³⁾
2.6 Switching capacity to IEC/EN 60947-5-1		
AC 15 ⁵⁾	AC V/A	NO: 250 / 3 NC: 250 / 2
AC 15 ²⁾	AC V/A	NO: 250 / 5 NC: 250 / 2
DC 13 ⁵⁾	DC V/A	NO: 24 / 2 NC: 24 / 2
DC 13 ⁵⁾ at 0.1 Hz	DC V/A	NO: 24 / 4 NC: 24 / 4
2.7 Electrical life		at 1 s On, 4 s Off (see contacts service life)
at AC 230 V, 8 A, $\cos\phi = 1$	switching cycles	$> 10^5$ AgNi
at DC 24 V 8 A ohmic	switching cycles	0.75×10^5 AgNi
2.8 Switching frequency max	switching cycles/s	10
2.9 Response time / Release time	ms	typically 16 / typically 8
2.10 Contact force	cN	≥ 8
2.14 Contact gap	mm	1.0 (> 0.5 ¹⁾)
3.0 Other		
3.1 Mechanical life	switching cycles	20×10^6
3.2 Temperature range	$^{\circ}$ C	- 40 ... + 80
3.3 Degree of protection, housing		Wash proof RT III
3.4 Test procedure		A (group mounting)
3.5 Vibration resistance		10 ... < 60 Hz, a = 0,35 mm IEC/EN 60068-2-6
Criteria: contact opening ≥ 10 μ s		60 ... 200 Hz, 5g (all contacts) IEC/EN 60068-2-6
3.6 Climate resistance		40 / 080 / 04 A / B / D IEC/EN 60068-1
3.7 Short circuit strength		1 kA / AC 250 V IEC/EN 60947-5-1 ^{2) 5)}
SCP/ Fuse		NO contact: 10 A gG/gL / NC contact: 6 A gG/gL IEC/EN 60269-1 ^{2) 5)}

¹⁾ Over entire service life, even when under fault and at 1.2 U_N

³⁾ Typical values for AgNi-contacts + 5 μ m Au

⁵⁾ Values for AgNi-contacts

²⁾ Values for AgSnO₂-contacts

⁴⁾ Typical values

⁶⁾ See notes


Technical Data

3.8	Insulation acc. to IEC 60664-1, EN 50178		
	Rated insulation voltage	AC V	250
	Pollution degree		2
	Oversvoltage category		III
	Test voltage		
	Contact-coil (1 min)	AC kV eff.	≥ 4
	Contact-contact (1min)	AC kV eff.	≥ 4
	between open contacts	AC kV eff.	≥ 1,5
	Transient voltage		
	Contact-coil (1.2 - 50 µs)	kV	≥ 6
	Clearance and creepage distance	mm	≥ 5.5
3.9	Weight	g	approx. 39.5
4.0 Packing unit			
4.1	on cardboard in slipcase	piece	15
4.2	in case package	piece	150
5.0 Solder method			
5.1	Solder method /-temperature /-duration	°C / s	Wafer soldering / 260 / 5


Design Versions

U _N (DCV)	Voltage range (DC V)	R _{Coil} at 20° C Ω±10%	OA 5623			
			.57	.58	.59	.63
			4S, 4Ö	5S, 3Ö	6S, 2Ö	7S, 1Ö
AgNi-contacts + 0,2µm Au						
6	4,8 ... 7,2	31	8001	8201	8401	8601
12	9,6 ... 14,4	120	8002	8202	8402	8602
24	19,2 ... 28,8	500	8003	8203	8403	8603
48	38,4 ... 57,6	2000	8004	8204	8404	8604
60	48,0 ... 72,0	2880	8005	8205	8405	8605
110	88,0 ... 132,0	10100	8006	8206	8406	8606
AgNi-contacts + 5 µm Au (goldplated contacts)						
6	4,8 ... 7,2	31	8101	8301	8501	8701
12	9,6 ... 14,4	120	8102	8302	8502	8702
24	19,2 ... 28,8	500	8103	8303	8503	8703
48	38,4 ... 57,6	2000	8104	8304	8504	8704
60	48,0 ... 72,0	2880	8105	8305	8505	8705
110	88,0 ... 132,0	10100	8106	8306	8506	8706
AgSnO ₂ -contacts +0,2 µm Au						
6	4,8 ... 7,2	31	8151	8351	8551	8751
12	9,6 ... 14,4	120	8152	8352	8552	8752
24	19,2 ... 28,8	500	8153	8353	8553	8753
48	38,4 ... 57,6	2000	8154	8354	8554	8754
60	48,0 ... 72,0	2880	8155	8355	8555	8755
110	88,0 ... 132,0	10100	8156	8356	8556	8756


Ordering Example




**On request
version with double contacts**




Operating voltage limit curve without influence through self-heating of surrounding components



Limit curve for arc-free operation (load limit curve)




Reduction factor for inductive loads




Electrical life


Pin configuration W1 / W5




Pin configuration W1
Drilling plan (solder side)




OA5623.57/___W1 4NO/4NC



OA5623.58/___W1 5NO/3NC




OA5623.59/___W1 6NO/2NC




OA5623.63/___W1 7NO/1NC

Pin configuration W5
Drilling plan (solder side)




OA5623.58/___W5 5NO/3NC




OA5623.63/___W5 7NO/1NC

Connection for basic grid dimensions 2.50 mm as well as 2.54 mm according to IEC/EN 60 097, IEC 60 326


Pin configuration W7 / W8




Pin configuration W7
Drilling plan (solder side)




OA5623.57/___W7 4NO/4NC



OA5623.58/___W7 5NO/3NC




OA5623.59/___W7 6NO/2NC




OA5623.63/___W7 7NO/1NC

Pin configuration W8
Drilling plan (solder side)




OA5623.58/___W8 5NO/3NC



OA5623.63/___W8 7NO/1NC

Connection for basic grid dimensions 2.50 mm as well as 2.54 mm according to IEC/EN 60 097, IEC 60 326



*) When using the maximum switching capacity it is recommended to open the relay at the indicated position.