

Technical data sheet · LÜTZE SUPERFLEX® N PVC

For medium to high requirements



PVC control cables · C-track compatible · unshielded

Identification	Type	SU N PVC 2×0,75
	Part-No.	100765
Use/Application/Characteristics		
Application	• Machine and device construction, transport and conveyor technology, HVAC technology • In dry and damp rooms • As a monitoring, measurement and control cable in continuously moving applications • For installation in energy chains with constant linear movement	
Characteristics	• Construction and material suitable for continuous movement application. • PVC Flame-retardant, self-extinguishing • Resistant to most oils, greases, acids and alkalis (see tech. information) • Silicone free • RoHS-compliant	
Construction		
Description	SUPERFLEX N PVC	
Number of conductors/cross-section	2×0.75	
Jacket material	Special PVC	
Jacket color	grey RAL 7001	
Outer Ø	5.4 mm	
Weight	4.4 kg/100 m	
Cu-Index	1.5 kg/100 m	

26.01.2017 – Subject to technical modification

Part-No. 100765

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · LÜTZE SUPERFLEX® N PVC

For medium to high requirements

Element 1

Element construction	2×0,75
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 6 DIN EN 13602 Superfinely stranded DIN VDE 0295
Conductor marking	black with white number print
Conductor insulation	Special PVC

overall construction

Overall stranding	Conductors stranded layers schlaglängenoptimiert Conductors twisted without mechanical stress
Overall wrapping	Non-woven material
Jacket characteristics	Flame-retardant self-extinguishing Oil resistant grease-resistant acid-resistant. alkali-resistant Silicone-free

Technical data

Rated voltage U_0/U	300/500 V
Test voltage type	AC 3000 V
Temperature range moving	-15 °C ... +80 °C
Temperature range fixed	-30 °C ... +80 °C
Minimum bending radius moving	10×D
Minimum bending radius fixed	4×D
Travel distance	≤15 m
Speed	5 m/s
Acceleration	10 m/s ²

Element 1

Element construction	2×0,75
Insulation resistance at 20°C	20.0 MΩ×km

Approvals/Standards

Conformity	CE RoHS
------------	------------

26.01.2017 – Subject to technical modification

Part-No. 100765

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · LÜTZE SUPERFLEX® N PVC

For medium to high requirements

Burning behavior	IEC 60332-2-2 DIN EN 60332-2-2 VDE 0482-332-2-2
------------------	---

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--

Symbols



26.01.2017 – Subject to technical modification

Part-No. 100765

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk