

Technical data sheet · LÜTZE ELECTRONIC LIYY

Unshielded electronic cable



PVC electronic cables · unshielded

Identification	Type	LIYY 6×0,5
	Part-No.	100918

Use/Application/Characteristics

Application	• In all areas of electronics, measuring, control and regulation technologies • In low voltage switchgears, communications engineering • In dry and damp rooms • For flexible application for free movement and without tensile loading
Characteristics	• PVC Flame-retardant, self-extinguishing • Resistant to most oils, greases, acids and alkalis • Silicone free • RoHS-compliant

Construction

Description	ELETRONIC LIYY
Number of conductors/cross-section	6×0.5
Jacket material	Special PVC
Jacket color	grey RAL 7001
Outer Ø	6.9 mm
Surface	adhesion-free matt
Separating agent	Talcum
Weight	6.5 kg/100 m

26.01.2017 – Subject to technical modification

Part-No. 100918

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE ELECTRONIC LiYY

Unshielded electronic cable

Cu-Index 2.9 kg/100 m

Element 1

Element construction	6×0,5
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 5 Finely stranded DIN VDE 0295 DIN EN 13602
Conductor marking	Colour coded
Conductor marking standard	DIN 47100
Conductor insulation	Special PVC

overall construction

Overall stranding	stranded layers
Jacket characteristics	Flame-retardant self-extinguishing Oil resistant grease-resistant acid-resistant. alkali-resistant Silicone-free

Technical data

Rated voltage U_0/U	500 V
Test voltage type	AC 2000 V
Temperature range moving	-5 °C ... +70 °C
Temperature range fixed	-30 °C ... +70 °C
Minimum bending radius moving	12×D
Minimum bending radius fixed	4×D

Element 1

Element construction	6×0,5
Insulation resistance at 20°C	20.0 MΩ×km
Operating capacitance Ader-Ader	120 pF/m

Approvals/Standards

Conformity	CE RoHS
Burning behavior	IEC 60332-1 DIN EN 60332-1-2 VDE 0482 322-1-2

26.01.2017 – Subject to technical modification

Part-No. 100918

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE ELECTRONIC LiYY

Unshielded electronic cable

General

Note

CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

Symbols



26.01.2017 – Subject to technical modification

Part-No. 100918

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY