

# Technical data sheet · LÜTZE ELECTRONIC LIYY

## Unshielded electronic cable



PVC electronic cables · unshielded

<b>Identification</b>	Type	LIYY 5×0,5
	Part-No.	101052

### Use/Application/Characteristics

Application	<ul style="list-style-type: none"> <li>• In all areas of electronics, measuring, control and regulation technologies</li> <li>• In low voltage switchgears, communications engineering</li> <li>• In dry and damp rooms</li> <li>• For flexible application for free movement and without tensile loading</li> </ul>
Characteristics	<ul style="list-style-type: none"> <li>• PVC Flame-retardant, self-extinguishing</li> <li>• Resistant to most oils, greases, acids and alkalis</li> <li>• Silicone free</li> <li>• RoHS-compliant</li> </ul>

### Construction

Description	ELETRONIC LIYY
Number of conductors/cross-section	5×0.5
Jacket material	Special PVC
Jacket color	grey RAL 7001
Outer Ø	6.1 mm
Surface	adhesion-free matt
Separating agent	Talcum
Weight	4.9 kg/100 m

26.01.2017 – Subject to technical modification

Part-No. 101052

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE ELECTRONIC LIYY

## Unshielded electronic cable

---

Cu-Index 2.4 kg/100 m

### Element 1

Element construction 5×0,5  
Conductor CU-wire bare  
Conductor category IEC 60228, Class 5  
Finely stranded DIN VDE 0295  
DIN EN 13602  
Conductor marking Colour coded  
Conductor marking standard DIN 47100  
Conductor insulation Special PVC

### overall construction

Overall stranding stranded layers  
Jacket characteristics Flame-retardant  
self-extinguishing  
Oil resistant  
grease-resistant  
acid-resistant.  
alkali-resistant  
Silicone-free

---

### Technical data

Rated voltage  $U_0/U$  500 V  
Test voltage type AC 2000 V  
Temperature range moving -5 °C ... +70 °C  
Temperature range fixed -30 °C ... +70 °C  
Minimum bending radius moving 12×D  
Minimum bending radius fixed 4×D

### Element 1

Element construction 5×0,5  
Insulation resistance at 20°C 20.0 MΩ×km  
Operating capacitance Ader-Ader 120 pF/m

---

### Approvals/Standards

Conformity CE  
RoHS  
Burning behavior IEC 60332-1  
DIN EN 60332-1-2  
VDE 0482 322-1-2

26.01.2017 – Subject to technical modification

Part-No. 101052

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE ELECTRONIC LiYY

## Unshielded electronic cable

---


### General

Note

CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

---

### Symbols



26.01.2017 – Subject to technical modification

Part-No. 101052

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY