


# Technical data sheet · LÜTZE ELECTRONIC BUS (C) Profibus

## Bus cables for Profibus



<b>Identification</b>	Type	(1×2×AWG22/7+3×0,75)StC
	Part-No.	104224
<b>Use/Area of application</b>		
Application	<ul style="list-style-type: none"> <li>• For the cabling of industrial field bus systems like PROFIBUS DP, SINEC L2, F.I.P.</li> <li>• With stranded conductor for moving use without compulsory guide in the automation technology, transport and conveyor technology, machine tool manufacture</li> </ul>	
Properties	<ul style="list-style-type: none"> <li>• High active and passive interference resistance</li> <li>• Free from paint wetting disruptive substances (LABS-free), RoHS-compliant</li> </ul>	
<b>Technical data</b>		
Impedance	150 Ω ± 15 %	
Loop resistance	Braid AWG 22/7= 0.34 <sup>2</sup>	<110 Ω/km
Operating capacitance	<30 pF/m	
Voltage	Signal	250 V
	Supply	300 V
Test voltage	Signal	1500 V
	Supply	3000 V
Temperature range	moving	-5 °C to +70 °C
	fixed	-30 °C to +80 °C
Minimum bending radius	moving	D × 12
	fixed	D × 6
Fire performance	Flame-retardant according to VDE 0482 T. 265-2-1; IEC 60332-1	

12.12.2012 – Subject to technical modification

Part-No. 104224

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk

# Technical data sheet · LÜTZE ELECTRONIC BUS (C) Profibus

---

Number of strands/cross-section	(1×2×0.64/AWG22/7+3×0.75)StC
Outer-Ø	10.7 approx. mm
Weight	14.4 kg/100 m
Cu-Index	5.7 kg/100 m

---

## Design

---

Strand colours	red, green blue, black greenyellow
Conductor structure	Bare copper wire
Cable structure	Braid according to AWG Braid AWG22/7 $0.34^2 = 0.75 \text{ mm } \varnothing$
Conductor insulation	Conductor insulation special polyolefin
Ground conductor	green/yellow according to DIN EN 50334
Stranding	Stranding with filler
Static shield	ST static shield
Overall shield	Meshwork from tinned copper wire braid, optical covering $\geq 80 \%$
Outer jacket	Jacket special thermoplast, matt, adhesion-free surface
Jacket colour	violet RAL 4001

---

## General

---

Note	CE These products are in conformity with the EU Low Voltage Directive 2006/95/EC
------	--

---

## Logo



12.12.2012 – Subject to technical modification

Part-No. 104224

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY