

Technical data sheet - LÜTZE ELECTRONIC BUS (C) Profibus



Bus cables for Profibus

Identification	Type	(1×2×0,64/AWG22/7+3×0,75)StC UR
	Part-No.	104274

Use/Area of application

Application	<ul style="list-style-type: none"> • For the cabling of industrial field bus systems like PROFIBUS DP, SINEC L2, F.I.P. • With solid conductor AWG22/1 for hard wiring or with stranded conductor for moving use without compulsory guide in the automation technology, transport and conveyor technology, machine tool manufacture
Properties	<ul style="list-style-type: none"> • High active and passive interference resistance • Free from paint wetting disruptive substances (LABS-free), RoHS-compliant

Technical data

Impedance	150 Ω ± 15 %	
Loop resistance	Braid AWG 22/7= 0.34 ²	<110 Ω/km
Operating capacitance	< 30 pF/m	
Voltage	Signal	250 V
	Supply	300 V
Test voltage	Signal	1500 V
	Supply	3000 V
Temperature range	moving	-5 °C to +70 °C
	fixed	-30 °C to +80 °C
Minimum bending radius	moving	D × 12
	fixed	D × 6

22.06.2010 – Subject to technical modification

Part-No. 104274

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



Systematic Technology

Technical data sheet - LÜTZE ELECTRONIC BUS (C) Profibus

Burning behaviour	Flame-retardant according to VDE 0482 part 265-2; IEC 60332-1; UL 1581 section VW-1 Flame-Test; CSA FT 1
Number of strands/cross-section	(1×2×0,64/AWG22/7+3×0,75)StC UR
Outer-∅	11.4 approx. mm
Weight	14.4 kg/100 m
Cu-Index	6.5 kg/100 m

Design

Strand colours	red, green blue, black greenyellow
Conductor structure	Bare copper wire
Cable structure	Braid according to AWG or DIN, solid wire according to DIN Braid AWG24/19 0,24 ² = 0,64 mm ∅
Conductor insulation	Conductor insulation special polyolefin
Ground conductor	green/yellow according to DIN EN 50334
Stranding	Stranding with filler
Static shield	ST static shield
Overall shield	Galvanised copper wire braid, optical coverage ≥ 85 %
Jacket colour	violet RAL 4001

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2006/95/EC
------	--

Logo



22.06.2010 – Subject to technical modification

Part-No. 104274

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



Systematic Technology