


Technical data sheet · LÜTZE SUPERFLEX[®] ETHERNET (C) PUR

For highest requirements



PUR Bus cables · ETHERNET · C-track compatible

Identification	Type	SU BUS(C)P ET(4×2×AWG24/19)C Cat.5e
	Part-No.	104337

Use/Application/Characteristics

Application	<ul style="list-style-type: none"> • For the cabling of industrial field bus systems with the globally accepted TCP/IP protocol • For continuous flexible use e.g. in c-tracks or free movement in the automation technology, transport and conveyor technology, machine tool manufacture
Characteristics	<ul style="list-style-type: none"> • High active and passive interference resistance (EMC) • Silicone free • Halogen free • RoHS-compliant

Construction

Description	SUPERFLEX Ethernet (C) PUR
Number of conductors/cross-section	(4×2×AWG24/19)
Jacket material	PUR
Jacket color	green RAL 6018
Outer Ø	7.8 mm
Outer Ø	0.307 inches
Surface	adhesion-free matt

28.04.2017 – Subject to technical modification

Part-No. 104337

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SUPERFLEX[®] ETHERNET (C) PUR

For highest requirements

Weight	8.5 kg/100 m
Weight	46 Lbs/Mft
Cu-Index	4.4 kg/100 m
Cu-Index	37 Lbs/Mft

Element 1

Element construction	(4×2×AWG24/19)
Conductor	AWG conductor CU-wire bare
Conductor marking	white/blue blue white/orange orange white/green green white/brown brown
Conductor insulation	Special Polyolefin

overall construction

Overall stranding	stranded layers
Overall shield	Braid shield Tinned copper wires optical cover approx. 85%
Jacket characteristics	Flame-retardant Silicone-free Halogen free

Technical data

Rated voltage UL	300 V
Test voltage type	AC 1500 V
Temperature range moving	-30 °C ... +70 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	12×D
Minimum bending radius fixed	6×D

Element 1

Element construction	(4×2×AWG24/19)
Operating capacitance Ader-Ader	48 pF/m
Loop resistance	159.5 mΩ/m
Impedance	100 Ω

28.04.2017 – Subject to technical modification

Part-No. 104337

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SUPERFLEX® ETHERNET (C) PUR

For highest requirements

Approvals/Standards

Approvals	cURus
UL style	AWM 21198
Conformity	CE RoHS REACH
Burning behavior according to	IEC 60332-1 DIN EN 60332-1-2 VDE 0482 322-1-2 UL 1581 Part VW-1 Flame Test UL FT1
Halogen free according to	DIN EN 60754-1 IEC 60754-1

General

Note	Note on laying PVC C-track cables in chapter 2 of the catalogue TK1. Bus cables for robot applications see chapter on robot cables.
Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

Symbols



28.04.2017 – Subject to technical modification

Part-No. 104337

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY