Technical data sheet · LÜTZE ELECTRONIC LiYY
Unshielded electronic cable

PVC electronic cables · unshielded

Identification	Type	LIYY 3×0,25
	Part-No.	110070

Use/Application/Characteristics	
Application	• In all areas of electronics, measuring, control and regulation technologies • In low voltage switchgears, communications engineering • In dry and damp rooms • For flexible application for free movement and without tensile loading
Characteristics	• PVC Flame-retardant, self-extinguishing • Resistant to most oils, greases, acids and alkalis • Silicone free • RoHS-compliant

Construction	
Description	ELETRONIC LiYY
Number of conductors/cross-section	3×0.25
Jacket material	Special PVC
Jacket color	grey RAL 7001
Outer ∅	4 mm
Surface	adhesion-free matt
Separating agent	Talcum
Weight	2.9 kg/100 m

USA: LUTZE INC.
13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.
Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

SYSTEMATIC TECHNOLOGY

Cu-Index	0.7 kg/100 m

Element 1

Element construction	3×0,25
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 5 Finely stranded DIN VDE 0295 DIN EN 13602
Conductor marking	Colour coded
Conductor marking standard	DIN 47100
Conductor insulation	Special PVC

overall construction

Overall stranding	stranded layers
Jacket characteristics	Flame-retardant self-extinguishing Oil resistant grease-resistant acid-resistant. alkali-resistant Silicone-free

Technical data

Rated voltage U_0/U	300 V
Test voltage type	AC 1200 V
Temperature range moving	-5 °C … +70 °C
Temperature range fixed	-30 °C … +70 °C
Minimum bending radius moving	12×D
Minimum bending radius fixed	4×D

Element 1

Element construction	3×0,25
Insulation resistance at 20°C	20.0 MΩ×km
Operating capacitance Ader-Ader	120 pF/m

Approvals/Standards

Conformity	CE RoHS
Burning behavior	IEC 60332-1 DIN EN 60332-1-2 VDE 0482 322-1-2

USA: LUTZE INC.
13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.
Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE ELECTRONIC LiYY
Unshielded electronic cable

General	
Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

Symbols

CE

USA: LUTZE INC.
13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.
Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

SYSTEMATIC TECHNOLOGY