

Technical data sheet · Cablefix

Bus flange (B/V)

Cable fittings and accessories



Identification	Type	CABLEFIX B/V
	Part-No.	600320
Use/Application/Characteristics		
Application	Cablefix flanges are used to introduce cables and wires into a housing. They are used in light to medium-weight machine and plant construction.	
Characteristics	<ul style="list-style-type: none">• With the dovetail guide, the Cablefix flanges can be lined up with each other. This means that various flange combinations can be realized to suit specific requirements.• Flanges can be used to suit specific requirements• The integrated strain relief closes automatically when the cables and wires are pushed through.• An integrated formed rubber part seals off the cables and wires by means of sealing lips.• For troubleshooting, maintenance or retrofitting, the individual cables can be easily loosened from the spring clamp using a screwdriver and replaced.• Unused inputs can be closed off using the plugs supplied with the product.• Resistant to fuels, mineral oils, greases, alkalis• Halogen- and silicone-free.	
Technical data		
Dimensions (w × h × d)	50 × 50 × 11.5 mm	
Cut-out (B×H)	46 × 46 mm	
Sheet thickness	3 mm	

28.01.2017 – Subject to technical modification

Part-No. 600320

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · Cablefix

Bus flange (B/V)

Burning behavior	UL 94 V2
Temperature range	-30 °C ... +70 °C
Protection class	IP55


Construction

Description	CABLEFIX B/V
Material	PA 6.6
Material seal	TPE
Material plug	PA 6
Bolt material	Galvanised steel
Material characteristics	fuel-resistant mineral oil-resistant grease-resistant alkali-resistant Halogen free Silicone-free

General

PU	5 Quantity
Note	Note: 50 mm must be allotted for each flange mounted side by side.

Dimensions



28.01.2017 – Subject to technical modification

Part-No. 600320

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk