



Identification	Type	LCR-I-100-2U-24-240
	Part-No.	750635
Description	Current monitoring 1-phase, AC-DC 5 A	
Time range		
Switch-on delay	300 ms	
Switch-off delay	0.1 – 10 s, adjustable	
Start-up suppression, settable	0 – 10 s	
Status indication		
Supply status	LED green	
Output relay status	LED yellow	
Status under/over-current	LED red	
Trigger delay status	LED red flashing	
Housing		
Dimensions (w × h × d)	45.0 × 67.0 × 76.0 mm	
Colour of the housing	light grey	
Housing material	PA 6.6 V0	
Protection class	IP20	
Connection device	Screwed terminal	

25.08.2017 – Subject to technical modification

Part-No. 750635

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA
 Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223
 www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
 Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU
 Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2
 www.lutze.com · sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · Interface Technology

Connection cross-section	AWG 20 – AWG 13
Connection cross-section	0.5 – 2.5 mm ² with AE
Installation position	any
Weight	0.070 kg/piece
Approvals	cULus

Supply circuit

Rated voltage range	AC/DC 24 V – 240 V
Tolerance	AC: -15 %/+10 %, DC: -30 %/+30 %
Rated frequency	16,6 – 400 Hz
Power consumption	0.40 W/0.25 VA @ 24 V, 0.50 W/0.9 VA @ 230 V
Operating time	100 % ED
Bridging time	<20 ms
Recovery time	>500 ms
Voltage drop	≥6 V

Output circuit

Number of channels	2
Switching element	Relays
Contact type	Change over contact
Measurement voltage	AC 250 V (IEC 60947-1)
Switching voltage	AC 400 V
Switching current max.	AC-1: 8A/250V, AC-15: 1.5A/240V(B300), DC-12: 8A/24V, DC-13: 0.1A/250V
Protection device	8 A, quick-acting
Mechanical service life	30 × 10 ⁶ (1000 VA)
Electrical service life	1 × 10 ⁵ (1000 VA) (AC-1)
Switching frequency	6/min with load

Accuracy

Basic accuracy	≤2.5 % (2.0 % @ 50/60 Hz)
Tolerance of setting	≤5 % (end of scale)
Repeat accuracy	≤1 %
Moisture influence	3 % on basic accuracy (>85 % air humidity)
Temperature error	≤0.04 %/°C

Measuring circuit

Measuring variable	Current 1-phase, current transformer
Measuring range	AC/DC 100 A
Measuring procedure	Real effective value

25.08.2017 – Subject to technical modification

Part-No. 750635

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223
www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2
www.lutze.com · sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


Technical data sheet · Interface Technology

Monitored functions	Under-current, over-current, under/over-current under/over-current with separated relay outputs (MM) Maximum monitoring (2Max) Error memory can be activated (+L)
Switching threshold min.	5 % – 95 %
Switching threshold max.	10 % – 100 %
Hysteresis	1 %


Environmental conditions

Temperature range	-25 °C ... +60 °C
Storage temperature range	-40 °C ... +70 °C
Relative air humidity	5 % to 95 % acc. IEC 60721-3-3 Class 3K3
Vibration resistance	2 – 13.2 Hz 1 mm 13.2 – 100 Hz 7 m/s ²
Impact resistance	15 g 11 ms acc. IEC 60068-2-27

Dimensions



PIN assignment



25.08.2017 – Subject to technical modification

Part-No. 750635

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223

www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2

www.lutze.com · sales.gb@lutze.co.uk