



<b>Identification</b>	Type	Media Converter MC2030
	Part-No.	772030
<b>Description</b>	1×1000 Mbps RJ45, 1×1000 Mbps SC, Auto MDI/MDI-X auto crossover DC 12 V - DC 48 V, redundant Full/half duplex operation, autonegotiation, ESD 4 kV, surge 3 kV	
<b>Communication</b>	Standard IEEE 802.3, 802.3ab, 802.3u, 802.3x, 802.3z LAN 10 / 100 / 1000 Base-TX, 1000 Base-SX, 1000 Base-LX Cable length (segment) Ethernet: max. 100 m, Fibre: 550 m (multimode), 10,000 m (single mode) Transfer rate max. 1000 Mbit/s Connection technology (data) 1 × RJ45, 1 × SC, 6-pin connector Status display communication P1, P2, P-Fail, Fibre: Link/Activity, Ethernet: 1000 M, Link/Activity	
<b>Fibre-optic cables (Multi Mode)</b>	Wavelength 850 nm Tx Power -4 / -9.5 dBm Rx sensitivity -18 dBm Parameters 50/125 µm, 62.5/125 µm DIP switch Port Alarm, LFP	

25.08.2017 – Subject to technical modification

Part-No. 772030

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
 www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
 www.lutze.com • sales.gb@lutze.co.uk



## Technical data sheet · Ethernet

---

### Safety

---

ESD (Ethernet)	DD 4 kV
Surge (EFT for power)	DC 3 kV
Reverse voltage protection	Yes
Rated over load protection	0.9 A @ DC 12 V, resettable

---

### Monitoring

---

Power supply voltage monitoring	Relay, 1 normally open
Switching voltage	AC 120 V / DC 28 V
Switching current	1 A @ DC 24 V
Isolation voltage	DC 500 V

---

### General

---

Operation voltage range	DC 12–48 V, redundant
Power consumption	5.18 W
Protection class	IP20
Relative humidity (operation)	5% - 95% (non-condensing)
Relative humidity (storage)	0% - 95% (non-condensing)
Operation temperature range	-10 °C ... +60 °C
Storage temperature range	-40 °C ... +85 °C
Dimensions (w × h × d)	37.0 × 140.0 × 95.0 mm
Weight	0.600 kg/piece
Housing material	Metal
Mounting	DIN rail mountable TS35 (EN 60715)
Installation position	any
Connection device	Screw terminal plug-in 0.20 mm <sup>2</sup> – 2.5 mm <sup>2</sup>
Standards	UL 60950-1 CAN/CSA-C22.2 No. 60950 USA-FCC Part 15 CISPR22 EN 55011 EN 55022 Class A EN 61000-3-2/3 EN 55024 IEC 61000-4-2/3/4/5/6/8 EN 61000-6-2 IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6

25.08.2017 – Subject to technical modification

Part-No. 772030

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223  
www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2  
www.lutze.com · sales.gb@lutze.co.uk




SYSTEMATIC TECHNOLOGY

# Technical data sheet · Ethernet


Approvals	cULus CE FCC
PU	1 piece

**Note** For more information on LED definition, see the data sheet.

## Dimensions



## PIN assignment



25.08.2017 – Subject to technical modification

Part-No. 772030

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk

## Technical data sheet · Ethernet

### LED status

LED	Color	Description	
P1	Green	On	Power input 1 ist active
		Off	Power input 1 is inactive
P2	Green	On	Power input 2 ist active
		Off	Power input 2 is inactive
P-Fail	Red	On	Power input 1 or 2has failed
		Off	Power input 1 and 2 are both functional, or no power input
LNK/ACT (fiber port)	Green	On	Connected to network
		Flashing	Network is active
		Off	Not connected to network
1000M (RJ-45)	Yellow	On	Link to 1000M bps network
		Off	Not connected to network
LNK/ACT (RJ-45)	Green	On	Connected to network
		Flashing	Networking is active
		Off	Not connected to network

25.08.2017 – Subject to technical modification

Part-No. 772030

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223

www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2

www.lutze.com · sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY