



Identification	Type	Media Converter MC2032
	Part-No.	772032
Description	1×10/100 Mbps RJ45; 1×10/100 Mbps SC, Auto MDI/MDI-X auto crossover DC 12 V - DC 48 V, redundant Full/half duplex operation, autonegotiation, ESD 4 kV, surge 3 kV	
Communication	Standard IEEE 802.3, 802.3u, 802.3x LAN 10 / 100 Base-TX, 100 Base-FX Cable length (segment) Ethernet: max. 100 m, Fibre: 2000 m (multimode), 30,000 m (single mode) Transfer rate max. 100 Mbit/s Connection technology (data) 1 × RJ45, 1 × SC, 6-pin connector Status display communication P1, P2, P-Fail, Fibre: HDX/FDX, Link/Activity, Ethernet: 10/100 M, Link/Activity	
Fibre-optic cables (Multi Mode)	Wavelength 850 nm Tx Power -4 / -9.5 dBm Rx sensitivity -18 dBm Parameters 50/125 µm, 62.5/125 µm DIP switch Port / Power Alarm, LFP, Fibre: HDX/FDX, converter/switch	

25.08.2017 – Subject to technical modification

Part-No. 772032

USA: LUTZE INC.
 13330 South Ridge Drive • Charlotte, NC 28273, USA
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
 www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.
 Unit 3, Sandy Hill Park
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
 www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · Ethernet

Safety

ESD (Ethernet)	DD 4 kV
Surge (EFT for power)	DC 3 kV
Reverse voltage protection	Yes
Rated over load protection	0.9 A @ DC 12 V, resettable

Monitoring

Power supply voltage monitoring	Relay, 1 normally open
Switching voltage	AC 120 V / DC 28 V
Switching current	1 A @ DC 24 V
Isolation voltage	DC 500 V

General

Operation voltage range	DC 12–48 V, redundant
Power consumption	max. 5 W
Protection class	IP20
Relative humidity (operation)	5% - 95% (non-condensing)
Relative humidity (storage)	0% - 95% (non-condensing)
Operation temperature range	-10 °C ... +60 °C
Storage temperature range	-40 °C ... +85 °C
Dimensions (w × h × d)	37.0 × 140.0 × 95.0 mm
Weight	0.600 kg/piece
Housing material	Metal
Mounting	DIN rail mountable TS35 (EN 60715)
Installation position	any
Connection device	Screw terminal plug-in 0.20 mm ² – 2.5 mm ²
Standards	UL 60950-1 CAN/CSA-C22.2 No. 60950 USA-FCC Part 15 CISPR22 EN 55011 EN 55022 Class A EN 61000-3-2/3 EN 55024 IEC 61000-4-2/3/4/5/6/8 EN 61000-6-2 IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6

25.08.2017 – Subject to technical modification

Part-No. 772032

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223
www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2
www.lutze.com · sales.gb@lutze.co.uk




SYSTEMATIC TECHNOLOGY

Technical data sheet · Ethernet


Approvals	cULus CE FCC
PU	1 piece

Note For more information on LED definition, see the data sheet.

Dimensions



PIN assignment



25.08.2017 – Subject to technical modification

Part-No. 772032

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · Ethernet

LED status

LED	Color	Description	
P1	Green	On	Power input 1 ist active
		Off	Power input 1 is inactive
P2	Green	On	Power input 2 ist active
		Off	Power input 2 is inactive
P-Fail	Red	On	Power input 1 or 2has failed
		Off	Power input 1 and 2 are both functional, or no power input
HDX/FDX (fiber port)	Yellow	On	Ethernet port full duplex
		Off	Ethernet port half duplex or not connect to network
LNK/ACT (fiber port)	Green	On	Connected to network
		Flashing	Network is active
		Off	Not connected to network
10/100M (RJ-45)	Yellow	On	Link to 100M bps network
		Off	Link to 10M bps network
LNK/ACT (RJ-45)	Green	On	Connected to network
		Flashing	Networking is active
		Off	Not connected to network

25.08.2017 – Subject to technical modification

Part-No. 772032

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223

www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2

www.lutze.com · sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY