

Technical data sheet · LÜTZE SILFLEX® M (C) TPE POWER TRAY CABLE

Flexible Motor Cable for Allen-Bradley and other systems



TPE Motor cables · shielded · static

Identification	Type	SI M(C)TPE SE(4GA-WG2+(2×AWG16))UL 0,6/1KV OR
	Part-No.	A3170204

Use/Application/Characteristics

Application	<ul style="list-style-type: none"> • Shielded multi-conductor cable for motor and servo motor applications • Cable design for harsh industrial environments and operating conditions with high noise levels • Improved insulation design with additional conductor stress relief layer as a power distortion suppressant • Compliant with NFPA 79 for machine tool wiring • TC-ER for use with cable trays without conduit, which can reduce material and labor costs • UL Type 1000V Flexible Motor Supply Cable for Motor/Power applications • Dry, damp and wet locations
-------------	---

29.01.2017 – Subject to technical modification

Part-No. A3170204

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223

www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2

www.lutze.com · sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SILFLEX[®]M (C) TPE POWER TRAY CABLE

Flexible Motor Cable for Allen-Bradley and other systems

Characteristics	<ul style="list-style-type: none"> • Conductor stress relief layer prevents premature cable failure and reduces corona effects, increasing reliability and lifetime • Flexible design with Nylon for crush impact resistance per UL 1277 and easy installation • Very round cable with small diameter • Specially formulated TPE jacket for superior oil resistance per Oil Res I and II • Resistant to many mineral and vegetable based cutting oils • Non-wicking fillers • Sunlight resistant • Direct burial • UL Type TC-Exposed Run • Talc free and Silicone free
-----------------	---

Construction

Description	SILFLEX M (C) TPE
Number of conductors/cross-section	(4×AWG2+1×2×AWG16)
Jacket material	TPE
Jacket color	orange RAL 2003
Outer Ø	34.1 mm
Outer Ø	1.34 inches
Weight	1543 Lbs/Mft
Cu-Index	983 Lbs/Mft

Element 1

Element construction	AWG2/4C
Conductor construction	AWG 2 (665/30)
Conductor	AWG conductor CU-wire bare
Conductor category	feindrähtig
Conductor marking	brown black blue green/yellow
Conductor insulation	PVC/Nylon

Element 2

Element construction	AWG16/1TSP
Conductor construction	AWG 16
Conductor	AWG conductor CU-wire bare
Conductor category	feindrähtig
Conductor marking	black white

29.01.2017 – Subject to technical modification

Part-No. A3170204

USA: LUTZE INC.
13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.
Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SILFLEX[®]M (C) TPE POWER TRAY CABLE

Flexible Motor Cable for Allen-Bradley and other systems

Conductor insulation	PVC/Nylon
Stranding	Conductors stranded in pairs

overall construction

Overall shield	Braid shield Tinned copper wires optical cover approx. 85%
Jacket characteristics	Oil resistant mineral oil-resistant bio-oil-resistant Silicone-free

Technical data

Rated voltage	600 V UL TC 600 V UL MTW 1000 V WTTC 1000 V Flexible Motor Supply 600 V UL AWM 105 °C
Temperature range fixed	-40 °C ... +90 °C
Minimum bending radius fixed	6×D

Element 1

Element construction	AWG2/4C
----------------------	---------

Element 2

Element construction	AWG16/1TSP
----------------------	------------

Approvals/Standards

Approvals	cULus TC-ER UL MTW WTTC Class 1 Div. 2 per NEC Art. 336, 392, 501 cUL TC CIC FT4 UL 1277 cURus
Conformity	CE RoHS REACH
Oil resistant according to	Oil Res I Oil Res II

29.01.2017 – Subject to technical modification

Part-No. A3170204

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


Technical data sheet · LÜTZE SILFLEX[®]M (C) TPE POWER TRAY CABLE Flexible Motor Cable for Allen-Bradley and other systems

General

Note

CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

Symbols



29.01.2017 – Subject to technical modification

Part-No. A3170204

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY