

MIRO BT

Bluetooth Master/Slave Profinet

PROFINET

Bluetooth Master/Slave
100 Mbit/s

For connection cables please see chapter "Connection Technology"

[Link to Product](#)

Illustration



Product may differ from Image

Connections

Fieldbus	M12, D-coded
Supply voltage	M12, A-coded
General data	
Standards	approved in: BE, DK, DE, EE, FI, FR (restricted), GR, GB, IE, IS, IT, CA, LV, LT, LU, MT, NL, NO (without Spitzbergen), AT, PL, PT, SE, CH, SK, SI, ES, CZ, HU, US, CY
Housing	Metal black
Protection	IP65
Mounting method	screw fixing, M4
Dimensions H × W × D	125×86×41 mm
Temperature range	-20...+60 °C (storage temperature -40...+75 °C)
Technical Data	
Operating voltage	24 V DC
Operating current	max. 150 mA
Fieldbus	
Transfer rate	100 Mbit/s
Number of PROFINET Devices	max. 6
Bluetooth	
Frequency	2.4 GHz Bluetooth
	100 mW
	max. 4
	100 m
Reichweite Outdoor	300 m
	SMA (50 Ohm)
Commercial data	
country of origin	DE
customs tariff number	85364900
minimum order quantity	1