

IRA PLUG-IN RELAY

IN: 24 VAC - OUT: 250 VAC/DC / 7 A

4 NO/NC contacts 24 V AC

Relays with other voltage available on request.

Link to Product

Illustration




The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16

Murrelektronik GmbH | Falkenstraße 3,71570 Oppenweiler | Fon +49 (71 91) 47-0, Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com



stay connected



Product may differ from Image

General data	
Dimensions H × W × D	36×28×21 mm
Contact material	Ag Ni; Ag hv
Technical Data	
Switching voltage	max. 250 V AC/110 V DC
Switching current	max. 5 A
Power rating (voltage dependent)	max. 1250 VA/100 W
Max. power (W)	max. 1.4 VA/0.9 W
Switching time	18 ms
Commercial data	
country of origin	ΙΤ
customs tariff number	85364900
minimum order quantity	10

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16

Murrelektronik GmbH | Falkenstraße 3,71570 Oppenweiler | Fon +49 (71 91) 47-0, Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com