



MIRO 6.2 PLUGGABLE COMPL.MODULE OUTPUT RELAY

IN: 60VAC/DC - OUT: 250 VAC/DC / 6A

1 NO/NC contact
60 V AC/DC
Spring clamp terminals

[Link to Product](#)**Illustration**



Product may differ from Image

Approvals



Input

Connection voltage - current	60 V AC/DC (43.5...72 V AC/DC - 7 mA)
LED display	LED (green)

Utilization category

AC-12	6 A (24/110/230 V AC)
AC-15	3 A (24/110 V AC); 1.5 A (230 V AC)
DC-13	1 A (24 V DC); 0.2 A (110 V DC); 0.1 A (230 V DC)

General data

Test isolation voltage	250 V
Mech./ elect. life	10.000.000 switching cycles (NO) 30.000; (NC) 10.000, load dependent
Protection	IP20
Mounting method	DIN-rail mountable (EN 60715)
Dimensions H x W x D	93x6.2x75.6 mm
Temperature range	-25...+60 °C

Output

Switching voltage	max. 250 V AC/30 V DC
Switching current per output	max. 6 A
Min. load current	100 mA
Power rating (voltage dependent)	max. 1500 VA/180 W
Switching frequency	max. 10 Hz
Contact material	Ag Sn O2

Energize/release/contact bounce time 8/4/- ms

Commercial data

country of origin CN

customs tariff number 85364900

minimum order quantity 1