

stay connected

MODLINK MSDD CABLE ENTRY SYSTEM

KDP/R

round (M 63) Cable diameter (19) × 3...5 mm

For sale only in packing units

Link to Product

Illustration



Product may differ from Image

Approvals	
General data	
Dimensions $H \times W \times D$	34×71×71 mm
Cut-out	63.5×63.5
Mounting method	DIN-rail mounting or screw mounting via locknut (wall thickness 1.52.0 mm)
Temperature range	-30+70 °C
Technical Data	
Sealing range (cable Ø)	(1) × 35.5 mm, (5) × 59.2 mm
Protection	IP65
Housing	Polyamide

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16

Murrelektronik GmbH | Falkenstraße 3,71570 Oppenweiler | Fon +49 (71 91) 47-0, Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com



Commercial data		
country of origin	DE	
customs tariff number	39269097	
minimum order quantity	1	

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 05/16

Murrelektronik GmbH | Falkenstraße 3,71570 Oppenweiler | Fon +49 (71 91) 47-0, Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com