




## Accessories for Rotary Sensors - Shaft couplings





Shaft coupling for 6 up to 10 mm shaft diameters, backlash-free, double cardanic


share coupling for o up to rominis	nurr diameters, backia	sir nee, double cu	laane	
Material	Aluminun	n, PEEK		
Max. torque	1 Nm			
Operating temperature	-40 +16	0° C		
Max. displacements	radial 0.1	mm, angular 0.45	0	
Mounting	2 threade	d pins with intern	al hexagon	
Туре	ØA	ØB	P/N	
Z-106-G6	6	6	103910	
Z-106-G-6,35	6	6,35	103912	
Z-106-G10	6	10	103913	



Fork coupling for 4 mm shaft diameters, low backlash


Material	stainless steel, ground driving pin		
Mounting	1 fillister head screw M2 each with internal hexagon. Angle screwdriver SW 1.5 in delivery included.		
Туре	ØA	ØB	P/N
Z-103-G-3	3	3	005687





Material	stainless s	teel, ground drivi	ng pin
Mounting			n with internal hexagon delivery included.
Туре	ØA	ØB	P/N
Z-104-G-6	6	6	005690





Material	anodized aluminum, black, driving pin and spring hardened
Max. transferable torque	5 Ncm
Mounting	1 fillister head screw M3 each with intenal hexagon Angle screwdriver SW 2.5 in delivery included.
Туре	P/N
Z-105-G-6	005691




## Novotechnik U.S., Inc.

155 Northboro Road Southborough, MA 01772 Phone: 508-485-2244 Fax: 508-485-2430 Email: info@novotechnik.com

© 12/2011 Art.-Nr.: 062 756.1 Subject to changes

© 06/2015 Subject to changes.





Material	anodized aluminum, black	
	Spring phosphor bronze	
Max. transferable torque	24 Ncm	
Mounting	2 threaded pins with internal hexagon	
уре	P/N	
Z-110-G-10	005692	