




Accessories
Connector System M16




Pin assignment




M16x0.75 Mating female connector 5-pin, straight, with coupling nut, solder terminal, IP67, not shielded	
Connector housing	Plastic PA -40 °C... +95 °C
For wire gauge	4...6 mm, max. 0.75 mm²
Type EEM 33-70, P/N 005611	




Pin assignment




M16x0.75 Mating female connector 5-pin, straight, with coupling nut, solder terminal, IP40, shielded	
Connector housing	CuZn (Brass, nickel plated) -40 °C... +85 °C
For wire gauge	4...6 mm, max. 0.75 mm²
Type EEM 33-71, P/N 005612	




Pin assignment




M16x0.75 Mating female connector 5-pin, angled, with coupling nut, solder terminal, IP40, not shielded	
Connector housing	Plastic PA -40 °C... +85 °C
For wire gauge	6...8 mm, max. 0.75 mm²
Type EEM 33-72, P/N 005613	




Pin assignment



M16x0.75 Mating female connector 5-pin, straight, with coupling nut, solder terminal, IP67, shielded	
Connector housing	CuZn (Brass, nickel plated) -40 °C... +95 °C
For wire gauge	4...6 mm, PG7 max. 0.75 mm²
Type EEM 33-76, P/N 005614	



Pin assignment




M16x0.75 Mating female connector
5-pin, angled, with coupling nut,
solder terminal, IP67, shielded


Connector housing CuZn
(Brass, nickel plated)
-40 °C... +95 °C

For wire gauge 4...6 mm, PG 7
max. 0.75 mm²

Type EEM 33-77, P/N 005615



Pin assignment




M16x0.75 Mating female connector
6-pin, straight, with coupling nut,
solder terminal, IP68, shielded


Connector housing CuZn
(Brass, nickel plated)
-40 °C... +85 °C

For wire gauge 4...8 mm,
max. 0.75 mm²

Type EEM 33-82, P/N 005639



Pin assignment




M16x0.75 Mating female connector
6-pin, angled, with coupling nut,
solder terminal, IP67, shielded


Connector housing CuZn
(Brass, nickel plated)
-40 °C... +95 °C

For wire gauge 6...8 mm, PG 9
max. 0.75 mm²

Type EEM 33-94, P/N 005648



Pin assignment




M16x0.75 Mating female connector
7-pin, straight, with coupling nut,
solder terminal, IP67, shielded


Connector housing CuZn
(Brass, nickel plated)
-40 °C... +95 °C

For wire gauge 4...6 mm, PG 7
max. 0.75 mm²

Type EEM 33-78, P/N 005621



Pin assignment




M16x0.75 Mating female connector,
7-pin, straight, with coupling nut,
solder terminal, IP40, shielded


Connector housing CuZn
(Brass, nickel plated)
-40 °C... +85 °C

For wire gauge 4...6 mm,
max. 0.75 mm²;

Type EEM 33-79, P/N 005622



Pin assignment




M16x0.75 Mating female connector,
7-pin, angled, with coupling nut,
solder terminal, IP40, not shielded


Connector housing Plastic PA
-40 °C... +85 °C

For wire gauge 6...8 mm,
max. 0.75 mm²

Type EEM 33-80, P/N 005623



Pin assignment




M16x0.75 Mating female connector,
8-pin, straight, with coupling nut,
solder terminal, IP68, shielded


Connector housing CuZn
(Brass, nickel plated)
-40 °C... +85 °C

For wire gauge 4...8 mm,
max. 0.75 mm²

Type EEM 33-84, P/N 005627



Pin assignment



M16x0.75 Mating female connector,
8-pin, angled, with coupling nut,
solder terminal, IP67, shielded

Connector housing CuZn
(Brass, nickel plated)
-40 °C... +95 °C



For wire gauge 6...8 mm, PG 9
max. 0.75 mm²

Type EEM 33-85, P/N 005628


Novotechnik U.S., Inc.
155 Northboro Road
Southborough, MA 01772

Phone 508 485 2244
Fax 508 485 2430
info@novotechnik.com
www.novotechnik.com

© 09/2014
Subject to change.



Pin assignment




- 1 = white
- 2 = brown
- 3 = blue
- 4 = black
- 5 = grey
- 6 = green

M16x0.75 Mating female connector,
6-pin, straight, with molded cable,
2 m length, shielded, IP67, open ended

Connector housing	PUR
Cable sheath	PUR; Ø max. 6 mm, -5...+70 °C (moved) -20...+70 °C (fixed)
Wires	PVC, 6 x 0.25 mm ²
Type EEM 33-26, P/N 056126	

This coupling can be used in combination
with 5-pin M16 connectors. Than „pin 6/
green“ is open.

Pin assignment



- 1 = white
- 2 = brown
- 3 = blue
- 4 = black
- 5 = grey
- 6 = green

M16x0.75 Mating female connector 6-pin,
angled, with molded cable, 2 m length,
shielded, IP67, open ended

Connector housing	PUR
Cable sheath	PUR; Ø max. 6 mm, -5...+70 °C (moved) -20...+70 °C (fixed)
Wires	PVC, 6 x 0.25 mm ²
Type EEM 33-27, P/N 0056127	

This coupling can be used in combination
with 5-pin M16 connectors. Than „pin 6 /
green“ is open.

IP40 Protection class IP40 to
DIN EN 60529

IP67 Protection class IP67 to
DIN EN 60529

Very good Electromagnetic
Compatibility (EMC) and
shield systems

UL UL - approved

Note: The protection class is valid
only in locked position with its plugs.
The application of these products
in harsh environments must be
checked in particular cases.