

## Universal handheld measuring device with Datalogger



### Description

With this mobile device it is possible to measure and record precise measurements. A high measuring rate allows to use the device in very fast processes.

The measured values can also be transferred to a PC or printer via a serial interface or USB device.

The integrated sensor parameter store allows the display to handle up to 10 sensors. In practice this means that a service technician, for example, by simply plugging the sensor into a different slot and selecting the stored parameter set is able to change over to the next measuring point very quickly.

The integrated data logging functionality enables series of measurements to be recorded with a timestamp, for subsequent transfer to a PC for evaluation. The recording of measured values is started manually, time-controlled or by an external signal, as desired.

Various energy-saving modes allow an operating time of up to 30 hours in battery mode.

There is a built-in jack available for charging of the optionally available rechargeable battery.

### Features

- Accuracy 0,1% ± 1 digit
- Measuring rate 1,000 measurements/sec.
- 10 sensor parameters
- Data logger up to 15,000 values
- Min–Max value store
- Tare button
- PC interface (RS 232, USB)
- Optional printer connection
- Units displayed freely selectable
- Simple 4-button operation

### Applications

- Measurement and control devices
- Construction of apparatus
- Setting up machinery
- Construction of devices and special machinery
- Calibration service

### Specific Information

- Accessories:  
Cable, 3 metres (with jack plug <-> free cord) for triggerinput, transporting suitcase

Model: E3907

## Technical data

Model	E3907	Options
Output	4½ digit LCD display plus 3-digit unit display 0.1% of F.S. ± 1 digits USB, RS-232 port, 9600 ... 115 k <sup>2</sup> baud	
Input	±3,3mV/V; ±10V or 4 ... 20 mA or 0 ... ±5 V and tripper input 5 VDC, max. 20 mA (at mV/V) 12 VDC, max. 100 mA (at mA or V) 1 ... 1000 Hz, adjustable	
Setting	Menu-driven via keyboard, optional parameterizing software	
Power requirement/operating time	with batteries, 4xMignon 1600 mAh: >20 h with batteries: > 30 h	
Nominal temperature range	+15°C ... +35°C	
Service temperature range	5°C ... +45°C	
Storage temperature range	-10°C ... +70°C	
Protection type (acc. to EN 60 529/ IEC 529)	IP 40	
Electrical connection	Force transducer: SUB-D-15-socket; RS-232: Jack socket; Charger: Jack socket; Trigger input: Jack socket	
Housing	Plastic 100 x 200 x 40 mm	
Weight	400 g	
A/D conversion	16 bit microcontroller	
Bridge resistance	≥ 350 Ω-2 kΩ	
Tare / Zero adjustment	Automatic, Manual	
Display rate	5 updates/sec.	
Display	LCD 4-digit + 3-digit unit	
Storage space for sensor parameters	10	
Data logging modes	Manual, Start-time, Digital input	
Data logging intervals	1ms, 10ms; 100ms, 1s, 10s, 1min, 10min, 1 h	
Data logging storage	Max. 3,000 values internally, unlimited via PC mass storage device	
Maximum value store	Min / Max	
Electrical connection	15-pole plug	
Control function	100% signal	
Interface	RS 232C, USB	
Re-chargeable batteries	4x mignon 1.2V	
Plug-in mains adapter	Mains operation, Battery charging	
Printer	On interface RS232 or USB	On request
Digital input lead	3m flexible lead	On request
Interface cable	SUB-D 9-pole, USB	On request
Carry case		On request

Ordering code	
Desing/Model	Order No.
Base unit	EE3907X000001
Base unit with RS232-interface cable	EE3907X000002
Base unit with batteries and mains/ charger	EE3907X000003
Base unit with USB-interface cable	EE3907X000008
Base unit with RS232 interface cable, batteries and mains/ charger	EE3907X000005
Base unit with USB interface cable, batteries and mains/ charger	EE3907X000009

Subject to technical changes