



OPTIONAL EXTRAS

Motorized Pulley 165E

Specification

165E

Total stainless steel option AISI 304 range	Re-greasable labyrinth seals!	x
Food grade oil & grease - FDA & USDA recognized - available on request		x
Dust explosion proof Motorized Pulleys - ATEX 95 - Zone 22 - for applications handling of dusty grain etc. according to European Directive 94/9/EC.		On request!
Black rubber lagging - STANDARD specifications: - Smooth lagging - Hardness 60 ±5 Shore A - Diamond lagging - Hardness 60 ±5 Shore A		o
White smooth rubber lagging (FDA). Oil, fat & grease resistant		o
Single phase motors available on request		x
Electromagnetic brake (for 5.5 kW not available)		x
	Min. RL dimensions by (mm)	50
Mechanical backstop		x
Modified for vertical mounting		o
Modified for mounting between 5° - ≤90° - e.g. for magnetic separators		o
Insulation class F - Allowable ambient temperature: -25°C/+40°C		Std.
Insulation class H with synthetic oil - Allowable ambient temperature: -25°C/+40°C		x
SPECIAL motors for applications with NO belt contact		o
Low noise drives for noise sensitive areas		x
Parallel shell		x
Thermal protector		Std.
IP66/67 Compact stainless steel - AISI 304 or 316 range - terminal box		x
Straight or elbow connector with flying lead		x
Straight connector with flying lead - Stainless steel - AISI 304 range -		x
Shaft sealing system - degree of protection IP66/67 (EN60034-5)		Std.
Screened cables - a MUST together with Frequency Converters		x
Euro wide range voltage (3x220-240V / 380-415V 50 Hz) with +/-10% tolerance - DIN IEC 38 or (3x380-400V / 660-690V 50 Hz)		Std.
Special voltages - 50 and/or 60 Hz	Please specify!	x
CSA approved motors - available on request only!		x

X = Optional extras

o = Available as option with certain limitations. Please refer to Technical precautions pages 81-92!

Std. = Fitted as standard