



- Designed for use in retail, access control and time and attendance environment such as personal ID verification systems, security access control and time keeping systems etc.
- Can be easily attached to most computer keyboards or to any flat surface or integrated into the terminal devices
- Capable of reading many popular barcode symbologies through the reader slot.
- Reads barcode cards

SPECIFICATIONS:

Reads the following barcode symbologies:

Code 39 and full ASCII Code 39

Interleaved 2 of 5 Code , 2 of 5 Code ,EAN 8 and EAN 13

UPCE and UPCA ,Code 128,CODABAR,Code 93,Code 11

Electrical:

Supply Voltage:+5V DC @ up to 80mA depending on model.

Interface:

TTL / RS-232 / Keyboard Wedge / Tk2 Magstripe

Light Source:

Visible LED / Infrared

Dimensions, depending on model:

W90*H24*D23 mm -- 90mm without cover

W100*H29*D27 mm -- 100mm without cover

W100*H31*D32 mm -- 100mm with cover

W170*H42*D44 mm -- 170mm with cover

Environment:

Operating Temperature:0~55 Degree C

Storage Temperature:-20~60 Degree C

Relative Humidity:10~90%

Available Versions:

- | | |
|---|--|
| * BCR150B --90mm without cover, Red LED ,TTL output. | * BCR250B --100mm with cover, Red LED ,RS-232 interface. |
| * BCR151B --90mm without cover, Infrared ,TTL output. | * BCR250F --100mm with cover, Infrared ,RD-232 interface. |
| * BCR180 --100mm without cover, Red LED TTL output. | * BCR250KB --100mm with cover ,Red LED keyboard interface. |
| * BCR181 --100mm without cover, Infrared ,TTL output. | * BCR250KF --100mm with cover ,Infrared ,Keyboard interface. |
| * BCR181C --100mm with cover, Red LED ,TTL output. | * BCR410 --170mm with cover Red LED , RS-232 interface. |
| * BCR181C --100mm with cover, Infrared ,TTL output. | * BCR411 --170mm with cover Infrared ,RS-232 interface |
| * BCR200B --90mm w/o cover, Red LED ,MSR ABA TK2 output. | * BCR430 --170mm with cover Red LED , Keyboard interface. |
| * BCR200F --90mm w/o cover, Infrared ,MSR ABA TK2 output. | * BCR431 --170mm with cover ,Infrared ,Keyboard interface. |
-