

Automatic machine for cutting and bags filling of cotton pads . The machine is composed of:

- Cutting press
- Bags packer
- Pre-feeding rollers
- Unwinder unit

Production capacity for round pads

Mold	Pads/bag	Bags/min	Bags/h	Web width	Waste %
16 prints round Ø57 mm	50	48	2880	451 mm	30,4%
	60	48	2880		
	70	48	2880		
	80	48	2880		
	100	38	2280		
	120	32	1920		

Max mechanical speed 300 strokes/min
 Max working speed 280 strokes/min.
 Average production speed 240 strokes/min
 Bags Packer production 48 bags/min
 Storage bags capacity 2000 pcs



Production capacity for special shapes

Mold	Pads/Bag	Bags/min	Bags/h
4 prints Rectangular 90x110 mm	40	24	1440
	60	16	960
	80	12	720
6 prints Round Ø80 mm	40	24	1440
	60	16	960
	80	12	720
6 prints Square 75	40	24	1440
	60	16	960
	80	12	720
6 prints Oval 70x90 mm	40	24	1440
	60	16	960
	80	12	720



Dimensions

Lenght	4400mm
Width	2450mm
Height	3200mm
Weight	5550 kg
Electric power consumption	12 KW
Compressed air consumption	1500 lt/ min a 6 atm

