

# Encoders without bearings - absolute

Magnetic sensor bore max.  $\varnothing 6$  mm

Magnetic single- or multiturn encoders / kit 12 bit ST / 13 bit MT

## BMSK 42, BMMK 42 SSI - MAGRES



BMMK 42 SSI kit

### Features

- Mini encoder / kit single- or multiturn / SSI
- Magnetic sensing
- Resolution: singleturn 12 bit, multiturn 13 bit
- Housing  $\varnothing 42$  mm
- High resistance to shock and vibrations
- Reset input

### Technical data - electrical ratings

Voltage supply	5 VDC $\pm 10$ % 10...30 VDC
Consumption typ.	100 mA (5 VDC, w/o load) 50 mA (24 VDC, w/o load)
Sensing method	Magnetic
Initializing time typ.	170 ms after power on
Steps per turn	4096 / 12 bit
Output stages	SSI data: linedriver RS485
Absolute accuracy	$\pm 1^\circ$
Interface	SSI
Code	Gray or binary
Code sequence	CW: ascending values with clockwise sense of rotation; looking at flange
Inputs	SSI clock Zero setting input
Interference immunity	DIN EN 61000-6-2
Emitted interference	DIN EN 61000-6-3
Approval	UL approval / E217823
<b>BMSK 42</b>	
Function	Singleturn
<b>BMMK 42</b>	
Number of turns	8192 / 13 bit
Function	Multiturn

### Technical data - mechanical design

Size (flange)	$\varnothing 55$ mm
Shaft type	$\varnothing 6$ mm (magnet bore)
Protection DIN EN 60529	IP 67
Gap tolerance	$\leq 0.3$ mm axial $\leq 0.1$ mm radial
Operating temperature	-20...+85 °C
Operating speed	$\leq 12000$ rpm (mechanical) $\leq 6000$ rpm (electric)
Resistance	DIN EN 60068-2-6 Vibration 30 g, 10-2000 Hz DIN EN 60068-2-27 Shock 100 g, 6 ms
Relative humidity	95 %
Connection	Connector M12, 8-pin Cable
<b>BMSK 42</b>	
Materials	Housing: steel/aluminium Flange: aluminium
Weight approx.	50 g
<b>BMMK 42</b>	
Materials	Housing: steel Flange: aluminium
Weight approx.	300 g

# Encoders without bearings - absolute

Magnetic sensor bore max.  $\varnothing 6$  mm

Magnetic single- or multiturn encoders / kit 12 bit ST / 13 bit MT

## BMSK 42, BMMK 42 SSI - MAGRES

### Part number


#### Singleturn

BMSK 42L1		05C	12/00	06	
					Connection
					5 Cable radial
					B Connector M12, axial
					N Connector M12, radial
					Solid shaft
				06	$\varnothing 6$ mm magnet bore
					Resolution
			12/00		12 bit singleturn
					Voltage supply / signals
		05C			5 VDC / SSI
					Code
					G Gray code
					N Binary code

#### Multiturn

BMMK 42L1			12/13	06	
					Connection
					5 Cable radial
					B Connector M12, axial
					N Connector M12, radial
					Solid shaft
				06	$\varnothing 6$ mm magnet bore
					Resolution
			12/13		12/13 bit single-/multiturn
					Voltage supply / signals
		05C			5 VDC / SSI
		24C			10...30 VDC / SSI
					Code
					G Gray code
					N Binary code

### Data transfer



Clock frequency $f$	100...1000 kHz
Duty cycle of $T$	40...60 %
Delay time $t_v$	200 ns
Monoflop time $t_m$	$20 \mu s + T/2$

### Accessories

#### Connectors and cables

10146775	Female connector M12, 8-pin, straight, less cable
----------	---

#### Mounting accessories

10112433	Hexagon wrench 2 mm
----------	---------------------

# Encoders without bearings - absolute

Magnetic sensor bore max.  $\varnothing 6$  mm


Magnetic single- or multiturn encoders / kit 12 bit ST / 13 bit MT

## BMSK 42, BMMK 42 SSI - MAGRES

Terminal significance	
+Vs	Encoder supply voltage.
0 V	Encoder ground connection relating to +Vs.
Data+	Positive, serial data output of differential linedriver.
Data-	Negative, serial data output of differential linedriver.
Clock+	Positive SSI clock input. Clock+ together with Clock- forms a current loop. A current of approx. 7 mA towards Clock+ input means logic 1 in positive logic.
Clock-	Negative SSI clock input. Clock- together with Clock+ forms a current loop. A current of approx. 7 mA towards Clock- input means logic 0 in positive logic.
Zero	Input for setting a zero point anywhere within the encoder resolution. The zero setting operation is triggered by a Low impulse. Connect to +Vs after setting operation for maximum interference immunity. Impulse duration >2 ms.
Rot. direction	Ascending position values when looking at the flange and rotating the shaft clockwise.

Terminal assignment		
<b>Cable</b>		
for connection reference -5		
Core colour	Signals	Description
brown	+Vs	Supply voltage
white	0 V	Supply voltage
grey	Data+	Data signal
pink	Data-	Data signal
green	Clock+	Clock signal
yellow	Clock-	Clock signal
blue	Zero	Zero setting input
red	d.u.	do not use
Screen	connected to housing	
Cable data	8 x 0.14 mm <sup>2</sup>	

Connector M12 male		
for connection reference -N		
Connector	Signals	Description
Pin 1	0 V	Supply voltage
Pin 2	+Vs	Supply voltage
Pin 3	Clock+	Clock signal
Pin 4	Clock-	Clock signal
Pin 5	Data+	Data signal
Pin 6	Data-	Data signal
Pin 7	Zero	Zero setting input
Pin 8	d.u.	do not use



Trigger level	
Control inputs	Input circuit
Input level Low	<0,4 V (>2 ms)
Input level High	+Vs or open

# Encoders without bearings - absolute


Magnetic sensor bore max.  $\varnothing 6$  mm

Magnetic single- or multiturn encoders / kit 12 bit ST / 13 bit MT


## BMSK 42, BMMK 42 SSI - MAGRES

### Dimensions


BMSK 42 SSI cable radial




BMSK 42 SSI connector axial



BMSK 42 SSI connector M12 radial



BMMK 42 SSI cable radial



BMMK 42 SSI connector M12 radial

