



### features

- shielded process interface and power cable for Baumer *VisiLine*® IP cameras
- M12/8-pin female connector to open wires
- cable carrier compatible
- length 2,0 m

### mechanical data

|                                     |         |
|-------------------------------------|---------|
| material                            | PUR     |
| bending radius (static)             | 48 mm   |
| bending radius (moved installation) | 59 mm   |
| bending cycles                      | 4000000 |
| use in cable carriers               | yes     |
| cable length                        | 2 m     |
| weight                              | ≤ 114 g |

### electrical data

|                 |  |
|-----------------|--|
| shielding       | yes  |
| number of poles | 8  |
| connectors      | M12 female connector, screw lock<br>open wires |


### interface

|                |                   |
|----------------|-------------------|
| data interface | process interface |
|----------------|-------------------|

### environmental conditions

|                                |                        |
|--------------------------------|------------------------|
| flame resistance               | UL FT-2                |
| operation temperature (static) | -25 ... +80 °C         |
| protection class               | IP 65/67 (camera side) |

### pin assignment



| M12 | color | M12 | color |
|-----|-------|-----|-------|
| 1:  | WH    | 5:  | GY    |
| 2:  | BN    | 6:  | PK    |
| 3:  | GN    | 7:  | BU    |
| 4:  | YE    | 8:  | RD    |