

Speed switches

Mechanical centrifugal switch

FS 90



FS 90

Features

- Mechanical speed monitoring based on centrifugal force
- Fixed switching speed
- Switch with insulated make and break contact

Optional

- As integrated centrifugal switch type FSL for combination with encoders and/or tachogenerators

Technical data - electrical ratings

Switching accuracy	$\pm 4\%$ ($\Delta n = 2$ rpm/s); $\leq +20\%$ ($\Delta n = 1500$ rpm/s)
Switching deviation cw-ccw rotation	$\leq 3\%$
Switching hysteresis	$\approx 40\%$ of switching speed
Switching outputs	1 output, speed control
Output switching capacity	≤ 6 A / 230 VAC ≤ 1 A / 125 VDC
Minimum switching current	50 mA
Interference immunity	EN 61000-6-2
Emitted interference	EN 61000-6-3
Approval	CE

Technical data - mechanical design

Size (flange)	$\varnothing 87$ mm
Shaft type	$\varnothing 11$ mm solid shaft
Flange	EURO flange B10
Protection DIN EN 60529	IP 55
Speed (n)	$\leq 1.25 \cdot n_s$
Range of switching speed (ns)	850...4500 rpm ($\Delta n = 2$ rpm/s)
Operating torque	≤ 2 Ncm
Rotor moment of inertia	0.35 kgcm ²
Admitted shaft load	≤ 150 N axial ≤ 250 N radial
Materials	Housing: aluminium die-cast Shaft: stainless steel
Operating temperature	-30...+130 °C
Weight approx.	900 g
Connection	Terminal box

