



## features

- Camera Link® PCI Express x4 interface board
- Camera Link® cable MDR/MDR 3,0 m (2 pieces)
- power supply/flash cable Hirose 5,0 m
- international power supply 12V/2,0A, incl. adapter cable with Hirose/6-pin connector for HXC13
- software for Windows®
- camera not included

## interface card

article number	11014581
name	PCIe-CL microEnable IV AD4-CL
features	<ul style="list-style-type: none"> <li>▪ Base, Dual Base, Medium and Full configurations support</li> <li>▪ quad lane PCI Express interface</li> <li>▪ 2 x MDR26 interface</li> <li>▪ 256 MB image buffer</li> </ul>

## cable

article number	11008811
name	2x cable Camera Link MDR/MDR 3,0 m
features	<ul style="list-style-type: none"> <li>▪ Camera Link® interface cable with MDR connectors</li> <li>▪ length 3,0 m</li> </ul>

## process interface cable

article number	11008801
name	cable Hirose 6 wires, 5,0 m
features	<ul style="list-style-type: none"> <li>▪ Hirose process interface cable for HXC13 cameras</li> <li>▪ 6-pin</li> <li>▪ with open wires</li> <li>▪ length 5,0 m</li> </ul>

## power supply

article number	11046251
name	power supply Hirose
features	<ul style="list-style-type: none"> <li>▪ international power supply 12V/2.0A, incl. adapter cable with Hirose/6-pin connector for HXC13</li> <li>▪ length 5,0 m</li> <li>▪ adapter for EU, US, UK, AU and KR</li> </ul>

## software

Baumer GAPI	for Windows®
-------------	--------------