



features

- Camera Link® PCI Express x4 interface board, color calculation in HW
- power supply cable 5,0 m
- trigger/flash cable, 5,0 m
- Camera Link® cable MDR/MDR 5,0 m (2 pieces)
- international power supply 12V/2,0A, cable length 1,8 m
- software for Windows®
- camera not included

interface card

article number	11014581
name	PCIe-CL microEnable IV AD4-CL
features	<ul style="list-style-type: none"> ▪ Base, Dual Base, Medium and Full configurations support ▪ quad lane PCI Express interface ▪ 2 x MDR26 interface ▪ 256 MB image buffer

cable

article number	11046254
name	2x cable mini CL MDR/SDR 5,0 m
features	<ul style="list-style-type: none"> ▪ Camera Link® interface cable with MDR and SDR connectors to connect a Camera Link® camera to a framegrabber ▪ length 5,0 m

process interface cable

article number	11004523
name	cable 8 wires, 5,0 m (ESG 32FH0500)
features	<ul style="list-style-type: none"> ▪ cable ▪ M8 female connector ▪ 8-pin ▪ open wires at one side ▪ cable carrier compatible ▪ length 5,0 m

power cable

article number	10125607
name	shielded cable 3 wires, 5,0 m
features	<ul style="list-style-type: none"> ▪ shielded cable ▪ M8 female connector ▪ 3-pin ▪ open wires at one side ▪ cable carrier compatible ▪ length 5,0 m

power supply

article number	11044200
----------------	----------

power supply

name	power supply 12V/2,0A intern.
features	<ul style="list-style-type: none"> ▪ international power supply 12V/2.0A with M8/3-pin female connector ▪ length 1,8 m ▪ adapter for EU, US, UK, AU and KR

software

Baumer GAPI	for Windows®
-------------	--------------