



GIG VISION **GEN<i>i</i>CAM**



sensor information

sensor	CMOSIS CMV2000
type	2/3" global shutter CMOS
resolution	2048 × 1088 px
exposure time	0,02 ... 1000 ms
pixel size	5.5 × 5.5 μm

acquisition formats

image formats, frame rate max.	Full Frame, 2048 × 1088 px, max. 105,0 fps Binning 2×1, 1024 × 1088 px, max. 211,0 fps Subsampling 2×2, 1024 × 544 px, max. 421,0 fps
--------------------------------	---

pixel formats	Mono8 Mono10 Mono12
---------------	---------------------------

image pre-processing

analog controls	Gain (0 ... 12 dB) Offset (0 ... 255 LSB)
-----------------	--

color models	Mono
--------------	------

interfaces and connectors

data interface	Dual Gigabit Ethernet, Transfer rate 2000 Mbits/sec, Connector: 2 x 8P8C Modular Jack (RJ45), screwable type
----------------	--

process interface	M8 / 8 pins
-------------------	-------------

power supply	M8 / 3 pins
--------------	-------------

mechanical data

material	housing: aluminum
lens mount	C-mount (F-mount on request)
width	52 mm
height	52 mm
depth	55 mm
weight	≤ 232 g

electrical data

voltage supply	20 ... 30 V DC (external power supply)
range +Vs	38 ... 57 V DC (Power over Ethernet)

electrical data

power consumption	approx. 7,7 W @ 24 VDC and 105,0 fps approx. 8,9 W @ 48 VDC (PoE) and 105,0 fps
-------------------	--

environmental conditions

operating temperature	+5 ... +50 °C
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

dimension drawing

