

Accessories

Mounting accessories

Coupling CPS25



Features

- Separable, torsion proof coupling with small profile depth

Part number

11065915	Coupling CPS25 L=19 d1=04/d2=10
11065916	Coupling CPS25 L=19 d1=06/d2=06
11065917	Coupling CPS25 L=19 d1=06/d2=08
11065918	Coupling CPS25 L=19 d1=07/d2=10
11065919	Coupling CPS25 L=19 d1=08/d2=08
11065920	Coupling CPS25 L=19 d1=08/d2=10
11065921	Coupling CPS25 L=19 d1=09/d2=10
11065922	Coupling CPS25 L=19 d1=10/d2=06
11065923	Coupling CPS25 L=19 d1=10/d2=10
11065924	Coupling CPS25 L=19 d1=10/d2=11
11065925	Coupling CPS25 L=19 d1=10/d2=12
11065926	Coupling CPS25 L=19 d1=11/d2=06
11065927	Coupling CPS25 L=19 d1=11/d2=11
11065928	Coupling CPS25 L=19 d1=12/d2=06
11065929	Coupling CPS25 L=19 d1=12/d2=12

Technical data

Operating speed	≤13500 rpm
Torque	≤1 Nm
Moment of inertia	≤20 gcm ²
Radial offset	≤0.5 mm
Angular shift	≤1°
Length (L)	19 mm
Diameter (D)	25 mm
Diameter (d ₁ , d ₂)	6 to 12 mm
Mounting types	Clamp fastening
Operating temperature	-30...+80 °C
Assembly	Plug-in
Materials	Hub: aluminium Centre disc: plastic
Weight approx.	18 g

Suitable for

EIL580 - clamping flange, EIL580 - synchro flange,
EIL580P - clamping flange, EIL580P - synchro flange

Dimensions

