



Link GEN*i*CAM



sensor information

sensor	CMOSIS CMV12000
type	APS-C global shutter CMOS
resolution	4096 × 3072 px
exposure time	0,02 ... 1000 ms
pixel size	5.5 × 5.5 µm

acquisition formats

image formats, frame rate max.	Full Frame, 4096 × 3072 px, max. 63,0 fps Binning 2×2, 2048 × 1536 px, max. 63,0 fps Binning 1×2, 4096 × 1536 px, max. 63,0 fps Binning 2×1, 2048 × 3072 px, max. 63,0 fps
--------------------------------	---

pixel formats	Mono8 Mono10
---------------	-----------------

image pre-processing

analog controls	Gain (0 ... 12 dB) Offset (0 ... 63 LSB 10 Bit)
-----------------	--

color models	Mono
--------------	------

interfaces and connectors

data interface	Camera Link® Full, connector: 2 x Standard SDR26 (Mini CL)
process interface	M8 / 8 pins
power supply	M8 / 8 pins

mechanical data

material	housing: aluminum
lens mount	M58-mount (F-mount, M42, C-mount via adapter)
width	60 mm
height	60 mm
depth	47,95 mm
weight	≤ 235 g (M58-mount)

electrical data

voltage supply range +Vs	12 ... 24 V DC (external power supply) 38 ... 57 V (PoCL)
--------------------------	--

electrical data

power consumption	approx. 6,5 W @ 24 VDC approx. 6,5 W @ 12 VDC (PoCL)
-------------------	---

environmental conditions

operating temperature	+5 ... +65 °C
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

dimension drawing

