



**GIG** VISION **GEN<i>i</i>CAM**



### sensor information

sensor	CMOSIS CMV20000
type	35 mm global shutter CMOS
resolution	5120 × 3840 px
exposure time	0,19 ... 1000 ms
pixel size	6.4 × 6.4 μm

### acquisition formats

image formats, frame rate max.	Full Frame, 5120 × 3840 px, max. 16,0 fps
pixel formats	Mono8 Mono12

### image pre-processing

analog controls	Gain (0 ... 12 dB) Offset (0 ... 255 LSB 12 Bit)
color models	Mono
image pre-processing	VisualApplets 2.x

### interfaces and connectors

data interface	Gigabit Ethernet, Transfer rate 1000 Mbits/sec, Connector: 8P8C Modular Jack (RJ45), screwable type
process interface	M8 / 8 pins (2x)
power supply	M8 / 8 pins

### mechanical data

material	housing: aluminum
lens mount	M58-mount (F-mount, M42, C-mount via adapter)
width	60 mm
height	60 mm
depth	54,25 mm
weight	≤ 290 g (M58-mount)

### electrical data

voltage supply range +Vs	12 ... 24 V DC (external power supply) 36 ... 57 V DC (Power over Ethernet)
--------------------------	--

### electrical data

power consumption	approx. 6,5 W @ 24 VDC approx. 6,5 W @ 48 VDC (PoE)
-------------------	--

### environmental conditions

operating temperature	+5 ... +50 °C
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

### dimension drawing

