



GIG VISION **GEN<i>i</i>CAM**



sensor information

sensor	Sony ICX414
type	1.2" interline progressive scan CCD
resolution	656 × 494 px
exposure time	0,004 ... 60000 ms
pixel size	9.9 × 9.9 µm

acquisition formats

image formats, frame rate max.	Full Frame, 656 × 494 px, max. 93,0 fps Binning 2×2, 328 × 247 px, max. 176,0 fps Binning 1×2, 656 × 247 px, max. 176,0 fps Binning 2×1, 328 × 494 px, max. 93,0 fps
--------------------------------	---

pixel formats	Mono8 Mono12 Mono12 Packed
---------------	----------------------------------

image pre-processing

analog controls	Gain (0 ... 20 dB) Offset (0 ... 255 LSB 12 Bit)
-----------------	---

color models	Mono
--------------	------

interfaces and connectors

data interface	Gigabit Ethernet, Transfer rate 1000 Mbits/sec, Connector: 8P8C Modular Jack (RJ45), Screw lock type
process interface	M8 / 4 pins
power supply	M8 / 3 pins

mechanical data

material	housing: aluminum
lens mount	C-mount
width	36 mm
height	36 mm
depth	48 mm
weight	≤ 90 g

electrical data

voltage supply range +Vs	8 ... 30 V DC
--------------------------	---------------

electrical data

power consumption	approx. 4,0 W
-------------------	---------------

environmental conditions

operating temperature	+5 ... +50 °C
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

dimension drawing

