

Accessories

Connectors and cables

Female connector M23, 12-pin



Features

- Female connector M23 with screwable nut
- With or without cable (shielded) in different lengths
- Cable version: shield is placed onto the connector housing

Part number

Z 141.001	Female connector M23, 12-pin, without cable
Z 141.003	Female connector M23, 12-pin, 2 m cable
Z 141.005	Female connector M23, 12-pin, 5 m cable
Z 141.007	Female connector M23, 12-pin, 10 m cable
Z 141.M15	Female connector M23, 12-pin, 15 m cable
Z 141.M22	Female connector M23, 12-pin, 22 m cable

Suitable for

G0333, G0355, G0356, G110H, G110S, GI330, GI331, GI332, GI333, GI355, GI356, GI357

Technical data

Voltage supply	60 VDC
Core diameter	1.05 ±0.05 mm
Cable length	2 m, 5 m, 10 m, 15 m, 22 m (further length upon request)
Cable type	LiY(C)11Y 10x0.14 mm ² (shielded cable)
Bending radius	5 x cable diameter
Outer diameter	6 ±0.2 mm
Operating temperature	-40...+105 °C
Conductor resistance	<135 Ω/km (20 °C)
Material	Cable sheath: PUR black

Terminal assignment

Connector	Core colour
Pin 1	pink
Pin 2	blue
Pin 3	red
Pin 4	black
Pin 5	brown
Pin 6	green
Pin 7	–
Pin 8	grey
Pin 9	–
Pin 10	white/green
Pin 11	white
Pin 12	brown/green

Dimensions

