


OGU 005 P1K-TSSL Optical Label Sensor




- Metal casing
- Integrated electronic module
- Sensitivity adjustable
- High operating frequency
- Light switching
- Bright ring LED
- High protection class
- 5-year warranty



Safety instructions

The Instruments are not to be used for safety applications, in particular applications in which safety of persons depends on proper operation of the instruments.

These instruments shall exclusively be used by qualified personnel.



TECHNICAL INFORMATION (typ.)	+20°C, 24V DC
Operating principle	Optical
Evaluation	digital
Size	25 x 45 x 10 mm (Dimensions)
Design	fork
Fork opening	5 mm
Branch length	17 mm
Slot width	5,0 mm
Emitted light	Infrared, clocked
Service voltage	10 ... 35 V DC (Supply Class 2)
Internal power consumption	< 35 mA
Resolution	Ø 0,5 mm
Sensitivity adjustment	potentiometer
Switching output	pnp, 200 mA, NC
Switching hysteresis	< 0,2 mm
Voltage drop	2,5 V
Switching frequency	1.000 Hz
Reproducibility	0,01 mm
Ambient temperature	-10 ... +60 °C
Ambient light immunity	20 kLx
Insulation voltage endurance	500 V
Protection class	IP 67
Protection degree	III, operation on protective low voltage
Casing material	Aluminium black anodized

OGU 005 P1K-TSSL

Optical Label Sensor



TECHNICAL INFORMATION (typ.)		+20°C, 24V DC
Connection		Connector, M8, 3-poled
Connecting cable		TK ...