


OLVK 61 P3FK-TSSL/5000 Hz


Amplifier for plastic fiber optics

- DIN-rail mounting and lateral mounting holes
- Mountable side by side, 10 mm mounting grid
- 12-turn metal potentiometer with illuminated readout
- Scanning range up to 200 mm, operating range up to 1500 mm
- Version with functional reserve output
- Light/dark switching switchable



Safety instructions

The Instruments are not to be used for safety applications, in particular applications in which safety of persons depends on proper operation of the instruments.
These instruments shall exclusively be used by qualified personnel.



TECHNICAL INFORMATION (typ.)	+20°C, 24V DC
Amplifier for	Plastic fiber optics 2x2,2 mm
Evaluation	digital
Emitted light	Red, 680 nm, clocked
Service voltage	10 ... 30 V DC (Supply Class 2)
Internal power consumption	< 15 mA
Sensitivity adjustment	potentiometer
Switching output	pnp, 200 mA, NO/NC, switchable
Switching hysteresis	< 10 %
Voltage drop	< 2,0 V
Switching frequency	5.000 Hz
Response-/release time	0,1 ms / 0,1 ms
Ambient temperature	-25 ... +55 °C
Temperature drift	0,2 %/K
Ambient light immunity	10 kLx
Insulation voltage endurance	500 V
Protection class	IP 64
Casing material	plastics (PBT)
Connection	Connector, M8, 4-poled