


DCC 18 VL 20 NOK-IBSL Inductive Proximity Switch


- For food industry
- For seawater applications
- Large sensing range to steel and aluminium
- One-piece stainless steel housing
- Protection class IP 68 and IP 69K
- Metal plug
- Integrated amplifier
- Short-circuit protection
- Starting pulse suppression
- LED



Safety instructions

The Instruments are not to be used for safety applications, in particular applications in which safety of persons depends on proper operation of the instruments.

These instruments shall exclusively be used by qualified personnel.



| TECHNICAL INFORMATION (typ.) | | +20°C, 24V DC |
|------------------------------|--|--|
| Operating principle | | Inductive |
| Evaluation | | digital |
| Size | | M18 x 1 (thread) |
| Design | | screw |
| Mounting | | non-flush |
| Characteristics | | extremely high operating distance, up to 60 bar, All stainless steel housing |
| Operating distance | | 20 mm |
| Standardized measuring plate | | 60 x 60 x 1 mm |
| Service voltage | | 10 ... 35 V DC |
| Internal power consumption | | < 10 mA |
| Switching output | | npn, 200 mA, NC |
| Switching hysteresis | | < 15 % |
| Voltage drop | | < 2,0 V |
| Switching frequency | | 200 Hz |
| Ambient temperature | | -25 ... +85 °C |
| Insulation voltage endurance | | 500 V |
| Protection class | | IP 68, IP 69K |
| Casing material | | stainless steel (1.4435 / AISI 316L) |
| Connection | | Connector, M12, 4-poled |