

Technical Information

Proline Promag W 400

Electromagnetic flowmeter



The flowmeter with integrated web server and a sensor with EN ISO 12944 corrosion protection

Application

- The measuring principle is virtually independent of pressure, density, temperature and viscosity
- The specialist in the water and wastewater industry for the most demanding applications

Device properties

- International drinking water approvals
- Degree of protection IP68 (Type 6P enclosure)
- Approved for custody transfer to MI-001/OIML R49
- Transmitter housing made of durable polycarbonate
- Same housing concept for compact/remote version
- Integrated data logger: measured values monitoring

Your benefits

- For direct underground installation or permanent underwater use
- Secure, reliable long-term operation – robust and completely welded sensor
- Energy-saving flow measurement – no pressure loss due to cross-section constriction
- Maintenance-free – no moving parts
- Safe operation – no need to open the device due to display with touch control, background lighting
- Time-saving local operation without additional software and hardware – integrated web server
- Integrated verification – Heartbeat Technology™

Table of contents

Document information	4	Mechanical load	39
Symbols used	4	Electromagnetic compatibility (EMC)	40
Function and system design	4	Process	40
Measuring principle	4	Medium temperature range	40
Measuring system	6	Conductivity	40
Device architecture	7	Pressure-temperature ratings	40
Safety	7	Pressure tightness	43
Input	7	Flow limit	43
Measured variable	7	Pressure loss	43
Measuring range	7	System pressure	43
Operable flow range	9	Vibrations	43
Input signal	10	Custody transfer measurement	44
Output	10	Mechanical construction	44
Output signal	10	Design, dimensions	44
Signal on alarm	12	Weight	78
Low flow cut off	13	Measuring tube specification	90
Galvanic isolation	13	Materials	91
Protocol-specific data	13	Fitted electrodes	94
Power supply	18	Process connections	94
Terminal assignment	18	Surface roughness	94
Pin assignment, device plug	22	Operability	94
Supply voltage	22	Operating concept	94
Power consumption	23	Local operation	95
Current consumption	23	Remote operation	96
Power supply failure	23	Service interface	97
Electrical connection	23	Certificates and approvals	99
Potential equalization	27	CE mark	99
Terminals	29	C-Tick symbol	99
Cable entries	29	Drinking water approval	99
Cable specification	29	Certification PROFIBUS	99
Performance characteristics	31	Modbus RS485 certification	99
Reference operating conditions	31	EtherNet/IP certification	99
Maximum measured error	32	Measuring instrument approval	99
Repeatability	33	Other standards and guidelines	100
Influence of ambient temperature	33	Ordering information	100
Installation	33	Application packages	100
Mounting location	33	Cleaning	101
Orientation	34	Diagnostics functions	101
Inlet and outlet runs	35	Heartbeat Technology	101
Adapters	35	Accessories	101
Length of connecting cable	36	Device-specific accessories	101
Installing the wall-mount housing	37	Communication-specific accessories	102
Special mounting instructions	37	Service-specific accessories	102
Environment	38	System components	103
Ambient temperature range	38	Supplementary documentation	103
Storage temperature	39	Standard documentation	103
Atmosphere	39	Supplementary device-dependent documentation	104
Degree of protection	39		
Shock resistance	39		
Vibration resistance	39		

Registered trademarks 104

Document information

Symbols used

Electrical symbols

Symbol	Meaning	Symbol	Meaning
	Direct current		Alternating current
	Direct current and alternating current		Ground connection A grounded terminal which, as far as the operator is concerned, is grounded via a grounding system.
	Protective ground connection A terminal which must be connected to ground prior to establishing any other connections.		Equipotential connection A connection that has to be connected to the plant grounding system: This may be a potential equalization line or a star grounding system depending on national or company codes of practice.

Symbols for certain types of information

Symbol	Meaning
	Permitted Procedures, processes or actions that are permitted.
	Preferred Procedures, processes or actions that are preferred.
	Forbidden Procedures, processes or actions that are forbidden.
	Tip Indicates additional information.
	Reference to documentation
	Reference to page
	Reference to graphic
	Visual inspection


Symbols in graphics

Symbol	Meaning	Symbol	Meaning
1, 2, 3, ...	Item numbers	1, 2, 3, ...	Series of steps
A, B, C, ...	Views	A-A, B-B, C-C, ...	Sections
	Hazardous area		Safe area (non-hazardous area)
	Flow direction		

Function and system design

Measuring principle

Following *Faraday's law of magnetic induction*, a voltage is induced in a conductor moving through a magnetic field.



A0017035

- U_e* Induced voltage
B Magnetic induction (magnetic field)
L Electrode spacing
I Current
v Flow velocity

In the electromagnetic measuring principle, the flowing medium is the moving conductor. The voltage induced (U_e) is proportional to the flow velocity (v) and is supplied to the amplifier by means of two measuring electrodes. The flow volume (Q) is calculated via the pipe cross-section (A). The DC magnetic field is created through a switched direct current of alternating polarity.

Formulae for calculation

- Induced voltage $U_e = B \cdot L \cdot v$
- Volume flow $Q = A \cdot v$


Measuring system

The device consists of a transmitter and a sensor.




Two device versions are available:

- Compact version - the transmitter and sensor form a mechanical unit.
- Remote version – the transmitter and sensor are mounted separately from one another.


Transmitter

Promag 400  A0017117	<p>Device versions and materials</p> <ul style="list-style-type: none"> ▪ Compact version: compact housing <ul style="list-style-type: none"> - Polycarbonate plastic - Aluminum, AlSi10Mg, coated ▪ Remote version: wall-mount housing <ul style="list-style-type: none"> - Polycarbonate plastic - Aluminum, AlSi10Mg, coated <p>Configuration:</p> <ul style="list-style-type: none"> ▪ External operation via four-line, illuminated local display with touch control and guided menus ("Make-it-run" wizards) for applications ▪ Via operating tools (e.g. FieldCare) ▪ Via Web browser (e.g. Microsoft Internet Explorer) ▪ Also for device version with EtherNet/IP output: <ul style="list-style-type: none"> - Via Add-on Profile Level 3 for automation system from Rockwell Automation - Via Electronic Data Sheet (EDS) ▪ Also for device version with PROFIBUS DP output: <ul style="list-style-type: none"> Via PDM driver for Siemens automation system
---	--

Sensor

Promag W <i>Fixed flange: DN 25 to 300 (1 to 12")</i>  A0017040	<ul style="list-style-type: none"> ▪ Nominal diameter range: DN 25 to 2000 (1 to 78") ▪ Materials: <ul style="list-style-type: none"> - Sensor housing: aluminum, AlSi10Mg, coated; carbon steel with protective varnish - Sensor connection housing (standard): aluminum, AlSi10Mg, coated - Sensor connection housing (option): polycarbonate - Measuring tubes¹⁾: <ul style="list-style-type: none"> DN 25 to 300 (1 to 12"): stainless steel, 1.4301/1.4306/304/304L DN 350 to 2000 (14 to 78"): stainless steel, 1.4301/304 - Liner: hard rubber, polyurethane - Electrodes: stainless steel, 1.4435 (316L); Alloy C22, 2.4602 (UNS N06022); tantalum - Process connections: <ul style="list-style-type: none"> Stainless steel, 1.4404/1.4571/F316L Carbon steel, A105/A181/A350LF2/A515(70)/FE410WB/S235JRG2/S235J+N/S275JR/P235GH/P250GH/P265GH - Seals: as per DIN EN 1514-1 - Ground disks: stainless steel, 1.4435 (316L); Alloy C22, 2.4602 (UNS N06022); tantalum
<i>Fixed flange: DN 25 to 300 (1 to 12")</i>  A0022673	
<i>Fixed flange: DN 350 to 2000 (14 to 78")</i>  A0017041	

1) For carbon steel flange material with Al/Zn protective coating (DN 25 to 300 (1 to 12")), protective varnish (IP68) (DN 50 to 300 (2 to 12")) or protective varnish ≥ DN 350 (14")

Device architecture**Fig 1 Possibilities for integrating measuring devices into a system**

- 1 Control system (e.g. PLC)
- 2 EtherNet/IP
- 3 PROFIBUS DP
- 4 4-20 mA HART, pulse/frequency/switch output
- 5 Non-hazardous area
- 6 Non-hazardous area and Zone 2/Div. 2

Safety**IT security**

We only provide a warranty if the device is installed and used as described in the Operating Instructions. The device is equipped with security mechanisms to protect it against any inadvertent changes to the device settings.

IT security measures in line with operators' security standards and designed to provide additional protection for the device and device data transfer must be implemented by the operators themselves.

Input

Measured variable**Direct measured variables**

- Volume flow (proportional to induced voltage)
- Electrical conductivity

In custody transfer: only volume flow

Calculated measured variables

Mass flow

Measuring range

Typically $v = 0.01$ to 10 m/s (0.03 to 33 ft/s) with the specified accuracy

Electrical conductivity: 5 to $10000 \mu\text{S/cm}$

Flow characteristic values in SI units

Nominal diameter		Recommended flow min./max. full scale value ($v \sim 0.3/10 \text{ m/s}$)	Factory settings					
			[mm]	[in]	[m^3/h]	[m^3/h]	[m^3]	[m^3/h]
25	1	9 to 300 dm^3/min	75	2.5	$75 \text{ dm}^3/\text{min}$	0.5	0.5 dm^3	$1 \text{ dm}^3/\text{min}$
32	–	15 to 500 dm^3/min	125	5	$125 \text{ dm}^3/\text{min}$	1	1 dm^3	$2 \text{ dm}^3/\text{min}$
40	1 ½	25 to 700 dm^3/min	200	8	$200 \text{ dm}^3/\text{min}$	1.5	1.5 dm^3	$3 \text{ dm}^3/\text{min}$

Nominal diameter		Recommended flow min./max. full scale value (v ~ 0.3/10 m/s)	Factory settings		
			Full scale value current output (v ~ 2.5 m/s)	Pulse value (~ 2 pulse/s)	Low flow cut off (v ~ 0.04 m/s)
[mm]	[in]	[m³/h]	[m³/h]	[m³]	[m³/h]
50	2	35 to 1 100 dm³/min	300 dm³/min	2.5 dm³	5 dm³/min
65	-	60 to 2 000 dm³/min	500 dm³/min	5 dm³	8 dm³/min
80	3	90 to 3 000 dm³/min	750 dm³/min	5 dm³	12 dm³/min
100	4	145 to 4 700 dm³/min	1 200 dm³/min	10 dm³	20 dm³/min
125	-	220 to 7 500 dm³/min	1 850 dm³/min	15 dm³	30 dm³/min
150	6	20 to 600	150	0.025	2.5
200	8	35 to 1 100	300	0.05	5
250	10	55 to 1 700	500	0.05	7.5
300	12	80 to 2 400	750	0.1	10
350	14	110 to 3 300	1 000	0.1	15
375	15	140 to 4 200	1 200	0.15	20
400	16	140 to 4 200	1 200	0.15	20
450	18	180 to 5 400	1 500	0.25	25
500	20	220 to 6 600	2 000	0.25	30
600	24	310 to 9 600	2 500	0.3	40
700	28	420 to 13 500	3 500	0.5	50
750	30	480 to 15 000	4 000	0.5	60
800	32	550 to 18 000	4 500	0.75	75
900	36	690 to 22 500	6 000	0.75	100
1000	40	850 to 28 000	7 000	1	125
-	42	950 to 30 000	8 000	1	125
1200	48	1250 to 40 000	10 000	1.5	150
-	54	1550 to 50 000	13 000	1.5	200
1400	-	1700 to 55 000	14 000	2	225
-	60	1950 to 60 000	16 000	2	250
1600	-	2200 to 70 000	18 000	2.5	300
-	66	2 500 to 80 000	20 500	2.5	325
1800	72	2 800 to 90 000	23 000	3	350
-	78	3 300 to 100 000	28 500	3.5	450
2000	-	3 400 to 110 000	28 500	3.5	450

Flow characteristic values in US units

Nominal diameter		Recommended flow min./max. full scale value (v ~ 0.3/10 m/s)	Factory settings		
			Full scale value current output (v ~ 2.5 m/s)	Pulse value (~ 2 pulse/s)	Low flow cut off (v ~ 0.04 m/s)
[in]	[mm]	[gal/min]	[gal/min]	[gal]	[gal/min]
1	25	2.5 to 80	18	0.2	0.25
-	32	4 to 130	30	0.2	0.5

Nominal diameter [in] [mm]		Recommended flow min./max. full scale value (v ~ 0.3/10 m/s) [gal/min]	Factory settings		
			Full scale value current output (v ~ 2.5 m/s) [gal/min]	Pulse value (~ 2 pulse/s) [gal]	Low flow cut off (v ~ 0.04 m/s) [gal/min]
1 1/2	40	7 to 190	50	0.5	0.75
2	50	10 to 300	75	0.5	1.25
-	65	16 to 500	130	1	2
3	80	24 to 800	200	2	2.5
4	100	40 to 1250	300	2	4
-	125	60 to 1950	450	5	7
6	150	90 to 2650	600	5	12
8	200	155 to 4850	1200	10	15
10	250	250 to 7500	1500	15	30
12	300	350 to 10600	2400	25	45
14	350	500 to 15000	3600	30	60
15	375	600 to 19000	4800	50	60
16	400	600 to 19000	4800	50	60
18	450	800 to 24000	6000	50	90
20	500	1000 to 30000	7500	75	120
24	600	1400 to 44000	10500	100	180
28	700	1900 to 60000	13500	125	210
30	750	2150 to 67000	16500	150	270
32	800	2450 to 80000	19500	200	300
36	900	3100 to 100000	24000	225	360
40	1000	3800 to 125000	30000	250	480
42	-	4200 to 135000	33000	250	600
48	1200	5500 to 175000	42000	400	600
54	-	9 to 300 Mgal/d	75 Mgal/d	0.0005 Mgal/d	1.3 Mgal/d
-	1400	10 to 340 Mgal/d	85 Mgal/d	0.0005 Mgal/d	1.3 Mgal/d
60	-	12 to 380 Mgal/d	95 Mgal/d	0.0005 Mgal/d	1.3 Mgal/d
-	1600	13 to 450 Mgal/d	110 Mgal/d	0.0008 Mgal/d	1.7 Mgal/d
66	-	14 to 500 Mgal/d	120 Mgal/d	0.0008 Mgal/d	2.2 Mgal/d
72	1800	16 to 570 Mgal/d	140 Mgal/d	0.0008 Mgal/d	2.6 Mgal/d
78	-	18 to 650 Mgal/d	175 Mgal/d	0.0010 Mgal/d	3.0 Mgal/d
-	2000	20 to 700 Mgal/d	175 Mgal/d	0.0010 Mgal/d	2.9 Mgal/d

 To calculate the measuring range, use the *Applicator* sizing tool (→ 102)

Recommended measuring range

"Flow limit" section (→ 43)

 For custody transfer, the applicable approval determines the permitted measuring range.



In custody transfer:

- 160 : 1 for DN 25 to 500 (1 to 20")
- 100 : 1 for DN 600 to 800 (24 to 32")

Further details are laid down by the applicable approval.

Input signal

External measured values



Various pressure transmitters and temperature measuring devices can be ordered from Endress + Hauser: see "Accessories" section (→ 103)

It is recommended to read in external measured values to calculate the following measured variables:
Corrected volume flow

HART protocol

The measured values are written from the automation system to the measuring device via the HART protocol. The pressure transmitter must support the following protocol-specific functions:

- HART protocol
- Burst mode

Fieldbuses

The measured values can be written from the automation system to the measuring via:

- PROFIBUS DP
- Modbus RS485
- EtherNet/IP

Status input

Maximum input values	<ul style="list-style-type: none"> ▪ DC 30 V ▪ 6 mA
Response time	Adjustable: 5 to 200 ms
Input signal level	<ul style="list-style-type: none"> ▪ Low signal: DC -3 to +5 V ▪ High signal: DC 12 to 30 V
Assignable functions	<ul style="list-style-type: none"> ▪ Off ▪ Reset totalizers 1-3 separately ▪ Reset all totalizers ▪ Flow override

Output

Output signal

Current output

Current output	Can be set as: <ul style="list-style-type: none"> ▪ 4-20 mA NAMUR ▪ 4-20 mA US ▪ 4-20 mA HART ▪ 0-20 mA
Maximum output values	<ul style="list-style-type: none"> ▪ DC 24 V (no flow) ▪ 22.5 mA
Load	0 to 700 Ω
Resolution	0.5 µA
Damping	Adjustable: 0.07 to 999 s
Assignable measured variables	<ul style="list-style-type: none"> ▪ Volume flow ▪ Mass flow ▪ Flow velocity ▪ Conductivity ▪ Electronic temperature

Pulse/frequency/switch output

Function	<ul style="list-style-type: none"> ▪ With the order code for "Output; Input", option H: output 2 can be set as a pulse or frequency output ▪ With the order code for "Output; Input", option I: output 2 and 3 can be set as a pulse, frequency or switch output ▪ With the order code for "Output; Input", option J: output 2 firmly assigned as certified pulse output
Version	Passive, open collector
Maximum input values	<ul style="list-style-type: none"> ▪ DC 30 V ▪ 250 mA
Voltage drop	For 25 mA: ≤ DC 2 V
Pulse output	
Pulse width	Adjustable: 0.05 to 2 000 ms
Maximum pulse rate	10 000 Impulse/s
Pulse value	Adjustable
Assignable measured variables	<ul style="list-style-type: none"> ▪ Volume flow ▪ Mass flow
Frequency output	
Output frequency	Adjustable: 0 to 12 500 Hz
Damping	Adjustable: 0 to 999 s
Pulse/pause ratio	1:1
Assignable measured variables	<ul style="list-style-type: none"> ▪ Volume flow ▪ Mass flow ▪ Conductivity ▪ Flow velocity ▪ Electronic temperature
Switch output	
Switching behavior	Binary, conductive or non-conductive
Switching delay	Adjustable: 0 to 100 s
Number of switching cycles	Unlimited
Assignable functions	<ul style="list-style-type: none"> ▪ Off ▪ On ▪ Diagnostic behavior ▪ Limit value: <ul style="list-style-type: none"> - Off - Volume flow - Mass flow - Conductivity - Flow velocity - Totalizer 1-3 - Electronic temperature ▪ Flow direction monitoring ▪ Status <ul style="list-style-type: none"> - Empty pipe detection - Low flow cut off

PROFIBUS DP

Signal encoding	NRZ code
Data transfer	9.6 kBaud...12 MBaud

Modbus RS485

Physical interface	In accordance with EIA/TIA-485-A standard
Terminating resistor	Integrated, can be activated via DIP switch on the transmitter electronics module

EtherNet/IP

Standards	In accordance with IEEE 802.3
------------------	-------------------------------

Signal on alarm

Depending on the interface, failure information is displayed as follows:

Current output*4-20 mA*

Failure mode	Selectable (as per NAMUR recommendation NE 43): <ul style="list-style-type: none"> ■ Minimum value: 3.6 mA ■ Maximum value: 22 mA ■ Defined value: 3.59 to 22.5 mA ■ Actual value ■ Last valid value
---------------------	---

0-20 mA

Failure mode	Choose from: <ul style="list-style-type: none"> ■ Maximum alarm: 22 mA ■ Defined value: 0 to 22.5 mA
---------------------	--

HART

Device diagnostics	Device condition can be read out via HART Command 48
---------------------------	--

Pulse/frequency/switch output

Pulse output	
Failure mode	Choose from: <ul style="list-style-type: none"> ■ Actual value ■ No pulses
Frequency output	
Failure mode	Choose from: <ul style="list-style-type: none"> ■ Actual value ■ Defined value: 0 to 12 500 Hz ■ 0 Hz
Switch output	
Failure mode	Choose from: <ul style="list-style-type: none"> ■ Current status ■ Open ■ Closed

PROFIBUS DP

Status and alarm messages	Diagnostics in accordance with PROFIBUS PA Profile 3.02
----------------------------------	---

Modbus RS485

Failure mode	Choose from: ■ NaN value instead of current value ■ Last valid value
---------------------	--

EtherNet/IP

Device diagnostics	Device condition can be read out in Input Assembly
---------------------------	--

Local display

Plain text display	With information on cause and remedial measures
Backlight	Red backlighting indicates a device error.

 Status signal as per NAMUR recommendation NE 107

Operating tool

- Via digital communication:
 - HART protocol
 - PROFIBUS DP
 - Modbus RS485
 - EtherNet/IP
- Via service interface

Plain text display	With information on cause and remedial measures
---------------------------	---

 Additional information on remote operation (→  96)

Web browser

Plain text display	With information on cause and remedial measures
---------------------------	---

Light emitting diodes (LED)

Status information	Status indicated by various light emitting diodes The following information is displayed depending on the device version: ■ Supply voltage active ■ Data transmission active ■ Device alarm/error has occurred ■ EtherNet/IP network available ■ EtherNet/IP connection established
---------------------------	---

Low flow cut off The switch points for low flow cut off are user-selectable.

Galvanic isolation The following connections are galvanically isolated from each other:
■ Inputs
■ Outputs
■ Power supply

Protocol-specific data HART

Manufacturer ID	0x11
Device type ID	0x67

HART protocol revision	7
Device description files (DTM, DD)	Information and files under: www.endress.com
HART load	Min. 250 Ω
Dynamic variables	<p>Read out the dynamic variables: HART command 3 The measured variables can be freely assigned to the dynamic variables.</p> <p>Measured variables for PV (primary dynamic variable)</p> <ul style="list-style-type: none"> ■ Off ■ Volume flow ■ Mass flow ■ Conductivity ■ Flow velocity ■ Electronic temperature <p>Measured variables for SV, TV, QV (secondary, tertiary and quaternary dynamic variable)</p> <ul style="list-style-type: none"> ■ Volume flow ■ Mass flow ■ Conductivity ■ Flow velocity ■ Electronic temperature ■ Totalizer 1 ■ Totalizer 2 ■ Totalizer 3
Device variables	<p>Read out the device variables: HART command 9 The device variables are permanently assigned.</p> <p>A maximum of 8 device variables can be transmitted:</p> <ul style="list-style-type: none"> ■ 0 = volume flow ■ 1 = mass flow ■ 2 = conductivity ■ 3 = flow velocity ■ 4 = electronic temperature ■ 5 = totalizer 1 ■ 6 = totalizer 2 ■ 7 = totalizer 3

PROFIBUS DP

Manufacturer ID	0x11
Ident number	0x1562
Profile version	3.02
Device description files (GSD, DTM, DD)	Information and files under: <ul style="list-style-type: none"> ■ www.endress.com ■ www.profibus.org
Output values (from measuring device to automation system)	<p>Analog input 1 to 4</p> <ul style="list-style-type: none"> ■ Mass flow ■ Volume flow ■ Flow velocity ■ Conductivity ■ Electronic temperature <p>Digital input 1 to 2</p> <ul style="list-style-type: none"> ■ Empty pipe detection ■ Low flow cut off ■ Verification status <p>Totalizer 1 to 3</p> <ul style="list-style-type: none"> ■ Mass flow ■ Volume flow

Input values (from automation system to measuring device)	Analog output 1 (fixed assignment) External density Digital output 1 to 2 (fixed assignment) <ul style="list-style-type: none"> ▪ Digital output 1: switch positive zero return on/off ▪ Digital output 2: start verification Totalizer 1 to 3 <ul style="list-style-type: none"> ▪ Totalize ▪ Reset and hold ▪ Preset and hold ▪ Stop ▪ Operating mode configuration: <ul style="list-style-type: none"> - Net flow total - Forward flow total - Reverse flow total
Supported functions	<ul style="list-style-type: none"> ▪ Identification & Maintenance Simplest device identification on the part of the control system and nameplate ▪ PROFIBUS upload/download Reading and writing parameters is up to ten times faster with PROFIBUS upload/download ▪ Condensed status Simplest and self-explanatory diagnostic information by categorizing diagnostic messages that occur
Configuration of the device address	<ul style="list-style-type: none"> ▪ DIP switches on the I/O electronics module ▪ Via operating tools (e.g. FieldCare)

Modbus RS485

Protocol	Modbus Applications Protocol Specification V1.1
Device type	Slave
Slave address range	1 to 247
Broadcast address range	0
Function codes	<ul style="list-style-type: none"> ▪ 03: Read holding register ▪ 04: Read input register ▪ 06: Write single registers ▪ 08: Diagnostics ▪ 16: Write multiple registers ▪ 23: Read/write multiple registers
Broadcast messages	Supported by the following function codes: <ul style="list-style-type: none"> ▪ 06: Write single registers ▪ 16: Write multiple registers ▪ 23: Read/write multiple registers
Supported baud rate	<ul style="list-style-type: none"> ▪ 1 200 BAUD ▪ 2 400 BAUD ▪ 4 800 BAUD ▪ 9 600 BAUD ▪ 19 200 BAUD ▪ 38 400 BAUD ▪ 57 600 BAUD ▪ 115 200 BAUD
Data transfer mode	<ul style="list-style-type: none"> ▪ ASCII ▪ RTU
Data access	Each device parameter can be accessed via Modbus RS485.  For Modbus register information

EtherNet/IP

Protocol	<ul style="list-style-type: none"> ▪ The CIP Networks Library Volume 1: Common Industrial Protocol ▪ The CIP Networks Library Volume 2: EtherNet/IP Adaptation of CIP 		
Communication type	<ul style="list-style-type: none"> ▪ 10Base-T ▪ 100Base-TX 		
Device profile	Generic device (product type: 0x2B)		
Manufacturer ID	0x49E		
Device type ID	0x1067		
Baud rates	Automatic $^{10}_{100}$ Mbit with half-duplex and full-duplex detection		
Polarity	Auto-polarity for automatic correction of crossed TxD and RxD pairs		
Supported CIP connections	Max. 3 connections		
Explicit connections	Max. 6 connections		
I/O connections	Max. 6 connections (scanner)		
Configuration options for measuring device	<ul style="list-style-type: none"> ▪ DIP switches on the electronics module for IP addressing ▪ Manufacturer-specific software (FieldCare) ▪ Add-on Profile Level 3 for Rockwell Automation control systems ▪ Web browser ▪ Electronic Data Sheet (EDS) integrated in the measuring device 		
Configuration of the EtherNet interface	<ul style="list-style-type: none"> ▪ Speed: 10 MBit, 100 MBit, auto (factory setting) ▪ Duplex: half-duplex, full-duplex, auto (factory setting) 		
Configuration of the device address	<ul style="list-style-type: none"> ▪ DIP switches on the electronics module for IP addressing (last octet) ▪ DHCP ▪ Manufacturer-specific software (FieldCare) ▪ Add-on Profile Level 3 for Rockwell Automation control systems ▪ Web browser ▪ EtherNet/IP tools, e.g. RSLink (Rockwell Automation) 		
Device Level Ring (DLR)	No		
Fix Input			
RPI	5 ms to 10 s (factory setting: 20 ms)		
Exclusive Owner Multicast		Instance	Size [byte]
	Instance configuration:	0x68	398
	O → T configuration:	0x66	56
	T → O configuration:	0x64	32
Exclusive Owner Multicast		Instance	Size [byte]
	Instance configuration:	0x69	-
	O → T configuration:	0x66	56
	T → O configuration:	0x64	32
Input only Multicast		Instance	Size [byte]
	Instance configuration:	0x68	398
	O → T configuration:	0xC7	-
	T → O configuration:	0x64	32
Input only Multicast		Instance	Size [byte]
	Instance configuration:	0x69	-
	O → T configuration:	0xC7	-
	T → O configuration:	0x64	32

Input Assembly	<ul style="list-style-type: none"> ■ Current device diagnostics ■ Volume flow ■ Mass flow ■ Conductivity ■ Totalizer 1 ■ Totalizer 2 ■ Totalizer 3 		
Configurable Input			
RPI	5 ms to 10 s (factory setting: 20 ms)		
Exclusive Owner Multicast		Instance	Size [byte]
	Instance configuration:	0x68	398
	O → T configuration:	0x66	56
Exclusive Owner Multicast		Instance	Size [byte]
	Instance configuration:	0x69	-
	O → T configuration:	0x66	56
	T → O configuration:	0x65	88
Input only Multicast		Instance	Size [byte]
	Instance configuration:	0x68	398
	O → T configuration:	0xC7	-
	T → O configuration:	0x65	88
Input only Multicast		Instance	Size [byte]
	Instance configuration:	0x69	-
	O → T configuration:	0xC7	-
	T → O configuration:	0x65	88
Configurable Input Assembly	<ul style="list-style-type: none"> ■ Volume flow ■ Mass flow ■ Electronic temperature ■ Conductivity ■ Totalizer 1 to 3 ■ Flow velocity ■ Volume flow unit ■ Mass flow unit ■ Temperature unit ■ Conductivity unit ■ Unit totalizer 1-3 ■ Flow velocity unit ■ Verification result ■ Verification status <p> The range of options increases if the measuring device has one or more application packages.</p>		
Fix Output			
Output Assembly	<ul style="list-style-type: none"> ■ Activation of reset totalizers 1-3 ■ Activation of reference density compensation ■ Reset totalizers 1-3 ■ External density ■ Density unit ■ Activation verification ■ Start verification 		

Configuration	
Configuration Assembly	<p>Only the most common configurations are listed below.</p> <ul style="list-style-type: none"> ▪ Software write protection ▪ Mass flow unit ▪ Mass unit ▪ Volume flow unit ▪ Volume unit ▪ Density unit ▪ Conductivity ▪ Temperature unit ▪ Totalizer 1-3: <ul style="list-style-type: none"> - Assignment - Unit - Measuring mode - Failure mode ▪ Alarm delay

Power supply


Terminal assignment

Transmitter

0-20 mA/4-20 mA HART connection version with additional outputs and inputs

The sensor can be ordered with terminals.

Connection methods available		Possible options for order code "Electrical connection"
Outputs	Power supply	
Terminals	Terminals	<ul style="list-style-type: none"> ▪ Option A: coupling M20x1 ▪ Option B: thread M20x1 ▪ Option C: thread G ½" ▪ Option D: thread NPT ½"



1 Supply voltage

2 Output 1 (26/27) and output 2 (24/25)

3 Output 3 (22/23) and input 1 (20/21)

Supply voltage

Order code for "Power supply"	Terminal numbers	
	1 (L+/L)	2 (L-/N)
Option L (wide range power unit)		AC100 to 240 V
		AC/DC24 V


Signal transmission 0-20 mA/4-20 mA HART with additional outputs and inputs

Order code for "Output" and "Input"	Terminal numbers							
	Output 1		Output 2		Output 3		Input	
	26 (+)	27 (-)	24 (+)	25 (-)	22 (+)	23 (-)	20 (+)	21 (-)
Option H	■ 4-20 mA HART (active)		Pulse/frequency output (passive)		Switch output (passive)		-	
Option I	■ 4-20 mA HART (active)		Pulse/frequency/ switch output (passive)		Pulse/frequency/ switch output (passive)		Status input	
Option J	■ 4-20 mA HART (active)		Permanently assigned Pulse output adjusted (passive)		Pulse/frequency/ switch output (passive)		Status input	

PROFIBUS DP connection version

The sensor can be ordered with terminals.

Connection methods available	Possible options for order code "Electrical connection"	
Outputs	Power supply	
Terminals	Terminals	<ul style="list-style-type: none"> ■ Option A: coupling M20x1 ■ Option B: thread M20x1 ■ Option C: thread G ½" ■ Option D: thread NPT ½"



- 1 Supply voltage (wide range power unit)
2 PROFIBUS DP

A0020426

Supply voltage

Order code for "Power supply"	Terminal numbers	
	1 (L+/L)	2 (L-/N)
Option L (wide range power unit)	AC100 to 240 V	
		AC/DC24 V


PROFIBUS DP signal transmission

Order code for "Output" and "Input"	Terminal numbers	
	26 (RxD/TxD-P)	27 (RxD/TxD-N)
Option L	B	A
Order code for "Output": Option L: PROFIBUS DP, for use in non-hazardous areas and Zone 2/div. 2		

Modbus RS485 connection version

The sensor can be ordered with terminals.

Connection methods available	Possible options for order code "Electrical connection"	
Outputs	Power supply	
Terminals	Terminals	<ul style="list-style-type: none"> ■ Option A: coupling M20x1 ■ Option B: thread M20x1 ■ Option C: thread G $\frac{1}{2}$" ■ Option D: thread NPT $\frac{1}{2}$"



A0020427

- 1 Supply voltage (wide range power unit)
2 Modbus RS485

Supply voltage

Order code for "Power supply"	Terminal numbers	
	1 (L+/L)	2 (L-/N)
Option L (wide range power unit)	AC100 to 240 V	
		AC/DC24 V


Signal transmission Modbus RS485

Order code for "Output" and "Input"	Terminal numbers	
	26 (+)	27 (-)
Option M	A	B

EtherNet/IP connection version

The sensor can be ordered with terminals or a device plug.

Outputs	Connection methods available	Possible options for order code "Electrical connection"
Power supply		
Terminals	Terminals	<ul style="list-style-type: none"> ■ Option A: coupling M20x1 ■ Option B: thread M20x1 ■ Option C: thread G ½" ■ Option D: thread NPT ½"
Device plug	Terminals	<ul style="list-style-type: none"> ■ Option L: plug M12x1 + thread NPT ½" ■ Option N: plug M12x1 + coupling M20 ■ Option P: plug M12x1 + thread G ½" ■ Option U: plug M12x1 + thread M20



A0020428

1 Supply voltage (wide range power unit)


2 EtherNet/IP

Supply voltage

Order code for "Power supply"	Terminal numbers	
	1 (L+/L)	2 (L-/N)
Option L (wide range power unit)		AC100 to 240 V
		AC/DC24 V

EtherNet/IP signal transmission


Order code for "Output"	Connection via
Option N	EtherNet/IP connector

Remote version

Power consumption	Order code for "Output"	Maximum power consumption
	Option H: 0/4-20mA HART, pulse/frequency/switch output, switch output	30 VA/8 W
	Option I: 0/4-20mA HART, 2 x pulse/frequency/switch output, status input	30 VA/8 W
	Option J: 0/4-20mA HART, certified pulse output, pulse/frequency/switch output, status input	30 VA/8 W
	Option L: PROFIBUS DP	30 VA/8 W
	Option M: Modbus RS485	30 VA/8 W
	Option N: EtherNet/IP	30 VA/8 W

Current consumption	Transmitter	Order code for "Power supply"	Maximum Current consumption	Maximum switch-on current
		Option L: AC 100 to 240 V	145 mA	25 A (< 5 ms)
		Option L: AC/DC 24 V	350 mA	27 A (< 5 ms)

- Power supply failure**
- Totalizers stop at the last value measured.
 - Configuration is retained in the plug-in memory (HistoROM DAT).
 - Error messages (incl. total operated hours) are stored.




3 Supply voltage and signal transmission connection

- A Compact version
 B Remote version wall-mount housing
 1 Cable entry for supply voltage
 2 Cable entry for signal transmission

Remote version connection

Connecting cable




4 Connecting cable connection: electrode and coil current cable

- A Transmitter wall-mount housing
 B Sensor connection housing
 1 Electrode cable
 2 Coil current cable

- Fix the cable run or route it in an armored conduit.
Cable movements can influence the measuring signal especially in the case of low fluid conductivities.
- Route the cable well clear of electrical machines and switching elements.
- Ensure potential equalization between sensor and transmitter.

Connection examples

Current output 4-20 mA HART




A0016800

5 Connection example for 4-20 mA HART current output (active)

- 1 Automation system with current input (e.g. PLC)
- 2 Cable shield, observe cable specifications (→ 29)
- 3 Connection for HART operating devices (→ 96)
- 4 Resistor for HART communication ($\geq 250 \Omega$): observe maximum load (→ 10)
- 5 Analog display unit: observe maximum load (→ 10)
- 6 Transmitter

Current output 4-20 mA




A0017162

6 Connection example for 0-20 mA current output (active) and 4-20 mA current output (active)

- 1 Automation system with current input (e.g. PLC)
- 2 Analog display unit: observe maximum load (→ 10)
- 3 Transmitter

Pulse/frequency output




A0016801

■ 7 Connection example for pulse/frequency output (passive)

- 1 Automation system with pulse/frequency input (e.g. PLC)
- 2 Power supply
- 3 Transmitter: observe input values (→ ■ 11)

Switch output




A0016802

■ 8 Connection example for switch output (passive)

- 1 Automation system with switch input (e.g. PLC)
- 2 Power supply
- 3 Transmitter: observe input values (→ ■ 11)

PROFIBUS DP




A0021429

■ 9 Connection example for PROFIBUS DP, non-hazardous area and Zone 2/Div. 2

- 1 Control system (e.g. PLC)
- 2 Cable shield: the cable shield must be grounded at both ends to comply with EMC requirements; observe cable specifications (→ ■ 29)
- 3 Transmitter

i If baud rates > 1.5 MBaud an EMC cable entry must be used and the cable shield must continue as far as the terminal wherever possible.

Modbus RS485




A0016803

■ 10 Connection example for Modbus RS485, non-hazardous area and Zone 2/Div. 2

- 1 Control system (e.g. PLC)
- 2 Cable shield: the cable shield must be grounded at both ends to comply with EMC requirements; observe cable specifications (→ ■ 30)
- 3 Distribution box
- 4 Transmitter

EtherNet/IP



A0016805

■ 11 Connection example for EtherNet/IP

- 1 Control system (e.g. PLC)
- 2 Ethernet switch
- 3 Observe cable specifications (→ ■ 30)
- 4 Device plug
- 5 Transmitter


Status input

Fig. 12 Connection example for status input

- 1 Automation system with status output (e.g. PLC)
- 2 Power supply
- 3 Transmitter: observe input values

Potential equalization**Requirements**

Please consider the following to ensure correct measurement:

- Same electrical potential for the fluid and sensor
- Remote version: same electrical potential for the sensor and transmitter
- Company-internal grounding concepts
- Pipe material and grounding


Connection examples for standard situations*Metal, grounded pipe*

Fig. 13 Potential equalization via measuring tube

Connection example in special situations*Unlined and ungrounded metal pipe*

This connection method also applies in situations where:

- The customary potential equalization is not used
- Equalizing currents are present

Ground cable	Copper wire, at least 6 mm ² (0.0093 in ²)
---------------------	---




Fig. 14 Potential equalization via ground terminal and pipe flanges

Note the following when installing:

- Connect both sensor flanges to the pipe flange via a ground cable and ground them.
- Connect the connection housing of the transmitter or sensor to ground potential by means of the ground terminal provided for the purpose. To mount the ground cable:
 - If $DN \leq 300$ (12"): Mount the ground cable directly on the conductive flange coating of the sensor with the flange screws.
 - If $DN \geq 350$ (14"): Mount the ground cable directly on the metal transport bracket.

i For remote device versions, the ground terminal in the example always refers to the sensor and **not** to the transmitter.


i The necessary ground cable can be ordered from Endress+Hauser .

Plastic pipe or pipe with insulating liner

This connection method also applies in situations where:

- The customary potential equalization is not used
- Equalizing currents are present

Ground cable	Copper wire, at least 6 mm ² (0.0093 in ²)
---------------------	---



A0016318

■ 15 Potential equalization via ground terminal and ground disks

Note the following when installing:

The ground disks must be connected to the ground terminal via the ground cable and be connected to ground potential.

i For remote device versions, the ground terminal in the example always refers to the sensor and **not** to the transmitter.


i The ground cable and ground disks can be ordered from Endress+Hauser (→ ■ 101).

Pipe with a cathodic protection unit

This connection method is only used if the following two conditions are met:

- Metal pipe without liner or pipe with electrically conductive liner
- Cathodic protection is integrated in the personal protection equipment

Ground cable	Copper wire, at least 6 mm ² (0.0093 in ²)
---------------------	---



A0016319

Prerequisite: The sensor is installed in the pipe in a way that provides electrical insulation.

1. Connect the two flanges of the pipe to one another via a ground cable.
2. Guide the shield of the signal lines through a capacitor.

3. Connect the measuring device to the power supply such that it is floating in relation to the protective ground (isolation transformer).

 For remote device versions, the ground terminal in the example always refers to the sensor and **not** to the transmitter.

 The necessary ground cable can be ordered from Endress+Hauser .

Terminals

Transmitter

- Supply voltage cable: plug-in spring terminals for wire cross-sections 0.5 to 2.5 mm² (20 to 14 AWG)
- Signal cable: plug-in spring terminals for wire cross-sections 0.5 to 2.5 mm² (20 to 14 AWG)
- Electrode cable: spring terminals for wire cross-sections 0.5 to 2.5 mm² (20 to 14 AWG)
- Coil current cable: spring terminals for wire cross-sections 0.5 to 2.5 mm² (20 to 14 AWG)

Sensor connection housing

Spring terminals for wire cross-sections 0.5 to 2.5 mm² (20 to 14 AWG)

Cable entries

Cable entry thread

- M20 x 1.5
- Via adapter:
 - NPT ½"
 - G ½"

Cable gland

- For standard cable: M20 × 1.5 with cable Ø6 to 12 mm (0.24 to 0.47 in)
- For reinforced cable: M20 × 1.5 with cable Ø9.5 to 16 mm (0.37 to 0.63 in)

 If metal cable entries are used, use a grounding plate.

Cable specification

Permitted temperature range

- -40 °C (-40 °F) to +80 °C (+176 °F)
- Minimum requirement: cable temperature range ≥ ambient temperature +20 K

Power supply cable

Standard installation cable is sufficient.

Signal cable

Current output

- For 0-20 mA and 4-20 mA: standard installation cable is sufficient.
- For 4-20 mA HART: Shielded cable recommended. Observe grounding concept of the plant.

Pulse/frequency/switch output

Standard installation cable is sufficient.

Status input

Standard installation cable is sufficient.

PROFIBUS DP

The IEC 61158 standard specifies two types of cable (A and B) for the bus line which can be used for every transmission rate. Cable type A is recommended.

Cable type	A
Characteristic impedance	135 to 165 Ω at a measuring frequency of 3 to 20 MHz
Cable capacitance	<30 pF/m
Wire cross-section	>0.34 mm ² (22 AWG)
Cable type	Twisted pairs
Loop resistance	≤110 Ω/km

Signal damping	Max. 9 dB over the entire length of the cable cross-section
Shielding	Copper braided shielding or braided shielding with foil shield. When grounding the cable shield, observe the grounding concept of the plant.

Modbus RS485

The EIA/TIA-485 standard specifies two types of cable (A and B) for the bus line which can be used for every transmission rate. Cable type A is recommended.

Cable type	A
Characteristic impedance	135 to 165 Ω at a measuring frequency of 3 to 20 MHz
Cable capacitance	<30 pF/m
Wire cross-section	>0.34 mm ² (22 AWG)
Cable type	Twisted pairs
Loop resistance	≤110 Ω/km
Signal damping	Max. 9 dB over the entire length of the cable cross-section
Shielding	Copper braided shielding or braided shielding with foil shield. When grounding the cable shield, observe the grounding concept of the plant.

EtherNet/IP

The standard ANSI/TIA/EIA-568-B.2 Annex specifies CAT 5 as the minimum category for a cable used for EtherNet/IP. CAT 5e and CAT 6 are recommended.


 For more information on planning and installing EtherNet/IP networks, please refer to the "Media Planning and Installation Manual. EtherNet/IP" of ODVA Organization.

Connecting cable for remote version*Electrode cable*

Standard cable	3 × 0.38 mm ² (20 AWG) with common, braided copper shield (φ ~7 mm (0.28 in)) and individual shielded cores
Cable for empty pipe detection (EPD)	4 × 0.38 mm ² (20 AWG) with common, braided copper shield (φ ~7 mm (0.28 in)) and individual shielded cores
Conductor resistance	≤50 Ω/km (0.015 Ω/ft)
Capacitance: core/shield	≤420 pF/m (128 pF/ft)
Operating temperature	-20 to +80 °C (-68 to +176 °F)

Coil current cable

Standard cable	2 × 0.75 mm ² (18 AWG) with common, braided copper shield (φ ~ 7 mm (0.28")) and individually shielded cores
Conductor resistance	≤37 Ω/km (0.011 Ω/ft)
Capacitance: core/core, shield grounded	≤120 pF/m (37 pF/ft)
Operating temperature	-20 to +80 °C (-68 to +176 °F)
Test voltage for cable insulation	≤ AC 1433 V r.m.s. 50/60 Hz or ≥ DC 2026 V



A0003194

图 16 Cable cross-section

- a** Electrode cable
- b** Coil current cable
- 1 Core
- 2 Core insulation
- 3 Core shield
- 4 Core jacket
- 5 Core reinforcement
- 6 Cable shield
- 7 Outer jacket

i A connecting cable can be ordered from Endress+Hauser for IP68:

- Pre-terminated cables that are already connected to the sensor.
- Pre-terminated cables, where the cables are connected by the customer onsite (incl. tools for sealing the connection compartment)

Reinforced connecting cables

Reinforced connecting cables with an additional, reinforcing metal braid should be used for:

- When laying the cable directly in the ground
- Where there is a risk of damage from rodents
- If using the device below IP68 degree of protection

i Reinforced connecting cables with an additional, reinforcing metal braid can be ordered from Endress+Hauser .

Operation in zones of severe electrical interference

The measuring system meets the general safety requirements (→ **图 100**) and EMC specifications (→ **图 40**).

Grounding is by means of the ground terminal provided for the purpose inside the connection housing. The stripped and twisted lengths of cable shield to the ground terminal must be as short as possible.

Performance characteristics

Reference operating conditions

In accordance with DIN EN 29104

- Fluid temperature: $+28 \pm 2^\circ\text{C}$ ($+82 \pm 4^\circ\text{F}$)
- Ambient temperature range: $+22 \pm 2^\circ\text{C}$ ($+72 \pm 4^\circ\text{F}$)
- Warm-up period: 30 min

Installation

- Inlet run $> 10 \times \text{DN}$
- Outlet run $> 5 \times \text{DN}$
- Sensor and transmitter grounded.
- The sensor is centered in the pipe.

i No special requirements must be observed at the inlet and outlet runs to keep within the in-service maximum permissible errors for custody transfer.

i To calculate the measuring range, use the *Applicator* sizing tool (→ **图 102**)

Maximum measured error**Error limits under reference operating conditions**

o.r. = of reading

Volume flow

- $\pm 0.5\% \text{ o.r.} \pm 1 \text{ mm/s (0.04 in/s)}$
- Optional: $\pm 0.2\% \text{ o.r.} \pm 2 \text{ mm/s (0.08 in/s)}$



Fluctuations in the supply voltage do not have any effect within the specified range.




Fig. 17 Maximum measured error in % o.r.




Fig. 18 Flat Spec in % o.r.

Flat Spec flow values 0.5 %

Nominal diameter		$v_{0.5}$	
[mm]	[in]	[m/s]	[ft/s]
25 to 600	1 to 24	0.5	1.64

Flat Spec flow values 0.2 %

Nominal diameter		$v_{0.2}$	
[mm]	[in]	[m/s]	[ft/s]
25 to 600	1 to 24	1.5	4.92

Electrical conductivity

Max. measured error not specified.

Accuracy of outputs

o.r. = of reading

The outputs have the following base accuracy specifications.

Current output

Accuracy	Max. $\pm 5 \mu\text{A}$
-----------------	--------------------------

Pulse/frequency output

Accuracy	Max. $\pm 50 \text{ ppm o.r.}$ (across the complete ambient temperature range)
-----------------	--

Repeatability

o.r. = of reading

Volume flowMax. $\pm 0.1 \%$ o.r. $\pm 0.5 \text{ mm/s}$ (0.02 in/s)**Electrical conductivity**Max. $\pm 5 \%$ o.r.**Influence of ambient temperature**

o.r. = of reading; o.f.s. = of full scale value

Current output


Temperature coefficient	Typically $\pm 50 \text{ ppm/}^\circ\text{C}$ o.r. or $\pm 1 \mu\text{A/}^\circ\text{C}$
--------------------------------	--

Pulse/frequency output

Temperature coefficient	Max. $\pm 0.5 \text{ ppm v.M./}^\circ\text{C}$
--------------------------------	--

Installation

No special measures such as supports are necessary. External forces are absorbed by the construction of the device.

Mounting location

A0023343

Preferably install the sensor in an ascending pipe, and ensure a sufficient distance to the next pipe elbow: $h \geq 2 \times DN$

To prevent measuring errors arising from accumulation of gas bubbles in the measuring tube, avoid the following mounting locations in the pipe:

- Highest point of a pipeline.
- Directly upstream of a free pipe outlet in a down pipe.

Installation in down pipes

Install a siphon with a vent valve downstream of the sensor in down pipes whose length $h \geq 5$ m (16.4 ft). This precaution is to avoid low pressure and the consequent risk of damage to the measuring tube. This measure also prevents the system losing prime.

 For information on the liner's resistance to partial vacuum (→ 43)





Fig. 19 Installation in a down pipe


- 1 Vent valve
- 2 Pipe siphon
- h Length of down pipe

Installation in partially filled pipes

A partially filled pipe with a gradient necessitates a drain-type configuration. The empty pipe detection (EPD) function offers additional protection by detecting empty or partially filled pipes.



For heavy sensors $DN \geq 350$ (14")




Orientation


The direction of the arrow on the sensor nameplate helps you to install the sensor according to the flow direction (direction of medium flow through the piping).

An optimum orientation position helps avoid gas and air accumulations and deposits in the measuring tube.

The measuring device also offers the empty pipe detection function to detect partially filled measuring pipes in the event of outgassing fluids or variable process pressures.

Vertical

Optimum for self-emptying pipe systems and for use in conjunction with empty pipe detection.

Horizontal


- 1 EPD electrode for empty pipe detection
- 2 Measuring electrodes for signal detection
- 3 Reference electrode for potential equalization

- i**
- The measuring electrode plane must be horizontal. This prevents brief insulation of the two measuring electrodes by entrained air bubbles.
 - Empty pipe detection only works if the transmitter housing is pointing upwards as otherwise there is no guarantee that the empty pipe detection function will actually respond to a partially filled or empty measuring tube.

Inlet and outlet runs

If possible, install the sensor upstream from fittings such as valves, T-pieces or elbows.

Observe the following inlet and outlet runs to comply with accuracy specifications:



- i** To keep within the in-service maximum permissible errors for custody transfer no additional requirements apply with regard to the graphic illustrated above.


Adapters

Suitable adapters to DIN EN 545 (double-flange reducers) can be used to install the sensor in larger-diameter pipes. The resultant increase in the rate of flow improves measuring accuracy with very slow-moving fluids.

The nomogram shown here can be used to calculate the pressure loss caused by reducers and expanders:

- Calculate the ratio of the diameters d/D .
- From the nomogram read off the pressure loss as a function of flow velocity (downstream from the reduction) and the d/D ratio.

- i** The nomogram only applies to liquids with a viscosity similar to that of water.




A0016359

Length of connecting cable

To ensure correct measuring results when using the remote version, observe the maximum permitted cable length L_{max} . This length is determined by the conductivity of the fluid.

If measuring liquids in general: 5 $\mu\text{S}/\text{cm}$



A0016359

■ 20 Permitted length of connecting cable for remote version


Area shaded gray = permitted range

L_{max} = length of connecting cable in [m] ([ft])

[$\mu\text{S}/\text{cm}$] = fluid conductivity


Installing the wall-mount housing

Wall mounting



21 Engineering unit mm (in)

Post mounting



22 Engineering unit mm (in)

Special mounting instructions

Display protection

To ensure that the optional display protection can be easily opened, maintain the following minimum head clearance: 350 mm (13.8 in)

Permanent immersion in water

A fully welded remote version with IP68 protection is optionally available for permanent immersion in water ≤ 3 m (10 ft) or in exceptional cases for use for up to 48 hours at ≤ 10 m (30 ft). The measuring device meets the requirements of corrosion categories C5-M and Im1/Im2/Im3. The fully

welded design along with the connection compartment sealing system ensure that moisture cannot enter the measuring device.





图 23 Engineering unit in m(ft)

i Replacement of cable gland on connection housing (→ 图 29)

Buried applications

A remote version with IP68 protection is optionally available for buried applications. The measuring device satisfies the certified corrosion protection Im1/Im2/Im3 in accordance with EN ISO 12944. It can be used directly underground without the need for additional protective measures. The device is mounted in accordance with the usual regional installation regulations (e.g. EN DIN 1610).



Environment

Ambient temperature range

Transmitter	-40 to +60 °C (-40 to +140 °F)
Local display	-20 to +60 °C (-4 to +140 °F), the readability of the display may be impaired at temperatures outside the temperature range.
Sensor	<ul style="list-style-type: none"> ▪ Process connection material, carbon steel: -10 to +60 °C (+14 to +140 °F) ▪ Process connection material, stainless steel: -40 to +60 °C (-40 to +140 °F) <p>Mount the transmitter separately from the sensor if both the ambient and fluid temperatures are high.</p>
Liner	Do not exceed or fall below the permitted temperature range of the liner (→ 图 40).

If operating outdoors:

- Install the measuring device in a shady location.
- Avoid direct sunlight, particularly in warm climatic regions.
- Avoid direct exposure to weather conditions.
- Protect the display against impact.
- Protect the display from abrasion by sand in desert areas.



A display protector can be ordered from Endress+Hauser: "Accessories" section (→ 101)

Storage temperature	The storage temperature corresponds to the operating temperature range of the measuring transmitter and the appropriate measuring sensors. ■ Protect the measuring device against direct sunlight during storage in order to avoid unacceptably high surface temperatures. ■ Select a storage location where moisture cannot collect in the measuring device as fungus or bacteria infestation can damage the liner. ■ If protection caps or protective covers are mounted these should never be removed before installing the measuring device.
Atmosphere	If a plastic transmitter housing is permanently exposed to certain steam and air mixtures, this can damage the housing. If you are unsure, please contact your Endress+Hauser Sales Center for clarification.
Degree of protection	<p>Transmitter</p> <ul style="list-style-type: none"> ■ As standard: IP66/67, type 4X enclosure ■ When housing is open: IP20, type 1 enclosure <p>Sensor</p> <ul style="list-style-type: none"> ■ As standard: IP66/67, type 4X enclosure ■ Optionally available for remote version: <ul style="list-style-type: none"> – IP66/67, type 4X enclosure; fully welded, with protective varnish EN ISO 12944 C5-M. Suitable for use in corrosive atmospheres. – IP68, type 6P enclosure; fully welded, with protective varnish as per EN ISO 12944 C5-M. Suitable for permanent immersion in water \leq 3 m (10 ft) or 48 hours at depths \leq 10 m (30 ft). – IP68, type 6P enclosure; fully welded, with protective varnish as per EN ISO 12944 Im1/Im2/Im3. Suitable for permanent immersion in saline water \leq 3 m (10 ft) or 48 hours at depths \leq 10 m (30 ft) or in buried applications.
Shock resistance	<p>Compact version 6 ms 30 g, according to IEC 60068-2-27</p> <p>Remote version</p> <ul style="list-style-type: none"> ■ Transmitter: 6 ms 30 g, according to IEC 60068-2-27 ■ Sensor: 6 ms 50 g, according to IEC 60068-2-27
Vibration resistance	<p>Compact version</p> <ul style="list-style-type: none"> ■ Vibration sinusoidal, 1 g peak, according to IEC 60068-2-6 ■ Vibration broad-band random, 1.54 g rms, according to IEC 60068-2-64 <p>Remote version</p> <ul style="list-style-type: none"> ■ Transmitter <ul style="list-style-type: none"> – Vibration sinusoidal, 1 g peak, according to IEC 60068-2-6 – Vibration broad-band random, 1.54 g rms, according to IEC 60068-2-64 ■ Sensor: <ul style="list-style-type: none"> – Vibration sinusoidal, 2 g peak, according to IEC 60068-2-6 – Vibration broad-band random, 2.70 g rms, according to IEC 60068-2-64
Mechanical load	<ul style="list-style-type: none"> ■ Protect the transmitter housing against mechanical effects, such as shock or impact; the use of the remote version is sometimes preferable. ■ Never use the transmitter housing as a ladder or climbing aid.

Electromagnetic compatibility (EMC)

- As per IEC/EN 61326 and NAMUR Recommendation 21 (NE 21)
- Complies with emission limits for industry as per EN 55011 (Class A)
- Device version with PROFIBUS DP: Complies with emission limits for industry as per EN 50170 Volume 2, IEC 61784

i The following applies for PROFIBUS DP: If baud rates > 1.5 MBaud an EMC cable entry must be used and the cable shield must continue as far as the terminal wherever possible.

book For details refer to the Declaration of Conformity.

Process**Medium temperature range**

- 0 to +80 °C (+32 to +176 °F) for hard rubber, DN 50 to 2000 (2 to 78")
- -20 to +50 °C (-4 to +122 °F) for polyurethane, DN 25 to 1200 (1 to 48")

Conductivity


≥ 5 µS/cm for liquids in general

i Note that in the case of the remote version, the requisite minimum conductivity also depends on the cable length (→ 36).

Pressure-temperature ratings


The following pressure-temperature ratings refer to the entire device and not just the process connection.

Process connection: fixed flange according to EN 1092-1 (DIN 2501)




■ 24 Process connection material: stainless steel, 1.4404/1.4571/F316L; carbon steel, A105/FE410WB/P250GH/S235JRG2/S235JR+N

A0021188-EN

Process connection: fixed flange according to ASME B16.5


A0021185-EN

图 25 Process connection material: stainless steel, F316L similar to 1.4404



A0021182-EN


图 26 Process connection material: carbon steel, A105/A515(70)

Process connection: fixed flange according to AWWA C207

A0021409-EN

图 27 Process connection material: carbon steel, A105/A181/P265GH/S275JR


Process connection: fixed flange according to AS 2129



A0021189-EN

28 Process connection material: carbon steel, A105/FE410WB/P235GH/P265GH/S235JRG2


Process connection: fixed flange according to AS 4087



A0023077-EN

29 Process connection material: carbon steel, A105/P265GH/S275JR

Process connection: fixed flange according to JIS B2220



A0021183-EN

30 Process connection material: stainless steel, F316L similar to 1.4404; carbon steel, A105/A350LF2

Pressure tightness*Liner: hard rubber*

Nominal diameter		Limit values for absolute pressure in [mbar] ([psi]) for fluid temperatures:		
[mm]	[in]	+25 °C (+77 °F)	+50 °C (+122 °F)	+80 °C (+176 °F)
50...2000	2...78	0 (0)	0 (0)	0 (0)

Liner: polyurethane

Nominal diameter		Limit values for absolute pressure in [mbar] ([psi]) for fluid temperatures:	
[mm]	[in]	+25 °C (+77 °F)	+50 °C (+122 °F)
25...1200	1...48	0 (0)	0 (0)

Flow limit

The diameter of the pipe and the flow rate determine the nominal diameter of the sensor. The optimum velocity of flow is between 2 to 3 m/s (6.56 to 9.84 ft/s). Also match the velocity of flow (v) to the physical properties of the fluid:

- $v < 2$ m/s (6.56 ft/s): for abrasive fluids (e.g. potter's clay, lime milk, ore slurry)
- $v > 2$ m/s (6.56 ft/s): for fluids producing buildup (e.g. wastewater sludges)


 A necessary increase in the flow velocity can be achieved by reducing the sensor nominal diameter.

 For an overview of the measuring range full scale values, see the "Measuring range" section

 For custody transfer, the applicable approval determines the permitted measuring range.

Pressure loss

- No pressure loss occurs if the sensor is installed in a pipe with the same nominal diameter.
- Pressure losses for configurations incorporating adapters according to DIN EN 545 (→ [35](#))

System pressure

A0015594

Never install the sensor on the pump suction side in order to avoid the risk of low pressure, and thus damage to the liner.

 Furthermore, install pulse dampers if reciprocating, diaphragm or peristaltic pumps are used.

- 
- For information on the liner's resistance to partial vacuum (→ [43](#))
 - Information on the shock resistance of the measuring system (→ [39](#))
 - Information on the vibration resistance of the measuring system (→ [39](#))


Vibrations

In the event of very strong vibrations, the pipe and sensor must be supported and fixed.

It is also advisable to mount the sensor and transmitter separately.

 Information on the shock resistance of the measuring system (→ [39](#))

 Information on the vibration resistance of the measuring system (→ [39](#))



31 Measures to avoid device vibrations ($L > 10 \text{ m (33 ft)}$)

Custody transfer measurement

As an option, Promag W 400 is tested in accordance with OIML R49 and has an EC type-examination certificate according to Measuring Instruments Directive 2004/22/EC (MID) for service subject to legal metrological control ("custody transfer") for cold water (Annex MI-001).

The permitted fluid temperature in these applications is 0 to +50 °C (+32 to +122 °F).

The device is used with a legally controlled totalizer on the local display and optionally with a legally controlled pulse output.

Measuring devices subject to legal metrological control totalize in both directions, i.e. all the outputs consider flow components in the positive (forward) and negative (reverse) flow direction.

Generally a measuring device subject to legal metrological control is secured against tampering by seals on the transmitter or sensor. These seals may normally only be opened by a representative of the competent authority for legal metrology controls.


- i** After putting the device into circulation or after sealing the device, operation is only possible to a limited extent.
- Detailed ordering information is available from your local Endress+Hauser sales center for national approvals as cold water meters based on OIML R49.

Mechanical construction

Design, dimensions

Compact version

Order code for "Housing", option M "Compact, Polycarbonate" or option A "Compact, alu, coated" with DN 25 to 300 (1 to 12")



Dimensions in SI units

DN ¹⁾ [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	J [mm]	K ²⁾ [mm]
25	193	103	90	167	222	84	306	120	94	200
32	193	103	90	167	222	84	306	120	94	200
40	193	103	90	167	222	84	306	120	94	200
50	193	103	90	167	222	84	306	120	94	200
65	193	103	90	167	247	109	356	180	94	200
80	193	103	90	167	247	109	356	180	94	200
100	193	103	90	167	247	109	356	180	94	250
125	193	103	90	167	287	150	437	260	140	250
150	193	103	90	167	287	150	437	260	140	300
200	193	103	90	167	312	180	492	324	156	350
250	193	103	90	167	337	205	542	400	166	450
300	193	103	90	167	362	230	592	460	166	500


- 1) EN (DIN), AS, JIS; For flanges according to AS, only nominal diameters DN 80, 100 and 150 to 300 are available.
 2) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Dimensions in US units

DN ¹⁾ [in]	A [in]	B [in]	C [in]	D [in]	E [in]	F [in]	G [in]	H [in]	J [in]	K ²⁾ [in]
1	7.60	4.06	3.54	6.57	8.74	3.31	12.1	4.72	3.70	7.87
1 ½	7.60	4.06	3.54	6.57	8.74	3.31	12.1	4.72	3.70	7.87
2	7.60	4.06	3.54	6.57	8.74	3.31	12.1	4.72	3.70	7.87
3	7.60	4.06	3.54	6.57	9.72	4.29	14.0	7.09	3.70	7.87
4	7.60	4.06	3.54	6.57	9.72	4.29	14.0	7.09	3.70	9.84
6	7.60	4.06	3.54	6.57	11.3	5.91	17.2	10.2	5.51	11.8
8	7.60	4.06	3.54	6.57	12.3	7.09	19.4	12.8	6.14	13.8
10	7.60	4.06	3.54	6.57	13.3	8.07	21.4	15.8	6.14	17.7
12	7.60	4.06	3.54	6.57	14.3	9.06	23.4	18.1	6.54	19.7

- 1) ASME
 2) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Order code for "Housing", option Q "Compact, Polycarbonate, tilted" or option R "Compact, alu, coated, tilted" with DN 25 to 300 (1 to 12")



Dimensions in SI units

DN ¹⁾ [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	J [mm]	K ²⁾ [mm]
25	199	119	80	167	267	84	351	120	94	200
32	199	119	80	167	267	84	351	120	94	200
40	199	119	80	167	267	84	351	120	94	200
50	199	119	80	167	267	84	351	120	94	200
65	199	119	80	167	292	109	401	180	94	200
80	199	119	80	167	292	109	401	180	94	200
100	199	119	80	167	292	109	401	180	94	250
125	199	119	80	167	332	150	482	260	140	250
150	199	119	80	167	332	150	482	260	140	300
200	199	119	80	167	357	180	537	324	156	350
250	199	119	80	167	382	205	587	400	166	450
300	199	119	80	167	407	230	637	460	166	500

- 1) EN (DIN), AS, JIS; For flanges according to AS, only nominal diameters DN 80, 100 and 150 to 300 are available.
- 2) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Dimensions in US units

DN ¹⁾ [in]	A [in]	B [in]	C [in]	D [in]	E [in]	F [in]	G [in]	H [in]	J [in]	K ²⁾ [in]
1	7.83	4.69	3.15	6.57	10.5	3.31	13.8	4.72	3.70	7.87
1 ½	7.83	4.69	3.15	6.57	10.5	3.31	13.8	4.72	3.70	7.87
2	7.83	4.69	3.15	6.57	10.5	3.31	13.8	4.72	3.70	7.87
3	7.83	4.69	3.15	6.57	11.5	4.29	15.8	7.09	3.70	7.87
4	7.83	4.69	3.15	6.57	11.5	4.29	15.8	7.09	3.70	9.84
6	7.83	4.69	3.15	6.57	13.1	5.91	19.0	10.2	5.51	11.8

DN ¹⁾ [in]	A [in]	B [in]	C [in]	D [in]	E [in]	F [in]	G [in]	H [in]	J [in]	K ²⁾ [in]
8	7.83	4.69	3.15	6.57	14.0	7.09	21.1	12.8	6.14	13.8
10	7.83	4.69	3.15	6.57	15.0	8.07	23.1	15.8	6.14	17.7
12	7.83	4.69	3.15	6.57	16.0	9.06	25.1	18.1	6.54	19.7


1) ASME

2) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Order code for "Sensor Option", option CA in combination with order code for "Calibration flow", options A/B/D/E/F/G/H/K/M/N



- Order code for "Calibration flow", options A/B/D/E/F/G/H/K/M/N available for order in conjunction with order code for "Housing", option M "Compact, Polycarbonate"
- Order code for "Calibration flow", options H/K additionally available for order in conjunction with order code for "Housing", option A "Compact, alu, coated"



A0021328

Dimensions in SI units

DN [mm]	A [mm]	B [mm]	C [mm]	D [mm]	F [mm]	G [mm]
25	193	103	90	167	200	188
32	193	103	90	167	200	188
40	193	103	90	167	200	188
50	193	103	90	167	200	188
65	193	103	90	167	200	200
80	193	103	90	167	200	205
100	193	103	90	167	250	218
125	193	103	90	167	250	231
150	193	103	90	167	300	252
200	193	103	90	167	350	278
250	193	103	90	167	450	311
300	193	103	90	167	500	336

Dimension E											
DN [mm]	EN (DIN)				ASME		AS		JIS		
	PN 10 [mm]	PN 16 [mm]	PN 25 [mm]	PN 40 [mm]	Class 150 [mm]	Class 300 [mm]	Table E [mm]	PN 16 [mm]	10K [mm]	20K [mm]	
25	-	-	-	140	140	140	140	-	140	140	
32	-	-	-	140	-	-	-	-	140	140	
40	-	-	-	150	140	155	-	-	140	140	
50	-	-	-	165	153	165	150	150	155	155	
65	-	185	-	185	-	-	-	-	175	175	
80	-	200	-	200	191	210	185	185	185	200	
100	-	220	-	325	229	254	215	215	210	225	
125	-	250	-	270	-	-	-	-	250	270	
150	-	285	-	300	280	318	280	280	280	305	
200	340	340	360	-	343	-	335	335	330	350	
250	395	405	425	-	407	-	405	405	400	430	
300	445	460	485	-	483	-	455	455	445	480	

Dimension H											
DN [mm]	EN (DIN)				ASME		AS		JIS		
	PN 10 [mm]	PN 16 [mm]	PN 25 [mm]	PN 40 [mm]	Class 150 [mm]	Class 300 [mm]	Table E [mm]	PN 16 [mm]	10K [mm]	20K [mm]	
25	-	-	-	258	258	258	258	-	258	258	
32	-	-	-	258	-	-	-	-	258	258	
40	-	-	-	262	258	265	-	-	258	258	
50	-	-	-	270	263	270	262	262	265	265	
65	-	293	-	293	-	-	-	-	288	288	
80	-	305	-	305	300	309	298	298	298	305	
100	-	328	-	380	331	344	325	325	323	330	
125	-	355	-	365	-	-	-	-	355	365	
150	-	394	-	402	391	410	393	393	393	404	
200	448	448	458	-	448	-	445	445	443	452	
250	508	513	523	-	514	-	513	513	511	526	
300	558	566	578	-	578	-	563	563	558	576	

Dimensions in US units

DN [in]	A [in]	B [in]	C [in]	D [in]	F [in]	G [in]
1	7.60	4.06	3.54	6.57	7.87	7.40
2	7.60	4.06	3.54	6.57	7.87	7.40
3	7.60	4.06	3.54	6.57	7.87	8.07
4	7.60	4.06	3.54	6.57	9.84	8.58
6	7.60	4.06	3.54	6.57	11.8	9.92


DN [in]	A [in]	B [in]	C [in]	D [in]	F [in]	G [in]
8	7.60	4.06	3.54	6.57	13.8	10.9
10	7.60	4.06	3.54	6.57	17.7	12.2
12	7.60	4.06	3.54	6.57	19.7	13.2

Dimension E										
DN [in]	EN (DIN)				ASME		AS		JIS	
	PN 10 [in]	PN 16 [in]	PN 25 [in]	PN 40 [in]	Class 150 [in]	Class 300 [in]	Table E [in]	PN 16 [in]	10K [in]	20K [in]
1	-	-	-	5.51	5.51	5.51	5.51	-	5.51	5.51
2	-	-	-	6.50	6.02	6.50	5.91	5.91	6.10	6.10
3	-	7.87	-	7.87	7.52	8.27	7.28	7.28	7.28	7.87
4	-	8.66	-	12.8	9.02	10.0	8.46	8.46	8.27	8.86
6	-	11.2	-	11.8	11.0	12.5	11.0	11.0	11.0	12.0
8	13.4	13.4	14.2	-	13.5	-	13.2	13.2	13.0	13.8
10	15.6	15.9	16.7	-	16.0	-	15.9	15.9	15.8	16.9
12	17.5	18.1	19.1	-	19.0	-	17.9	17.9	17.5	18.9

Dimension H										
DN [in]	EN (DIN)				ASME		AS		JIS	
	PN 10 [in]	PN 16 [in]	PN 25 [in]	PN 40 [in]	Class 150 [in]	Class 300 [in]	Table E [in]	PN 16 [in]	10K [in]	20K [in]
1	-	-	-	10.2	10.2	10.2	10.2	-	10.2	10.2
2	-	-	-	10.6	10.4	10.6	10.3	10.3	10.4	10.4
3	-	12	-	12	11.8	12.2	11.7	11.7	11.7	12
4	-	12.9	-	15	13	13.5	12.8	12.8	12.7	13
6	-	15.5	-	15.8	15.4	16.1	15.5	15.5	15.5	15.9
8	17.6	17.6	18	-	17.6	-	17.5	17.5	17.4	17.8
10	20	20.2	20.6	-	20.2	-	20.2	20.2	20.1	20.7
12	22	22.3	22.8	-	22.8	-	22.2	22.2	22	22.7

Order code for "Sensor Option", option CA in combination with order code for "Calibration flow", options A/B/D/E/F/G/H/K/M/N

-  ■ Order code for "Calibration flow", options A/B/D/E/F/G/H/K/M/N available for order in conjunction with order code for "Housing", option Q "Compact, Polycarbonate, tilted"
 - Order code for "Calibration flow", options H/K additionally available for order in conjunction with order code for "Housing", option R "Compact, alu, coated, tilted"



Dimensions in SI units

DN [mm]	A [mm]	B [mm]	C [mm]	D [mm]	F [mm]	G [mm]
25	199	119	80	167	200	232
32	199	119	80	167	200	232
40	199	119	80	167	200	232
50	199	119	80	167	200	232
65	199	119	80	167	200	244
80	199	119	80	167	200	249
100	199	119	80	167	250	262
125	199	119	80	167	250	275
150	199	119	80	167	300	296
200	199	119	80	167	350	322
250	199	119	80	167	450	355
300	199	119	80	167	500	380

Dimension E

DN [mm]	EN (DIN)				ASME		AS		JIS	
	PN 10 [mm]	PN 16 [mm]	PN 25 [mm]	PN 40 [mm]	Class 150 [mm]	Class 300 [mm]	Table E [mm]	PN 16 [mm]	10K [mm]	20K [mm]
25	-	-	-	140	140	140	140	-	140	140
32	-	-	-	140	-	-	-	-	140	140
40	-	-	-	150	140	155	-	-	140	140
50	-	-	-	165	153	165	150	150	155	155
65	-	185	-	185	-	-	-	-	175	175
80	-	200	-	200	191	210	185	185	185	200
100	-	220	-	325	229	254	215	215	210	225
125	-	250	-	270	-	-	-	-	250	270
150	-	285	-	300	280	318	280	280	280	305
200	340	340	360	-	343	-	335	335	330	350

Dimension E											
DN [mm]	EN (DIN)				ASME		AS		JIS		
	PN 10 [mm]	PN 16 [mm]	PN 25 [mm]	PN 40 [mm]	Class 150 [mm]	Class 300 [mm]	Table E [mm]	PN 16 [mm]	10K [mm]	20K [mm]	
250	395	405	425	-	407	-	405	405	400	430	
300	445	460	485	-	483	-	455	455	445	480	

Dimension H											
DN [mm]	EN (DIN)				ASME		AS		JIS		
	PN 10 [mm]	PN 16 [mm]	PN 25 [mm]	PN 40 [mm]	Class 150 [mm]	Class 300 [mm]	Table E [mm]	PN 16 [mm]	10K [mm]	20K [mm]	
25	-	-	-	302	302	302	302	-	302	302	
32	-	-	-	302	-	-	-	-	302	302	
40	-	-	-	307	302	310	-	-	302	302	
50	-	-	-	315	309	315	307	307	310	310	
65	-	337	-	337	-	-	-	-	332	332	
80	-	349	-	349	345	354	342	342	342	349	
100	-	372	-	425	377	389	370	370	367	375	
125	-	400	-	410	-	-	-	-	400	410	
150	-	439	-	446	436	455	436	436	436	449	
200	492	492	502	-	494	-	490	490	487	497	
250	553	558	568	-	559	-	558	558	555	570	
300	603	610	623	-	622	-	608	608	603	620	


Dimensions in US units

DN [in]	A [in]	B [in]	C [in]	D [in]	F [in]	G [in]
1	7.83	4.69	3.15	6.57	7.87	9.13
2	7.83	4.69	3.15	6.57	7.87	9.13
3	7.83	4.69	3.15	6.57	7.87	9.80
4	7.83	4.69	3.15	6.57	9.84	10.3
6	7.83	4.69	3.15	6.57	11.8	11.7
8	7.83	4.69	3.15	6.57	13.8	12.7
10	7.83	4.69	3.15	6.57	17.7	14.0
12	7.83	4.69	3.15	6.57	19.7	15.0

Dimension E											
DN [in]	EN (DIN)				ASME		AS		JIS		
	PN 10 [in]	PN 16 [in]	PN 25 [in]	PN 40 [in]	Class 150 [in]	Class 300 [in]	Table E [in]	PN 16 [in]	10K [in]	20K [in]	
1	-	-	-	5.51	5.51	5.51	5.51	-	5.51	5.51	
2	-	-	-	6.50	6.02	6.50	5.91	5.91	6.10	6.10	
3	-	7.87	-	7.87	7.52	8.27	7.28	7.28	7.28	7.87	
4	-	8.66	-	12.8	9.02	10.0	8.46	8.46	8.27	8.86	
6	-	11.2	-	11.8	11.0	12.5	11.0	11.0	11.0	12.0	
8	13.4	13.4	14.2	-	13.5	-	13.2	13.2	13.0	13.8	
10	15.6	15.9	16.7	-	16.0	-	15.9	15.9	15.7	16.9	
12	17.5	18.1	19.1	-	19.0	-	17.9	17.9	17.5	18.9	

Dimension H											
DN [in]	EN (DIN)				ASME		AS		JIS		
	PN 10 [in]	PN 16 [in]	PN 25 [in]	PN 40 [in]	Class 150 [in]	Class 300 [in]	Table E [in]	PN 16 [in]	10K [in]	20K [in]	
1	-	-	-	11.9	11.9	11.9	11.9	-	11.9	11.9	
2	-	-	-	12.4	12.2	12.4	12.1	12.1	12.2	12.2	
3	-	13.7	-	13.7	13.6	13.9	13.5	13.5	13.5	13.7	
4	-	14.6	-	16.7	14.8	15.3	14.6	14.6	14.4	14.8	
6	-	17.3	-	17.6	17.2	17.9	17.2	17.2	17.2	17.7	
8	19.4	19.4	19.8	-	19.4	-	19.3	19.3	19.2	19.6	
10	21.8	22.0	22.4	-	22.0	-	22.0	22.0	21.9	22.4	
12	23.7	24.0	24.5	-	24.5	-	23.9	23.9	23.7	24.4	

Order code for "Housing", option M "Compact, Polycarbonate" or option A "Compact, alu, coated" with DN 350 to 2000 (14 to 78")



Dimensions in SI units

DN ¹⁾ [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	J [mm]	K ²⁾ [mm]
350	193	103	90	167	432	282	714	564	276	550
375	193	103	90	167	458	308	766	616	276	600
400	193	103	90	167	458	308	766	616	276	600
450	193	103	90	167	483	333	816	666	292	650
500	193	103	90	167	508	359	867	717	292	650
600	193	103	90	167	560	410	970	821	402	780
700	193	103	90	167	662	512	1174	1024	589	910
750	193	103	90	167	662	512	1174	1024	626	975
800	193	103	90	167	683	534	1217	1067	647	1040
900	193	103	90	167	760	610	1370	1220	785	1170
1000	193	103	90	167	836	686	1522	1372	862	1300
1050	193	103	90	167	862	712	1574	1424	912	1365
1200	193	103	90	167	961	811	1772	1622	992	1560
1350	193	103	90	167	1062	912	1974	1824	1252	1755
1400	193	103	90	167	1137	987	2124	1974	1252	1820
1500	193	103	90	167	1161	1011	2172	2022	1392	1950
1600	193	103	90	167	1206	1056	2262	2112	1482	2080
1650	193	103	90	167	1243	1093	2336	2186	1482	2145

DN ¹⁾ [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	J [mm]	K ²⁾ [mm]
1800	193	103	90	167	1338	1188	2526	2376	1632	2340
2000	193	103	90	167	1388	1238	2626	2476	1732	2600


- 1) EN (DIN), AS; For flanges according to AS, only nominal diameters DN 350, 400, 500 and 600 are available.
 2) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Dimensions in US units

DN ¹⁾ [in]	A [in]	B [in]	C [in]	D [in]	E [in]	F [in]	G [in]	H [in]	J [in]	K ²⁾ [in]
14	7.60	4.06	3.54	6.57	17.0	11.1	28.1	22.2	10.9	21.7
15	7.60	4.06	3.54	6.57	18.0	12.1	30.1	24.2	10.9	23.6
16	7.60	4.06	3.54	6.57	18.0	12.1	30.1	24.2	10.9	23.6
18	7.60	4.06	3.54	6.57	19.0	13.1	32.1	26.2	11.5	25.6
20	7.60	4.06	3.54	6.57	20.0	14.1	34.1	28.2	11.5	25.6
24	7.60	4.06	3.54	6.57	22.1	16.2	38.3	32.3	15.8	30.7
28	7.60	4.06	3.54	6.57	26.1	20.1	46.2	40.3	23.2	35.8
30	7.60	4.06	3.54	6.57	26.1	20.1	46.2	40.3	24.6	38.4
32	7.60	4.06	3.54	6.57	26.9	21.0	47.9	42.0	25.5	40.9
36	7.60	4.06	3.54	6.57	29.9	24.0	53.9	48.0	30.9	46.0
40	7.60	4.06	3.54	6.57	32.9	27.0	59.9	54.0	33.9	51.2
42	7.60	4.06	3.54	6.57	33.9	28.0	61.9	56.0	35.9	53.7
48	7.60	4.06	3.54	6.57	37.8	31.9	69.7	63.8	39.0	61.4
54	7.60	4.06	3.54	6.57	41.8	35.9	77.7	71.8	42.3	69.1
60	7.60	4.06	3.54	6.57	45.7	39.8	85.5	79.6	54.8	76.8
66	7.60	4.06	3.54	6.57	48.9	43.0	91.9	86.0	58.4	84.4
72	7.60	4.06	3.54	6.57	52.7	46.8	99.5	93.5	64.2	92.1
78	7.60	4.06	3.54	6.57	54.7	48.7	103.4	97.5	68.2	102.3

- 1) ASME, AWWA; flanges ≤ 24 in only available according to ASME, flanges ≥ 28 in only available according to AWWA.
 2) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Order code for "Housing", option Q "Compact, Polycarbonate, inclined" or option R "Compact, alu, coated, tilted" with DN 350 to 2000 (14 to 78")



Dimensions in SI units

DN ¹⁾ [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	J [mm]	K ²⁾ [mm]
350	199	119	80	167	477	282	759	564	276	550
375	199	119	80	167	503	308	811	616	276	600
400	199	119	80	167	503	308	811	616	276	600
450	199	119	80	167	528	333	861	666	292	650
500	199	119	80	167	553	359	912	717	292	650
600	199	119	80	167	605	410	1015	821	402	780
700	199	119	80	167	707	512	1219	1024	589	910
750	199	119	80	167	707	512	1219	1024	626	975
800	199	119	80	167	728	534	1262	1067	647	1040
900	199	119	80	167	805	610	1415	1220	785	1170
1000	199	119	80	167	881	686	1567	1372	862	1300
1050	199	119	80	167	907	712	1619	1424	912	1365
1200	199	119	80	167	1006	811	1817	1622	992	1560
1350	199	119	80	167	1107	912	2019	1824	1252	1755
1400	199	119	80	167	1182	987	2169	1974	1252	1820
1500	199	119	80	167	1206	1011	2217	2022	1392	1950
1600	199	119	80	167	1251	1056	2307	2112	1482	2080
1650	199	119	80	167	1288	1093	2381	2186	1482	2145

DN ¹⁾ [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	J [mm]	K ²⁾ [mm]
1800	199	119	80	167	1383	1188	2571	2376	1632	2340
2000	199	119	80	167	1433	1238	2671	2476	1732	2600


- 1) EN (DIN), AS; For flanges according to AS, only nominal diameters DN 350, 400, 500 and 600 are available.
 2) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Dimensions in US units

DN ¹⁾ [in]	A [in]	B [in]	C [in]	D [in]	E [in]	F [in]	G [in]	H [in]	J [in]	K ²⁾ [in]
14	7.83	4.69	3.15	6.57	18.8	11.1	29.9	22.2	10.9	21.7
15	7.83	4.69	3.15	6.57	19.8	12.1	31.9	24.2	10.9	23.6
16	7.83	4.69	3.15	6.57	19.8	12.1	31.9	24.2	10.9	23.6
18	7.83	4.69	3.15	6.57	20.8	13.1	33.9	26.2	11.5	25.6
20	7.83	4.69	3.15	6.57	21.8	14.1	35.9	28.2	11.5	25.6
24	7.83	4.69	3.15	6.57	23.8	16.2	40.0	32.3	15.8	30.7
28	7.83	4.69	3.15	6.57	27.8	20.2	48.0	40.3	23.2	35.8
30	7.83	4.69	3.15	6.57	27.8	20.2	48.0	40.3	24.6	38.4
32	7.83	4.69	3.15	6.57	28.7	21.0	49.7	42.0	25.5	40.9
36	7.83	4.69	3.15	6.57	32.7	24.0	55.7	48.0	30.9	46.0
40	7.83	4.69	3.15	6.57	34.7	27.0	61.7	54.0	33.9	51.2
42	7.83	4.69	3.15	6.57	35.7	28.0	63.7	56.0	35.9	53.7
48	7.83	4.69	3.15	6.57	39.6	31.9	71.5	63.8	39.0	61.4
54	7.83	4.69	3.15	6.57	43.6	35.9	79.5	71.8	42.3	69.1
60	7.83	4.69	3.15	6.57	47.5	39.8	87.3	79.6	54.8	76.8
66	7.83	4.69	3.15	6.57	50.7	43.0	93.7	86.0	58.4	84.4
72	7.83	4.69	3.15	6.57	54.4	46.8	101.2	93.5	64.2	92.1
78	7.83	4.69	3.15	6.57	56.4	48.8	105.2	97.5	68.2	102.3

- 1) ASME, AWWA; flanges \leq 24 in only available according to ASME, flanges \geq 28 in only available according to AWWA.
 2) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Order code for "Housing", option M "Compact, Polycarbonate" or option A "Compact, alu, coated"; order code for "Design", option A "Insertion length short" with DN 350 to 2000 (14 to 78")



Dimensions in SI units

DN [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	H [mm]	J [mm]
350	193	103	90	167	386	290	550
375	193	103	90	167	412	290	600
400	193	103	90	167	412	290	600
450	193	103	90	167	440	290	600
500	193	103	90	167	465	290	600
600	193	103	90	167	506	290	600
700	193	103	90	167	571	424	700
750	193	103	90	167	608	454	750
800	193	103	90	167	627	500	800
900	193	103	90	167	677	580	900
1000	193	103	90	167	727	660	1000
1050	193	103	90	167	763	755	1050
1200	193	103	90	167	841	828	1200
1350	193	103	90	167	953	1008	1350
1400	193	103	90	167	953	1008	1400
1500	193	103	90	167	1053	1147	1500
1600	193	103	90	167	1053	1147	1600
1650	193	103	90	167	1104	1284	1650
1800	193	103	90	167	1161	1379	1800
2000	193	103	90	167	1272	1569	2000

DN [mm]	Dimension F					Dimension G				
	EN (DIN)			ASME AWWA [mm]	AS [mm]	EN (DIN)			ASME AWWA [mm]	AS [mm]
	PN 6 [mm]	PN 10 [mm]	PN 16 [mm]			PN 6 [mm]	PN 10 [mm]	PN 16 [mm]		
350	631	638	702	653	648	490	505	520	533	525
375	-	-	-	-	687	-	-	-	-	550
400	682	694	760	710	702	540	565	580	597	580
450	737	747	823	757	760	595	615	640	635	640
500	787	800	926	814	817	645	670	715	699	705
600	883	896	1026	912	918	755	780	840	813	825
700	1001	1018	1145	1034	1026	860	895	910	927	910
750	-	-	-	1100	1106	-	-	-	984	995
800	1115	1135	1240	1157	1157	975	1015	1025	1060	1060
900	1215	1235	1240	1261	1265	1075	1115	1125	1168	1175
1000	1315	1342	1355	1372	1355	1175	1230	1225	1289	1255
1050	-	-	-	1436	-	-	-	-	1346	-
1200	1544	1569	1584	1597	1586	1405	1455	1255	1511	1490
1350	-	-	-	1795	-	-	-	-	1683	-
1400	1768	1791	1796	-	-	1630	1675	1685	-	-
1500	-	-	-	1980	-	-	-	-	1854	-
1600	1968	2011	2019	-	-	1830	1915	1930	-	-
1650	-	-	-	2120	-	-	-	-	2032	-
1800	2183	2218	2226	2259	-	2045	2115	2130	2197	-
2000	2404	2434	2444	2453	-	2265	2325	2345	2362	-


Dimensions in US units

DN [in]	A [in]	B [in]	C [in]	D [in]	E [in]	H [in]	J [in]
14	7.60	4.06	3.54	6.57	15.2	11.4	21.6
15	7.60	4.06	3.54	6.57	16.2	11.4	23.6
16	7.60	4.06	3.54	6.57	16.2	11.4	23.6
18	7.60	4.06	3.54	6.57	17.3	11.4	23.6
20	7.60	4.06	3.54	6.57	18.3	11.4	23.6
24	7.60	4.06	3.54	6.57	19.9	11.4	23.6
28	7.60	4.06	3.54	6.57	22.5	16.7	27.6
30	7.60	4.06	3.54	6.57	23.9	17.9	29.5
32	7.60	4.06	3.54	6.57	24.7	19.7	31.5
36	7.60	4.06	3.54	6.57	26.6	22.8	35.4
40	7.60	4.06	3.54	6.57	28.6	26.0	39.4
42	7.60	4.06	3.54	6.57	30.0	29.7	41.3
48	7.60	4.06	3.54	6.57	33.1	32.6	47.2
54	7.60	4.06	3.54	6.57	37.5	39.7	53.1
60	7.60	4.06	3.54	6.57	41.4	45.2	59.0

DN [in]	A [in]	B [in]	C [in]	D [in]	E [in]	H [in]	J [in]
66	7.60	4.06	3.54	6.57	43.4	50.6	64.9
72	7.60	4.06	3.54	6.57	45.7	54.3	70.8
78	7.60	4.06	3.54	6.57	50.1	61.8	78.7

DN [in]	Dimension F					Dimension G				
	EN (DIN)		ASME	AS		EN (DIN)		ASME	AS	
PN 6 [in]	PN 10 [in]	PN 16 [in]	AWWA [in]		PN 6 [in]	PN 10 [in]	PN 16 [in]	AWWA [in]		
14	24.8	25.1	27.6	25.7	25.5	19.3	19.9	20.5	21.0	20.7
15	-	-	-	-	27	-	-	-	-	21.7
16	26.8	27.3	30.0	27.0	27.6	21.3	22.2	22.8	23.5	22.8
18	29.0	29.4	32.4	29.8	29.9	23.4	24.2	25.2	25.0	25.2
20	31.0	31.5	36.5	32.0	32.1	25.4	26.4	28.1	27.5	27.8
24	34.7	35.3	40.4	35.9	36.1	29.7	30.7	33.1	32.0	32.5
28	39.4	40.1	45.1	40.7	40.4	33.9	35.2	35.8	36.5	35.8
30	-	-	-	43.3	43.5	-	-	-	38.7	39.2
32	43.9	44.7	48.8	45.5	45.5	38.4	40.0	40.4	41.7	41.7
36	47.8	48.6	48.8	49.6	49.8	42.3	43.9	44.3	46.0	46.3
40	51.7	52.8	53.4	54.0	53.3	46.3	48.4	48.2	50.7	49.4
42	-	-	-	56.5	-	-	-	-	53.0	-
48	60.8	61.7	62.4	62.9	62.4	55.3	57.3	49.4	59.5	58.7
54	-	-	-	70.6	-	-	-	-	66.3	-
60	-	-	-	77.9	-	-	-	-	73.0	-
66	-	-	-	83.4	-	-	-	-	80.0	-
72	85.9	87.3	87.6	88.9	-	80.5	83.3	83.9	86.5	-
78	94.6	95.8	96.2	96.6	-	89.2	91.5	92.3	93.0	-

Order code for "Housing", option Q "Compact, Polycarbonate, inclined" or option R "Compact, alu, coated, tilted"; order code for "Design", option A "Insertion length short" with DN 350 to 2000 (14 to 78")



Dimensions in SI units

DN [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	H [mm]	J [mm]
350	199	119	80	167	431	290	550
375	199	119	80	167	457	290	600
400	199	119	80	167	457	290	600
450	199	119	80	167	485	290	600
500	199	119	80	167	510	290	600
600	199	119	80	167	551	290	600
700	199	119	80	167	616	424	700
750	199	119	80	167	653	454	750
800	199	119	80	167	672	500	800
900	199	119	80	167	722	580	900
1000	199	119	80	167	772	660	1000
1050	199	119	80	167	808	755	1050
1200	199	119	80	167	886	828	1200
1350	199	119	80	167	998	1008	1350
1400	199	119	80	167	953	1008	1400
1500	199	119	80	167	1098	1147	1500
1600	199	119	80	167	1098	1147	1600
1650	199	119	80	167	1149	1284	1650
1800	199	119	80	167	1206	1379	1800
2000	199	119	80	167	1317	1569	2000

DN [mm]	Dimension F					Dimension G				
	EN (DIN)			ASME AWWA	AS [mm]	EN (DIN)			ASME AWWA	AS [mm]
	PN 6 [mm]	PN 10 [mm]	PN 16 [mm]			PN 6 [mm]	PN 10 [mm]	PN 16 [mm]		
350	676	683	618	698	693	490	505	520	533	525
375	-	-	-	-	732	-	-	-	-	550
400	727	739	672	755	747	540	565	580	597	580
450	782	792	732	802	805	595	615	640	635	640
500	832	845	795	859	862	645	670	715	699	705
600	928	941	898	957	963	755	780	840	813	825
700	1046	1063	1008	1079	1071	860	895	910	927	910
750	-	-	-	1145	1151	-	-	-	984	995
800	1160	1180	1112	1202	1202	975	1015	1025	1060	1060
900	1260	1280	1212	1306	1310	1075	1115	1125	1168	1175
1000	1360	1387	1327	1417	1400	1175	1230	1225	1289	1255
1050	-	-	-	1481	-	-	-	-	1346	-
1200	1589	1614	1556	1642	1631	1405	1455	1255	1511	1490
1350	-	-	-	1840	-	-	-	-	1683	-
1400	1813	1836	1768	-	-	1630	1675	1685	-	-
1500	-	-	-	2025	-	-	-	-	1854	-
1600	2013	2056	1991	-	-	1830	1915	1930	-	-
1650	-	-	-	2165	-	-	-	-	2032	-
1800	2228	2263	2198	2304	-	2045	2115	2130	2197	-
2000	2449	2479	2416	2498	-	2265	2325	2345	2362	-

Dimensions in US units


DN [in]	A [in]	B [in]	C [in]	D [in]	E [in]	H [in]	J [in]
14	7.83	4.69	3.15	6.57	17.0	11.4	21.6
15	7.83	4.69	3.15	6.57	18.0	11.4	23.6
16	7.83	4.69	3.15	6.57	18.0	11.4	23.6
18	7.83	4.69	3.15	6.57	19.1	11.4	23.6
20	7.83	4.69	3.15	6.57	20.1	11.4	23.6
24	7.83	4.69	3.15	6.57	21.7	11.4	23.6
28	7.83	4.69	3.15	6.57	24.3	16.7	27.6
30	7.83	4.69	3.15	6.57	25.7	17.9	29.5
32	7.83	4.69	3.15	6.57	26.5	19.7	31.5
36	7.83	4.69	3.15	6.57	28.4	22.8	35.4
40	7.83	4.69	3.15	6.57	30.4	26.0	39.4
42	7.83	4.69	3.15	6.57	31.8	29.7	41.3
48	7.83	4.69	3.15	6.57	34.9	32.6	47.2
54	7.83	4.69	3.15	6.57	39.3	39.7	53.1
60	7.83	4.69	3.15	6.57	43.2	45.2	59.0

DN [in]	A [in]	B [in]	C [in]	D [in]	E [in]	H [in]	J [in]
66	7.83	4.69	3.15	6.57	45.2	50.6	64.9
72	7.83	4.69	3.15	6.57	47.5	54.3	70.8
78	7.83	4.69	3.15	6.57	51.9	61.8	78.7

DN [in]	Dimension F					Dimension G				
	EN (DIN)			ASME AWWA	AS	EN (DIN)			ASME AWWA	AS
PN 6 [in]	PN 10 [in]	PN 16 [in]	[in]	[in]	[in]	PN 6 [in]	PN 10 [in]	PN 16 [in]	[in]	[in]
14	26.6	26.9	24.3	27.5	27.3	19.3	19.9	20.5	21.0	20.7
15	-	-	-	-	28.8	-	-	-	-	21.7
16	28.6	29.1	26.5	28.8	29.4	21.3	22.2	22.8	23.5	22.8
18	30.8	31.2	28.8	31.6	31.7	23.4	24.2	25.2	25.0	25.2
20	32.8	33.3	31.3	33.8	33.9	25.4	26.4	28.1	27.5	27.8
24	36.5	37.1	35.4	37.7	37.9	29.7	30.7	33.1	32.0	32.5
28	41.2	41.9	39.7	42.5	42.2	33.9	35.2	35.8	36.5	35.8
30	-	-	-	45.1	45.3	-	-	-	38.7	39.2
32	45.7	46.5	43.8	47.3	47.3	38.4	40.0	40.4	41.7	41.7
36	49.6	50.4	47.7	51.4	49.8	42.3	43.9	44.3	46.0	46.3
40	53.5	54.6	52.2	55.8	55.1	46.3	48.4	48.2	50.7	49.4
42	-	-	-	58.3	-	-	-	-	53.0	-
48	62.6	63.5	61.3	64.7	64.2	55.3	57.3	49.4	59.5	58.7
54	-	-	-	72.4	-	-	-	-	66.3	-
60	-	-	-	79.7	-	-	-	-	73.0	-
66	-	-	-	85.2	-	-	-	-	80.0	-
72	87.7	89.1	86.5	90.7	-	80.5	83.3	83.9	86.5	-
78	96.4	97.6	95.1	98.4	-	89.2	91.5	92.3	93.0	-

Transmitter remote version

Order code for "Housing", option N "Remote, polycarbonate" or option P "Remote, aluminum coated"



A0020522

Dimensions in SI units


A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]
167	24	187	21	232	80	50	240

Dimensions in US units

A [in]	B [in]	C [in]	D [in]	E [in]	F [in]	G [in]	H [in]
6.57	0.94	7.36	0.83	9.13	3.15	1.97	9.5

Sensor remote version

DN 25 to 300 (1 to 12")

*Dimensions in SI units*

DN¹⁾ [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G²⁾ [mm]
25	136	207	84	291	120	94	200
32	136	207	84	291	120	94	200
40	136	207	84	291	120	94	200
50	136	207	84	291	120	94	200
65	136	232	109	341	180	94	200
80	136	232	109	341	180	94	200
100	136	232	109	341	180	94	250
125	136	272	150	422	260	140	250
150	136	272	150	422	260	140	300
200	136	297	180	477	324	156	350
250	136	322	205	527	400	156	450
300	136	347	230	577	460	166	500

1) EN (DIN), AS, JIS; For flanges according to AS, only nominal diameters DN 80, 100 and 150 to 300 are available.

2) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Dimensions in US units

DN¹⁾ [in]	A [in]	B [in]	C [in]	D [in]	E [in]	F [in]	G²⁾ [in]
1	5.35	8.15	3.31	11.5	4.72	3.70	7.87
1 ½	5.35	8.15	3.31	11.5	4.72	3.70	7.87
2	5.35	8.15	3.31	11.5	4.72	3.70	7.87
3	5.35	9.13	4.29	13.4	7.09	3.70	7.87
4	5.35	9.13	4.29	13.4	7.09	3.70	9.84
6	5.35	10.7	5.91	16.6	10.2	5.51	11.8
8	5.35	11.7	7.09	18.8	12.8	6.14	13.8


DN ¹⁾ [in]	A [in]	B [in]	C [in]	D [in]	E [in]	F [in]	G ²⁾ [in]
10	5.35	12.7	8.07	20.8	15.8	6.14	17.7
12	5.35	13.7	9.06	22.8	18.1	6.54	19.7

1) ASME

2) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Order code for "Sensor option", option CA...CE "Corrosion protection" with DN 25 to 300 (1 to 12")

Option	Description
CA	IP66/67, Type 4X, fully welded; corrosion protection EN ISO 12944 C5-M
CB	IP68, Type 6P, fact-potted; corrosion protection EN ISO 12944 C5-M/Im1/Im2/Im3
CC	IP68, Type 6P, cust-potted; corrosion protection EN ISO 12944 C5-M/Im1/Im2/Im3
CD	Buried IP68, Type 6P, fact-potted; corrosion protection EN ISO 12944 Im2/Im3
CE	Buried IP68, Type 6P, cust-potted; corrosion protection EN ISO 12944 Im2/Im3



Dimensions in SI units

DN [mm]	A [mm]	B [mm]	E [mm]
25	112	189	200
32	112	189	200
40	112	189	200
50	112	189	200
65	112	202	200
80	112	207	200
100	112	219	250
125	112	232	250
150	112	254	300
200	112	279	350
250	112	313	450
300	112	338	500

Dimension C											
DN [mm]	EN (DIN)				ASME		AS		JIS		
	PN 10 [mm]	PN 16 [mm]	PN 25 [mm]	PN 40 [mm]	Class 150 [mm]	Class 300 [mm]	Table E [mm]	PN 16 [mm]	10K [mm]	20K [mm]	
25	-	-	-	260	260	260	260	-	260	260	
32	-	-	-	260	-	-	-	-	260	260	
40	-	-	-	264	260	267	-	-	260	260	
50	-	-	-	272	265	272	264	264	267	267	
65	-	295	-	295	-	-	-	-	290	290	
80	-	307	-	307	302	311	300	300	300	307	
100	-	330	-	382	333	346	327	327	325	332	
125	-	357	-	367	-	-	-	-	357	367	
150	-	396	-	404	393	412	395	395	395	406	
200	450	450	460	-	450	-	447	447	445	454	
250	510	515	525	-	516	-	515	515	513	528	
300	560	568	580	-	580	-	565	565	560	578	

Dimension D											
DN [mm]	EN (DIN)				ASME		AS		JIS		
	PN 10 [mm]	PN 16 [mm]	PN 25 [mm]	PN 40 [mm]	Class 150 [mm]	Class 300 [mm]	Table E [mm]	PN 16 [mm]	10K [mm]	20K [mm]	
25	-	-	-	140	140	140	140	-	140	140	
32	-	-	-	140	-	-	-	-	140	140	
40	-	-	-	150	140	155	-	-	140	140	
50	-	-	-	165	152.4	165	150	150	155	155	
65	-	185	-	185	-	-	-	-	175	175	
80	-	200	-	200	190.5	209.6	185	185	185	200	
100	-	220	-	325	228.6	254	215	215	210	225	
125	-	250	-	270	-	-	-	-	250	270	
150	-	285	-	300	279.4	317.5	280	280	280	305	
200	340	340	360	-	342.9	-	335	335	330	350	
250	395	405	425	-	406.4	-	405	405	400	430	
300	445	460	485	-	482.6	-	455	455	445	480	

Dimensions in US units


DN [in]	A [in]	B [in]	E [in]
1	4.41	7.44	7.87
2	4.41	7.44	7.87
3	4.41	8.15	7.87
4	4.41	8.62	9.84
6	4.41	10.0	11.8

DN [in]	A [in]	B [in]	E [in]
8	4.41	11.0	13.8
10	4.41	12.3	17.7
12	4.41	13.3	19.7

Dimension C											
DN [in]	EN (DIN)					ASME		AS		JIS	
	PN 10 [in]	PN 16 [in]	PN 25 [in]	PN 40 [in]	Class 150 [in]	Class 300 [in]	Table E [in]	PN 16 [in]	10K [in]	20K [in]	
1	-	-	-	10.2	10.2	10.2	10.2	-	10.2	10.2	
2	-	-	-	10.7	10.4	10.7	10.4	10.4	10.5	10.5	
3	-	12.1	-	12.1	11.9	12.2	11.8	11.8	11.8	12.1	
4	-	13.0	-	15.0	13.1	13.6	12.9	12.9	12.8	13.1	
6	-	15.6	-	15.9	15.5	16.2	15.6	15.6	15.6	16.0	
8	17.7	17.7	18.1	-	17.7	-	17.6	17.6	17.5	17.9	
10	20.1	20.3	20.7	-	20.3	-	20.3	20.3	20.2	20.8	
12	22.0	22.4	22.8	-	22.8	-	22.2	22.2	22.0	22.8	

Dimension D											
DN [in]	EN (DIN)					ASME		AS		JIS	
	PN 10 [in]	PN 16 [in]	PN 25 [in]	PN 40 [in]	Class 150 [in]	Class 300 [in]	Table E [in]	PN 16 [in]	10K [in]	20K [in]	
1	-	-	-	5.51	5.51	5.51	5.51	-	5.51	5.51	
2	-	-	-	6.50	6.00	6.50	5.91	5.91	6.10	6.10	
3	-	7.87	-	7.87	7.5	8.25	7.28	7.28	7.28	7.87	
4	-	8.66	-	12.8	9.00	10.0	8.46	8.46	8.27	8.86	
6	-	11.2	-	11.8	11.0	12.5	11.0	11.0	11.0	12.0	
8	13.4	13.4	14.2	-	13.5	-	13.2	13.2	13.0	13.8	
10	15.6	15.9	16.7	-	16.0	-	15.9	15.9	15.8	16.9	
12	17.5	18.1	19.1	-	19.0	-	17.9	17.9	17.5	18.9	

DN 350 to 2000 (14 to 78")



Dimensions in SI units

DN ¹⁾ [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G ²⁾ [mm]
350	136	407	282	689	564	276	550
375	136	433	308	741	616	276	600
400	136	433	308	741	616	276	600
450	136	458	333	791	666	292	650
500	136	483	359	842	717	292	650
600	136	535	411	946	821	402	780
700	136	637	512	1149	1024	589	910
750	136	637	512	1149	1024	626	975
800	136	658	534	1192	1067	647	1040
900	136	735	610	1345	1220	785	1170
1000	136	811	686	1497	1372	862	1300
1050	136	837	712	1549	1424	912	1365
1200	136	936	811	1747	1622	992	1560
1350	136	1037	912	1949	1824	1252	1755
1400	136	1112	987	2099	1974	1252	1820
1500	136	1136	1011	2147	2022	1392	1950
1600	136	1181	1056	2237	2112	1482	2080
1650	136	1218	1093	2311	2186	1482	2145
1800	136	1313	1188	2501	2376	1632	2340
2000	136	1363	1238	2601	2476	1732	2600

1) EN (DIN), AS; For flanges according to AS, only nominal diameters DN 350, 400, 500 and 600 are available.


2) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Dimensions in US units

DN¹⁾ [in]	A [in]	B [in]	C [in]	D [in]	E [in]	F [in]	G²⁾ [in]
14	5.35	16.0	11.1	29.3	22.2	10.9	21.7
15	5.35	17.0	12.1	31.3	24.2	10.9	23.6
16	5.35	17.0	12.1	31.3	24.2	10.9	23.6
18	5.35	18.0	13.1	33.3	26.2	11.5	25.6
20	5.35	19.0	14.1	35.3	28.2	11.5	25.6
24	5.35	21.1	16.2	39.4	32.3	15.8	30.7
28	5.35	25.1	20.1	45.2	40.3	23.2	35.8
30	5.35	25.1	20.1	45.2	40.3	24.6	38.4
32	5.35	25.9	21.0	46.9	42.0	25.5	40.9
36	5.35	28.9	24.0	52.9	48.0	30.9	46.0
40	5.35	31.9	27.0	58.9	54.0	33.9	51.2
42	5.35	32.9	28.0	60.9	56.0	35.9	53.7
48	5.35	36.8	31.9	68.7	63.8	39.0	61.4
54	5.35	40.8	35.9	76.7	71.8	42.3	69.1
60	5.35	44.7	39.8	84.5	79.6	54.8	76.8
66	5.35	47.9	43.0	91.0	86.0	58.4	84.4
72	5.35	51.7	46.8	98.4	93.5	64.2	92.1
78	5.35	53.6	48.7	102.4	97.5	68.2	102.3

1) ASME, AWWA; flanges ≤ 24 in only available according to ASME, flanges ≥ 28 in only available according to AWWA.

2) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Order code for "Design", option A "Insertion length short" with DN 350 to 2000 (14 to 78")

A0017284

Dimensions in SI units

DN [mm]	A [mm]	B [mm]	E [mm]	F [mm]
350	136	358	290	550
375	136	384	290	600
400	136	384	290	600
450	136	412	290	600
500	136	437	290	600
600	136	478	290	600
700	136	543	424	700
750	136	579	454	750
800	136	599	500	800
900	136	649	580	900
1000	136	699	660	1000
1050	136	735	755	1050
1200	136	813	828	1200
1350	136	925	1008	1350
1400	136	925	1008	1400
1500	136	1025	1147	1500
1600	136	1025	1147	1600
1650	136	1076	1284	1650
1800	136	1133	1379	1800
2000	136	1244	1569	2000

DN [mm]	Dimension C					Dimension D				
	EN (DIN)			ASME AWWA	AS	EN (DIN)			ASME AWWA	AS
	PN 6 [mm]	PN 10 [mm]	PN 16 [mm]			PN 6 [mm]	PN 10 [mm]	PN 16 [mm]		
350	603	610	616	625	620	490	505	520	533	525
375	-	-	-	-	659	-	-	-	-	550
400	654	666	672	682	674	540	565	580	597	580
450	709	719	729	729	732	595	615	640	635	640
500	759	772	791	786	789	645	670	715	699	705
600	855	868	903	884	890	755	780	840	813	825
700	973	990	1009	1006	998	860	895	910	927	910
750	-	-	-	1072	1078	-	-	-	984	995
800	1087	1107	1123	1129	1129	975	1015	1025	1060	1060
900	1187	1207	1223	1233	1237	1075	1115	1125	1168	1175
1000	1287	1314	1338	1344	1327	1175	1230	1225	1289	1255
1050	-	-	-	1408	-	-	-	-	1346	-
1200	1516	1541	1567	1569	1558	1405	1455	1255	1511	1490
1350	-	-	-	1767	-	-	-	-	1683	-
1400	1740	1763	1779	-	-	1630	1675	1685	-	-

DN [mm]	Dimension C					Dimension D				
	EN (DIN)			ASME	AS	EN (DIN)			ASME	AS
	PN 6 [mm]	PN 10 [mm]	PN 16 [mm]	AWWA [mm]	[mm]	PN 6 [mm]	PN 10 [mm]	PN 16 [mm]	AWWA [mm]	[mm]
1500	-	-	-	1952	-	-	-	-	1854	-
1600	1940	1983	2002	-	-	1830	1915	1930	-	-
1650	-	-	-	2092	-	-	-	-	2032	-
1800	2155	2190	2209	2231	-	2045	2115	2130	2197	-
2000	2376	2406	2427	2425	-	2265	2325	2345	2362	-

Dimensions in US units


DN [in]	A [in]	B [in]	E [in]	F [in]
14	5.35	14.1	11.4	21.6
15	5.35	15.1	11.4	23.6
16	5.35	15.1	11.4	23.6
18	5.35	16.2	11.4	23.6
20	5.35	17.2	11.4	23.6
24	5.35	18.8	11.4	23.6
28	5.35	21.6	16.7	27.6
30	5.35	23.0	17.9	29.5
32	5.35	23.6	19.7	31.5
36	5.35	25.6	22.8	35.4
40	5.35	27.5	26.0	39.4
42	5.35	28.9	29.7	41.3
48	5.35	32.0	32.6	47.2
54	5.35	36.4	39.6	53.1
60	5.35	40.4	45.2	59.0
66	5.35	42.4	50.6	64.9
72	5.35	44.6	54.2	70.8
78	5.35	49.0	61.8	78.7

DN [in]	Dimension C					Dimension D				
	EN (DIN)			ASME	AS	EN (DIN)			ASME	AS
	PN 6 [in]	PN 10 [in]	PN 16 [in]	AWWA [in]	[in]	PN 6 [in]	PN 10 [in]	PN 16 [in]	AWWA [in]	[in]
14	23.7	24.0	24.3	24.6	24.4	19.3	19.9	20.5	21.0	20.7
15	-	-	-	-	25.9	-	-	-	-	21.7
16	25.8	26.2	26.5	26.9	26.5	21.3	22.2	22.8	23.5	22.8
18	27.9	28.3	28.7	28.7	28.8	23.4	24.2	25.2	25.0	25.2
20	29.9	30.4	31.1	30.9	31.1	25.4	26.4	28.1	27.5	27.8
24	33.7	34.2	35.6	34.8	35.0	29.7	30.7	33.1	32.0	32.5
28	38.5	39.2	39.7	39.8	39.5	33.9	35.2	35.8	36.5	35.8

DN [in]	Dimension C					Dimension D				
	EN (DIN)			ASME AWWA [in]	AS [in]	EN (DIN)			ASME AWWA [in]	AS [in]
	PN 6 [in]	PN 10 [in]	PN 16 [in]			PN 6 [in]	PN 10 [in]	PN 16 [in]		
30	-	-	-	42.4	42.4	-	-	-	38.7	39.2
32	43.0	43.8	44.2	44.6	44.6	38.4	40.0	40.4	41.7	41.7
36	46.9	47.7	48.2	48.7	48.9	42.3	43.9	44.3	46.0	46.3
40	50.8	51.9	52.7	53.1	52.4	46.3	48.4	48.2	50.7	49.4
42	-	-	-	55.6	-	-	-	-	53.0	-
48	59.9	60.8	61.7	62.0	61.5	55.3	57.3	49.4	59.5	58.7
54	-	-	-	69.6	-	-	-	-	66.3	-
60	-	-	-	76.9	-	-	-	-	73.0	-
66	-	-	-	82.4	-	-	-	-	80.0	-
72	84.9	86.3	87.0	87.9	-	80.5	83.3	83.9	86.5	-
78	93.6	94.7	95.6	95.5	-	89.2	91.5	92.3	93.0	-

Order code for "Design", option A "Insertion length short" with DN 450 to 2000 (18 to 78") and order code for "Sensor option", option CA...CE "Corrosion protection" with DN 350 to 2000 (14 to 78")

Option	Description
CA	IP66/67, Type 4X, fully welded; corrosion protection EN ISO 12944 C5-M
CB	IP68, Type 6P, fact-potted; corrosion protection EN ISO 12944 C5-M/Im1/Im2/Im3
CC	IP68, Type 6P, cust-potted; corrosion protection EN ISO 12944 C5-M/Im1/Im2/Im3
CD	Buried IP68, Type 6P, fact-potted; corrosion protection EN ISO 12944 Im2/Im3
CE	Buried IP68, Type 6P, cust-potted; corrosion protection EN ISO 12944 Im2/Im3



A0018158

Dimensions in SI units

DN [mm]	A [mm]	B [mm]	E [mm]	F [mm]
350	112	350	290	550
375	112	376	290	600
400	112	376	290	600
450	112	403	290	600
500	112	428	290	600
600	112	478	290	600
700	112	549	424	700
750	112	586	454	750
800	112	605	500	800
900	112	655	580	900
1000	112	705	660	1000
1050	112	741	755	1050
1200	112	819	828	1200
1350	112	931	1008	1350
1400	112	931	1008	1400
1500	112	1031	1147	1500
1600	112	1031	1147	1600
1650	112	1082	1284	1650
1800	112	1139	1379	1800
2000	112	1250	1569	2000

DN [mm]	Dimension C					Dimension D				
	EN (DIN)			ASME AWWA [mm]	AS [mm]	EN (DIN)			ASME AWWA [mm]	AS [mm]
	PN 6 [mm]	PN 10 [mm]	PN 16 [mm]			PN 6 [mm]	PN 10 [mm]	PN 16 [mm]		
350	595	603	610	–	613	490	505	520	–	525
375	–	–	–	–	651	–	–	–	–	550
400	646	659	666	–	666	540	565	580	–	580
450	701	711	723	–	723	595	615	640	–	640
500	751	763	786	–	781	645	670	715	–	705
600	856	868	898	–	891	755	780	840	–	825
700	979	996	1004	1012	1004	860	895	910	927	910
750	–	–	–	1078	1084	–	–	–	984	995
800	1093	1113	1118	1135	1135	975	1015	1025	1060	1060
900	1193	1213	1218	1239	1243	1075	1115	1125	1168	1175
1000	1293	1320	1333	1350	1333	1175	1230	1225	1289	1255
1050	–	–	–	1414	–	–	–	–	1346	–
1200	1522	1547	1562	1575	1564	1405	1455	1255	1511	1490
1350	–	–	–	1773	–	–	–	–	1683	–
1400	1746	1769	1774	–	–	1630	1675	1685	–	–

DN [mm]	Dimension C					Dimension D				
	EN (DIN)			ASME	AS	EN (DIN)			ASME	AS
	PN 6 [mm]	PN 10 [mm]	PN 16 [mm]	AWWA [mm]	[mm]	PN 6 [mm]	PN 10 [mm]	PN 16 [mm]	AWWA [mm]	[mm]
1500	-	-	-	1958	-	-	-	-	1854	-
1600	1946	1989	1997	-	-	1830	1915	1930	-	-
1650	-	-	-	2098	-	-	-	-	2032	-
1800	2161	2196	2204	2237	-	2045	2115	2130	2197	-
2000	2382	2412	2422	2431	-	2265	2325	2345	2362	-

Dimensions in US units


DN [in]	A [in]	B [in]	E [in]	F [in]
14	4.41	13.8	11.4	21.7
15	4.41	14.8	11.4	23.6
16	4.41	14.8	11.4	23.6
18	4.41	15.9	11.4	23.6
20	4.41	16.9	11.4	23.6
24	4.41	18.8	11.4	23.6
28	4.41	21.6	16.7	27.6
30	4.41	23.1	17.9	29.5
32	4.41	23.8	19.7	31.5
36	4.41	25.8	22.8	35.4
40	4.41	27.8	26.0	39.4
42	4.41	29.2	29.7	41.3
48	4.41	32.2	32.6	47.2
54	4.41	36.7	39.7	53.2
60	4.41	40.6	45.2	59.1
66	4.41	42.6	50.6	65.0
72	4.41	44.8	54.3	70.9
78	4.41	49.2	61.8	78.7

DN [in]	Dimension C					Dimension D				
	EN (DIN)			ASME	AS	EN (DIN)			ASME	AS
	PN 6 [in]	PN 10 [in]	PN 16 [in]	AWWA [in]	[in]	PN 6 [in]	PN 10 [in]	PN 16 [in]	AWWA [in]	[in]
14	23.4	23.7	24.0	-	24.1	19.3	19.9	20.5	-	20.7
15	-	-	-	-	25.6	-	-	-	-	21.7
16	25.4	25.9	26.2	-	26.2	21.3	22.2	22.8	-	22.8
18	27.6	28.0	28.5	-	28.5	23.4	24.2	25.2	-	25.2
20	29.6	30.0	30.9	-	30.7	25.4	26.4	28.1	-	27.8
24	33.7	34.2	35.4	-	35.1	29.7	30.7	33.1	-	32.5
28	38.5	39.2	39.5	39.8	39.5	33.9	35.2	35.8	36.5	35.8

DN [in]	Dimension C					Dimension D				
	EN (DIN)			ASME AWWA	AS [in]	EN (DIN)			ASME AWWA	AS [in]
	PN 6 [in]	PN 10 [in]	PN 16 [in]			PN 6 [in]	PN 10 [in]	PN 16 [in]		
30	-	-	-	42.4	42.7	-	-	-	38.7	39.2
32	43.0	43.8	44.0	44.7	44.7	38.4	40.0	40.4	41.7	41.7
36	47.0	47.8	48.0	48.8	48.9	42.3	43.9	44.3	46.0	46.3
40	50.9	52.0	52.5	53.1	52.5	46.3	48.4	48.2	50.7	49.4
42	-	-	-	55.7	-	-	-	-	53.0	-
48	59.9	60.9	61.5	62.0	61.6	55.3	57.3	49.4	59.5	58.7
54	-	-	-	69.8	-	-	-	-	66.3	-
60	-	-	-	77.1	-	-	-	-	73.0	-
66	-	-	-	82.6	-	-	-	-	80.0	-
72	85.1	86.5	86.8	88.1	-	80.5	83.3	83.9	86.5	-
78	93.8	95.0	95.4	95.7	-	89.2	91.5	92.3	93.0	-

Order code for "Sensor option", option CA...CE "Corrosion protection" with DN 350 to 2000 (14 to 78")

Option	Description
CA	IP66/67, Type 4X, fully welded; corrosion protection EN ISO 12944 C5-M
CB	IP68, Type 6P, fact-potted; corrosion protection EN ISO 12944 C5-M/Im1/Im2/Im3
CC	IP68, Type 6P, cust-potted; corrosion protection EN ISO 12944 C5-M/Im1/Im2/Im3
CD	Buried IP68, Type 6P, fact-potted; corrosion protection EN ISO 12944 Im2/Im3
CE	Buried IP68, Type 6P, cust-potted; corrosion protection EN ISO 12944 Im2/Im3



A0020435

Dimensions in SI units

DN [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G¹⁾ [mm]
350	112	395	282	677	564	276	550
375	112	421	308	729	616	276	600
400	112	421	308	729	616	276	600
450	112	446	333	779	666	292	650
500	112	472	359	830	717	292	650
600	112	524	411	934	821	402	780
700	112	625	512	1137	1024	589	910
750	112	625	512	1137	1024	626	975
800	112	647	534	1180	1067	647	1040
900	112	723	610	1333	1220	785	1170
1000	112	799	686	1485	1372	862	1300
1050	112	825	712	1537	1424	912	1365
1200	112	924	811	1735	1622	992	1560
1350	112	1025	912	1937	1824	1252	1755
1400	112	1100	987	2087	1974	1252	1820
1500	112	1124	1011	2135	2022	1392	1950
1600	112	1169	1056	2225	2112	1482	2080
1650	112	1206	1093	2299	2186	1482	2145
1800	112	1301	1188	2489	2376	1632	2340
2000	112	1351	1238	2589	2476	1732	2600

1) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Dimensions in US units


DN [in]	A [in]	B [in]	C [in]	D [in]	E [in]	F [in]	G¹⁾ [in]
14	4.41	15.6	11.1	26.7	22.2	10.9	21.7
15	4.41	16.6	12.1	28.7	24.2	10.9	23.6
16	4.41	16.6	12.1	28.7	24.2	10.9	23.6
18	4.41	17.6	13.1	30.7	26.2	11.5	25.6
20	4.41	18.6	14.1	32.7	28.2	11.5	25.6
24	4.41	20.6	16.2	36.8	32.3	15.8	30.7
28	4.41	24.6	20.2	44.8	40.3	23.2	35.8
30	4.41	24.6	20.2	44.8	40.3	24.6	38.4
32	4.41	25.5	21.0	46.5	42.0	25.5	40.9
36	4.41	28.5	24.0	52.5	48.0	30.9	46.0
40	4.41	31.5	27.0	58.5	54.0	33.9	51.2
42	4.41	32.5	28.0	60.5	56.0	35.9	53.7
48	4.41	36.4	31.9	68.3	63.8	39.0	61.4
54	4.41	40.4	35.9	76.3	71.8	42.3	69.1
60	4.41	44.3	39.8	84.1	79.6	54.8	76.8

DN [in]	A [in]	B [in]	C [in]	D [in]	E [in]	F [in]	G ¹⁾ [in]
66	4.41	47.5	43.0	90.5	86.0	58.4	84.4
72	4.41	51.2	46.8	98.0	93.5	64.2	92.1
78	4.41	53.2	48.7	101.9	97.5	68.2	102.3

1) The length is independent of the selected pressure rating. Length in accordance with DVGW/ISO.

Accessories

Ground disks for flange connections



A0015442

■ 32 Engineering unit mm (in)

Dimensions in SI and US units

DN		Pressure rating	A		B		D		H	
[mm]	[in]		[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]
25	1	¹⁾	26	1.02	62	2.44	77.5	3.05	87.5	3.44
32	1 1/4	¹⁾	35	1.38	80	3.15	87.5	3.44	94.5	3.72
40	1 1/2	¹⁾	41	1.61	82	3.23	101	3.98	103	4.06
50	2	¹⁾	52	2.05	101	3.98	115.5	4.55	108	4.25
65	2 1/2	¹⁾	68	2.68	121	4.76	131.5	5.18	118	4.65
80	3	¹⁾	80	3.15	131	5.16	154.5	6.08	135	5.31
100	4	¹⁾	104	4.09	156	6.14	186.5	7.34	153	6.02
125	5	¹⁾	130	5.12	187	7.36	206.5	8.13	160	6.30
150	6	¹⁾	158	6.22	217	8.54	256	10.1	184	7.24
200	8	¹⁾	206	8.11	267	10.5	288	11.3	205	8.07
250	10	¹⁾	260	10.2	328	12.9	359	14.1	240	9.45
300	12	¹⁾	312	12.3	375	14.8	413	16.3	273	10.8
350	14	DIN, PN 6	343	13.5	433	16.5	479	18.9	365	14.4
350	14	DIN, PN 10	343	13.5	400	15.8	479	18.9	365	14.4
350	14	ASME, Class 150	343	13.5	400	15.8	479	18.9	365	14.4
400	16	DIN, PN 6	393	15.5	470	18.5	542	21.3	395	15.6
400	16	DIN, PN 10	393	15.5	469	18.5	542	21.3	395	15.6

DN		Pressure rating	A		B		D		H	
[mm]	[in]		[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]
400	16	ASME, Class 150	393	15.5	469	18.5	542	21.3	395	15.6
450	18	DIN, PN 6	439	17.3	525	20.7	583	23.0	417	16.4
450	18	DIN, PN 10	439	17.3	535	21.1	583	23.0	417	16.4
450	18	ASME, Class 150	439	17.3	535	21.1	583	23.0	417	16.4
500	20	DIN, PN 6	493	19.4	575	23.3	650	25.6	460	18.1
500	20	DIN, PN 10	493	19.4	588	23.2	650	25.6	460	18.1
500	20	ASME, Class 150	493	19.4	588	23.2	650	25.6	460	18.1
600	24	DIN, PN 6	593	23.4	676	27.3	766	30.2	522	20.6
600	24	DIN, PN 10	593	23.4	688	27.1	766	30.2	522	20.6
600	24	ASME, Class 150	593	23.4	688	27.1	766	30.2	522	20.6
700	28	DIN, PN 6	697	27.4	-	-	786	30.9	460	18.1
700	28	DIN, PN 10	693	27.3	-	-	813	32.0	480	18.9
700	28	AS, PN 16	687	27.1	-	-	807	31.8	490	19.3
700	28	AWWA, Class D	693	27.3	-	-	832	32.8	494	19.5
750	30	AWWA, Class D	743	29.3	-	-	833	32.8	523	20.6
800	32	DIN, PN 6	799	31.5	-	-	893	35.2	520	20.5
800	32	DIN, PN 10	795	31.3	-	-	920	36.2	540	21.3
800	32	AS, PN 16	789	31.1	-	-	914	36.0	550	21.7
800	32	AWWA, Class D	795	31.3	-	-	940	37.0	561	22.1
900	36	DIN, PN 6	897	35.3	-	-	993	39.1	570	22.4
900	36	DIN, PN 10	893	35.2	-	-	1020	40.2	590	23.2
900	36	AS, PN 16	886	34.9	-	-	1014	39.9	595	23.4
900	36	AWWA, Class D	893	35.2	-	-	1048	41.3	615	24.2
1000	40	DIN, PN 6	999	39.3	-	-	1093	43.0	620	24.4
1000	40	DIN, PN 10	995	39.2	-	-	1127	44.4	650	25.6
1000	40	AS, PN 16	988	38.9	-	-	1131	44.5	660	26.0
1000	40	AWWA, Class D	995	39.2	-	-	1163	45.8	675	26.6
1050	42	AWWA, Class D	1044	41.1	-	-	1220	48.0	704	27.7
1200	48	DIN, PN 6	1203	47.4	-	-	1310	51.6	733	28.9

- 1) Ground disks can be used for all the flange standards/pressure ratings which can be supplied in the standard version.

Weight

Compact version

Weight data:

- Including the transmitter
 - Order code for "Housing", option M, Q: 1.3 kg (2.9 lbs)
 - Order code for "Housing", option A, R: 2.0 kg (4.4 lbs)
- Excluding packaging material

*Weight in SI units**Standard version*

EN 1092-1 (DIN 2501)			
DN [mm]	Pressure rating	Weight [kg]	
		Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
25	PN 40	5	.7
32	PN 40	6	6.7
40	PN 40	8	8.7
50	PN 40	9	9.7
65	PN 16	10	10.7
80	PN 16	12	12.7
100	PN 16	14	14.7
125	PN 16	20	20.7
150	PN 16	24	24.7
200	PN 10	43	43.7
250	PN 10	63	63.7
300	PN 10	68	68.7
350	PN 6	105	105.7
375	PN 6	120	120.7
400	PN 6	120	120.7
450	PN 6	161	161.7
500	PN 6	156	156.7
600	PN 6	208	208.7
700	PN 6	304	304.7
800	PN 6	357	357.7
900	PN 6	485	485.7
1000	PN 6	589	589.7
1200	PN 6	850	850.7
1400	PN 6	1300	1300.7
1600	PN 6	1700	1700.7
1800	PN 6	2200	2200.7
2000	PN 6	2800	2800.7

AS 4087, PN 16			
DN [mm]	Weight [kg]		Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
	Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated	
80	12		12.7
100	14		14.7
150	24		24.7

JIS B2220, 10K

DN [mm]	Weight [kg]	
	Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
25	5	5.7
32	5	5.7
40	6	6.7
50	7	7.7
65	9	9.7
80	11	11.7
100	13	13.7
125	19	19.7
150	23	23.7
200	40	40.7
250	68	68.7
300	70	70.7

Order code for "Design", option A

Option A "Insertion length short; ISO/DVGW to DN400, DN450-2000 1:1"

EN 1092-1 (DIN 2501)

DN [mm]	Order code for "Housing", option M, Q Polycarbonate plastic ¹⁾		
	PN 6	PN 10	PN 16
450	100	113	139
500	115	133	179
600	156	163	224
700	191	241	288
800	241	316	350
900	309	394	441
1000	360	469	563
1200	530	718	840
1400	785	1115	1201
1600	1059	1625	1842
1800	1419	2108	2354
2000	1878	2631	2926

1) Values for aluminum transmitter, AlSi10Mg, coated: + 0.7 kg

AS 2129, Table E

DN [mm]	Weight [kg]	
	Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
450	144	144.7
500	183	183.7

AS 2129, Table E

DN [mm]	Weight [kg]	
	Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
600	261	261.7
700	347	347.7
750	434	434.7
800	494	494.7
900	691	691.7
1000	762	762.7
1200	1238	1238.7

AS 4087, PN 16

DN [mm]	Weight [kg]	
	Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
450	134	134.7
500	183	183.7
600	261	261.7
700	368	368.7
750	446	446.7
800	504	504.7
900	703	703.7
1000	760	760.7
1200	1220	1220.7

Order code for "Calibration flow", options H and K, or options H/K, or order code for "Sensor Option", Option CA

Option	Description
H	MID Type Examination Cert MI-001
K	OIML R49 Class 2
CA	IP66/67, Type 4X, fully welded; corrosion protection EN ISO 12944 C5-M

EN 1092-1 (DIN 2501)

DN [mm]	Pressure rating	Weight [kg]	
		Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
25	PN 40	9	9.7
32	PN 40	10	10.7
40	PN 40	11	11.7
50	PN 40	12	12.7
65	PN 16	13	13.7
80	PN 16	15	15.7
100	PN 16	17	17.7

EN 1092-1 (DIN 2501)			
DN [mm]	Pressure rating	Weight [kg]	
		Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
125	PN 16	22	22.7
150	PN 16	27	27.7
200	PN 10	38	38.7
250	PN 10	51	51.7
300	PN 10	60	60.7

AS 2129, PN 16			
DN [mm]		Weight [kg]	
		Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
80		15	15.7
100		17	17.7
125		22	22.7
150		27	27.7

JIS B2220, 10K			
DN [mm]		Weight [kg]	
		Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
25		9	9.7
32		10	10.7
40		10	10.7
50		11	11.7
65		12	12.7
80		13	13.7
100		15	15.7
125		20	20.7
150		25	25.7
200		34	34.7
250		50	50.7
300		57	57.7

Weight in US units

Standard version

ASME B16.5, Class 150			
DN [in]		Weight [lbs]	
		Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
1		11	12.5
1½		18	19.5

ASME B16.5, Class 150

DN [in]	Weight [lbs]	
	Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
2	20	21.5
3	26	27.5
4	31	32.5
6	53	54.5
8	95	96.5
10	161	162.5
12	238	239.5
14	386	387.5
16	452	453.5
18	562	563.5
20	628	629.5
24	893	894.5

AWWA C207, Class D

DN [in]	Weight [lbs]	
	Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
28	882	883.5
30	1014	1015.5
32	1213	1214.5
36	1764	1765.5
40	1985	1986.5
42	2426	2427.5
48	3087	3088.5
54	4851	4852.5
60	5954	5955.5
66	8159	8160.5
72	9041	9042.5
78	10143	10144.5

*Order code for "Design", option A**Option A "Insertion length short; ISO/DVGW to DN400, DN450-2000 1:1"*

ASME B16.5, Class 150

DN [in]	Weight [lbs]	
	Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
18	423	424.5
20	505	506.5
24	668	667.5

AWWA C207, Class D		
DN [in]	Weight [lbs]	
	Order code for "Housing", option M, Q Polycarbonate plastic	Order code for "Housing", option A, R Aluminum, AlSi10Mg, coated
28	589	590.5
30	703	704.5
32	847	848.5
36	1039	1040.5
40	1297	1298.5
42	1480	1481.5
48	1989	1990.5
54	2809	2810.5
60	3517	3518.5
66	4701	4702.5
72	5665	5666.5
78	6866	6867.5

Order code for "Sensor option", option CA

Option CA "IP66/67, Type 4X, fully welded; corrosion protection EN ISO 12944 C5-M"

ASME B16.5, Class 150	
DN [in]	Weight [lbs]
1	17.6
1½	19.8
2	24.3
3	33.1
4	41.9
6	61.7
8	97.0
10	134.5
12	189.6

Transmitter remote version

Wall-mount housing

Depends on the material of the wall-mount housing:

- Polycarbonate plastic: 1.3 kg (2.9 lb)
- Aluminum, AlSi10Mg, coated: 2.0 kg (4.4 lb)

Sensor remote version

Weight data:

- Including sensor connection housing
- Excluding the connecting cable
- Excluding packaging material

Weight in SI units

Standard version

EN 1092-1 (DIN 2501)		
DN [mm]	Pressure rating	Weight [kg]
25	PN 40	5
32	PN 40	6
40	PN 40	7
50	PN 40	9
65	PN 16	10
80	PN 16	12
100	PN 16	14
125	PN 16	20
150	PN 16	24
200	PN 10	43
250	PN 10	63
300	PN 10	68
350	PN 6	103
375	PN 6	118
400	PN 6	118
450	PN 6	159
500	PN 6	154
600	PN 6	206
700	PN 6	302
800	PN 6	355
900	PN 6	483
1000	PN 6	587
1200	PN 6	848
1400	PN 6	1298
1600	PN 6	1698
1800	PN 6	2198
2000	PN 6	2798

AS 4087, PN 16		
DN [mm]	Weight [kg]	
80	12	
100	14	
125	20	
150	24	

JIS B2220, 10K	
DN [mm]	Weight [kg]
25	5
32	5
40	6
50	7
65	9
80	11
100	13
125	19
150	23
200	40
250	67
300	70

Order code for "Design", option A

Option A "Insertion length short; ISO/DVGW to DN400, DN450-2000 1:1"

EN 1092-1 (DIN 2501)				
DN [mm]	Weight [kg]	PN 6	PN 10	PN 16
450	98	111	139	
500	113	131	179	
600	154	161	224	
700	190	240	288	
800	240	315	350	
900	308	393	441	
1000	359	468	563	
1200	529	717	840	
1400	784	1 114	1 200	
1600	1 058	1 624	1 841	
1800	1 418	2 107	2 353	
2000	1 877	2 630	2 925	

AS 2129, Table E	
DN [mm]	Weight [kg]
450	142
500	181
600	259
700	346
750	433
800	493
900	690

AS 2129, Table E

DN [mm]	Weight [kg]
1000	761
1200	1237

AS 4087, PN 16

DN [mm]	Weight [kg]
450	132
500	181
600	259
700	367
750	445
800	503
900	702
1000	759
1200	1219

Order code for "Calibration flow", options H and K, or order code for "Sensor option", option CA

Option	Description
H	MID Type Examination Cert MI-001
K	OIML R49 Class 2
CA	IP66/67, Type 4X, fully welded; corrosion protection EN ISO 12944 C5-M

EN 1092-1 (DIN 2501)

DN [mm]	Pressure rating	[kg]
25	PN 40	6.5
32	PN 40	8
40	PN 40	8.5
50	PN 40	10
65	PN 16	11
80	PN 16	13
100	PN 16	15
125	PN 16	20
150	PN 16	25
200	PN 10	36
250	PN 10	49
300	PN 10	58

AS 4087, PN 16

DN [mm]	[kg]
80	13
100	15
150	25

JIS B2220, 10K

DN [mm]	Weight [kg]
25	6.5
32	7.5
40	7.5
50	9
65	10
80	11
100	13
125	18
150	23
200	32
250	48
300	55

Weight in US units

Standard version

ASME B16.5, Class 150

DN [in]	Weight [lbs]
1	11
1½	15
2	20
3	26
4	31
6	53
8	95
10	161
12	238
14	381
16	448
18	558
20	624
24	889

AWWA C207, Class D	
DN [in]	Weight [lbs]
28	878
30	1010
32	1208
36	1760
40	1980
42	2421
48	3083
54	4847
60	5949
66	8154
72	9036
78	10139

Order code for "Design", option A

Option A *"Insertion length short; ISO/DVGW to DN400, DN450-2000 1:1"*

ASME B16.5, Class 150	
DN [in]	Weight [lbs]
18	420
20	501
24	664

AWWA C207, Class D	
DN [in]	Weight [lbs]
28	587
30	701
32	845
36	1036
40	1294
42	1477
48	1987
54	1273
60	3515
66	4699
72	5662
78	6864

Order code for "Sensor option", option CA

Option CA "IP66/67, Type 4X, fully welded; corrosion protection EN ISO 12944 C5-M"

ASME B16.5, Class 150	
DN [in]	Weight [lbs]
1	13
1½	15.5
2	20
3	29
4	37
6	57
8	93
10	130
12	185

Measuring tube specification

Nominal diameter		Pressure rating				Measuring tube internal diameter			
		EN (DIN)	ASME AWWA	AS 2129 AS 4087	JIS	Hard rubber		Polyurethane	
[mm]	[in]					[mm]	[in]	[mm]	[in]
25	1	PN 40	Class 150	–	20K	–	–	24	0.94
32	–	PN 40	–	–	20K	–	–	32	1.26
40	1 ½	PN 40	Class 150	–	20K	–	–	38	1.50
50	2	PN 40	Class 150	Table E, PN 16	10K	50	1.97	50	1.97
65	–	PN 16	–	–	10K	66	2.60	66	2.60
80	3	PN 16	Class 150	Table E, PN 16	10K	79	3.11	79	3.11
100	4	PN 16	Class 150	Table E, PN 16	10K	102	4.02	102	4.02
125	–	PN 16	–	–	10K	127	5.00	127	5.00
150	6	PN 16	Class 150	Table E, PN 16	10K	156	6.14	156	6.14
200	8	PN 10	Class 150	Table E, PN 16	10K	204	8.03	204	8.03
250	10	PN 10	Class 150	Table E, PN 16	10K	258	10.2	258	10.2
300	12	PN 10	Class 150	Table E, PN 16	10K	309	12.2	309	12.2
350	14	PN 6	Class 150	Table E, PN 16	–	342	13.5	342	13.5
375	15	–	–	PN 16	–	392	15.4	–	–
400	16	PN 6	Class 150	Table E, PN 16	–	392	15.4	392	15.4
450	18	PN 6	Class 150	–	–	437	17.2	437	17.2
500	20	PN 6	Class 150	Table E, PN 16	–	492	19.4	492	19.4
600	24	PN 6	Class 150	Table E, PN 16	–	594	23.4	594	23.4
700	28	PN 6	Class D	Table E, PN 16	–	692	27.2	692	27.2
750	30	–	Class D	Table E, PN 16	–	742	29.2	742	29.2
800	32	PN 6	Class D	Table E, PN 16	–	794	31.3	794	31.3
900	36	PN 6	Class D	Table E, PN 16	–	891	35.1	891	35.1
1000	40	PN 6	Class D	Table E, PN 16	–	994	39.1	994	39.1
–	42	–	Class D	–	–	1043	41.1	1043	41.1
1200	48	PN 6	Class D	Table E, PN 16	–	1197	47.1	1197	47.1


Nominal diameter		Pressure rating				Measuring tube internal diameter					
[mm]	[in]	EN (DIN)	ASME AWWA	AS 2129 AS 4087	JIS	Hard rubber	Polyurethane	[mm]	[in]	[mm]	[in]
–	54	–	Class D	–	–	1339	52.7	–	–	–	–
1 400	–	PN 6	–	–	–	1402	55.2	–	–	–	–
–	60	–	Class D	–	–	1492	58.7	–	–	–	–
1 600	–	PN 6	–	–	–	1600	63.0	–	–	–	–
–	66	–	Class D	–	–	1638	64.5	–	–	–	–
1 800	72	PN 6	Class D	–	–	1786	70.3	–	–	–	–
2 000	78	PN 6	Class D	–	–	1989	78.3	–	–	–	–

Materials**Transmitter housing****Order Code for "Housing"**

- Compact version, standard:
 - Option **A**: aluminum, AlSi10Mg, coated
 - Option **M**: polycarbonate plastic
- Compact version, inclined:
 - Option **Q**: polycarbonate plastic
 - Option **R**: aluminum, AlSi10Mg, coated
- Remote version (wall-mount housing):
 - Option **N**: polycarbonate plastic
 - Option **P**: aluminum, AlSi10Mg, coated

Window material

Transmitter housing material	Window material
Polycarbonate plastic	Plastic
Aluminum, AlSi10Mg, coated	Glass

Cable entries/cable glands

A0020640

Fig. 33 Possible cable entries/cable glands

- 1 Cable entry in transmitter housing, wall-mount housing or connection housing with internal thread M20 x 1.5
- 2 Cable gland M20 x 1.5
- 3 Adapter for cable entry with internal thread G 1/2" or NPT 1/2"

Compact and remote versions and sensor connection housing

Cable entry/cable gland	Material
Cable gland M20 × 1.5	Plastic
Remote version: cable gland M20 × 1.5 Option of reinforced connecting cable	<ul style="list-style-type: none"> ▪ Sensor connection housing: Nickel-plated brass ▪ Transmitter wall-mount housing: Plastic
Adapter for cable entry with internal thread G ½" or NPT ½"	Nickel-plated brass

Device plug

Electrical connection	Material
Plug M12x1	<ul style="list-style-type: none"> ▪ Socket: Stainless steel, 1.4404 (316L) ▪ Contact housing: Polyamide ▪ Contacts: Gold-plated brass

Connecting cable for remote version

Electrode and coil current cable

- Standard cable: PVC cable with copper shield
- Reinforced cable: PVC cable with copper shield and additional steel wire braided jacket

Sensor housing

- DN 25 to 300 (1 to 12''):
 - Aluminum, AlSi10Mg, coated
 - Carbon steel with Al/Zn protective coating
- DN 50 to 300 (2 to 12''):
 - Carbon steel with protective varnish (IP68)
- DN 350 to 2000 (14 to 78''):
 - Carbon steel with protective varnish

Sensor connection housing

- Standard: aluminum, AlSi10Mg, coated (IP66/67)
- Option:
 - Polycarbonate for IP68 with DN 50 to 300 (2 to 12'')
 - Polycarbonate for order code "Sensor option", option CA...CE "Corrosion protection" with DN 350 to 2000 (14 to 78'')

Measuring tubes

- DN 25 to 300 (1 to 12'')¹⁾: stainless steel, 1.4301/1.4306/304/304L
- DN 350 to 1200 (14 to 48'')¹⁾: stainless steel, 1.4301/304
- DN 1350 to 2000 (54 to 78'')¹⁾: stainless steel, 1.4301 similar to 304

Liner

- DN 25 to 1200 (1 to 48''): polyurethane
- DN 50 to 2000 (2 to 78''): hard rubber

Electrodes

- Stainless steel, 1.4435 (316L)
- Alloy C22, 2.4602 (UNS N06022)
- Tantalum

1) For carbon steel flange material with Al/Zn protective coating (DN 25 to 300 (1 to 12'')), protective varnish (IP68) (DN 50 to 300 (2 to 12'')) or protective varnish ≥ DN 350 (14'')

Process connections

EN 1092-1 (DIN 2501)

- DN 25 to 1200¹⁾:
 - Stainless steel, 1.4404/1.4571/F316L
 - Carbon steel, A105/FE410WB/P250GH/S235JRG2/S235JR+N
- DN 1350 to 2000¹⁾:
 - Stainless steel ,1.4404/1.4571
 - Carbon steel, P250GH/S235JRG2
- DN 450 to 2000²⁾:
 - Carbon steel, A105/S235JRG2

EN 1092-1 (DIN 2501), PN6:

DN 350 to 1000¹⁾:
Carbon steel, A105/FE410WB/S235JRG2

ASME B16.5

- DN 25 to 1200 (1 to 48)":
Stainless steel, F316L similar to 1.4404
- DN 25 to 300 (1 to 12)":
Carbon steel, A105 similar to 1.0432
- DN 350 to 1200 (14 to 48")²⁾:
Carbon steel, A105/A515 Grade 70

AWWA C207

- DN 48":
Carbon steel, A105/A181/P265GH/S275JR
- DN 54 to 72":
Carbon steel, P265GH similar to 1.0425
- DN 48 to 78"²⁾:
Carbon steel, A105/A181/P265GH/S275JR

AS 2129

- DN 50 to 1200:
Carbon steel, A105/S235JRG2
- DN 350 to 1200²⁾:
Carbon steel, A105/FE410WB/P235GH/P265GH/S235JRG2

AS 4087

- DN 50 to 1200:
Carbon steel, A105/S275JR
- DN 350 to 1200²⁾:
Carbon steel, A105/P265GH/S275JR

JIS B2220

- Stainless steel, F316L similar to 1.4404
- Carbon steel, A105/A350LF2¹⁾

Seals

In accordance with DIN EN 1514-1

Accessories

Display protection

Stainless steel, 1.4301 (304L)

2) Order Code for "Design", Option A "Insertion length short"

Ground disks

- Stainless steel, 1.4435 (316L)
- Alloy C22, 2.4602 (UNS N06022)
- Tantalum

Fitted electrodes

Measurement, reference and empty pipe detection electrodes available as standard with:

- 1.4435 (316L)
- Alloy C22, 2.4602 (UNS N06022)
- Tantalum

Optionally available with DN 350 to 2000 (14 to 78"):
Exchangeable measuring electrodes made from 1.4435 (316L)

Process connections

- EN 1092-1 (DIN 2501)³⁾
 - DN ≤ 300: fixed flange (PN 10/16/25/40) = form A
 - DN ≥ 350: fixed flange (PN 6/10/16/25) = flat face
 - DN 450 to 2000⁴⁾: fixed flange (PN 6/10/16) = flat face
- ASME B16.5
 - DN 25 to 600 (1 to 24)": fixed flange (Class 150)
 - DN 350 to 2000 (14 to 78")⁴⁾: fixed flange (Class 150)
 - DN 25 to 150 (1 to 6)": fixed flange (Class 300)
- AWWA C207
 - DN 48 to 72": fixed flange (Class D)
 - DN 48 to 78"⁴⁾: fixed flange (Class D)
- AS 2129
 - DN 50 to 1200: fixed flange (Table E)
 - DN 350 to 1200⁴⁾: fixed flange (Table E)
- AS 4087
 - DN 50 to 1200): fixed flange (PN 16)
 - DN 350 to 1200⁴⁾: fixed flange (PN 16)
- JIS B2220
 - DN 50 to 300: fixed flange (10K)
 - DN 25 to 300: fixed flange (20K)



For information on the materials of the process connections (→ 93)

Surface roughness

Electrodes with 1.4435 (316L); Alloy C22, 2.4602 (UNS N06022); tantalum:

≤ 0.3 to 0.5 µm (11.8 to 19.7 µin)

(All data relate to parts in contact with fluid)

Operability

Operating concept**Operator-oriented menu structure for user-specific tasks**

- Commissioning
- Operation
- Diagnostics
- Expert level

Quick and safe commissioning

- Guided menus ("Make-it-run" wizards) for applications
- Menu guidance with brief explanations of the individual parameter functions

3) Dimensions as per DIN 2501, DN 65 (2 ½") PN 16 and DN 600 (24") PN 16 only as per EN 1092-1


4) Order code for "Design", option A "Insertion length short"

Reliable operation

- Operation in the following languages:
 - Via local display:
English, German, French, Spanish, Italian, Dutch, Portuguese, Polish, Russian, Turkish, Chinese, Japanese, Bahasa (Indonesian), Vietnamese, Czech
 - Via "FieldCare" operating tool:
English, German, French, Spanish, Italian, Chinese, Japanese
 - Via Web browser:
English, German, French, Spanish, Italian, Dutch, Portuguese, Polish, Russian, Turkish, Chinese, Japanese, Bahasa (Indonesian), Vietnamese, Czech
- Uniform operating philosophy applied to device, operating tools and Web browser
- If replacing the electronic module, transfer the device configuration via the plug-in memory (HistoROM DAT) which contains the process and measuring device data and the event logbook. No need to reconfigure.

Efficient diagnostics increase measurement availability

- Troubleshooting measures can be called up via the device, operating tools and Web browser
 - Diverse simulation options, logbook for events that occur and optional line recorder functions
-  In custody transfer mode, operation is only possible to a limited extent once the device has been put into circulation or has been lead-sealed.

Local operation**Via display module**

A0020538

Display elements


- 4-line display
- White background lighting; switches to red in event of device errors
- Format for displaying measured variables and status variables can be individually configured
- Permitted ambient temperature for the display: -20 to +50 °C (-4 to +122 °F)
The readability of the display may be impaired at temperatures outside the temperature range.

Operating elements

External operation via touch control; 3 optical keys: , , 

Additional functionality

- Data backup function
The device configuration can be saved in the display module.
- Data comparison function
The device configuration saved in the display module can be compared to the current device configuration.
- Data transfer function
The transmitter configuration can be transmitted to another device using the display module.


Remote operation**Via HART protocol**

34 Options for remote operation via HART protocol

- 1 Control system (e.g. PLC)
- 2 Field Communicator 475
- 3 Computer with operating tool (e.g. FieldCare, AMS Device Manager, SIMATIC PDM)
- 4 Commubox FXA195 (USB)
- 5 Field Xpert SFX350 or SFX370
- 6 VIATOR Bluetooth modem with connecting cable
- 7 Transmitter

Via PROFIBUS DP network


This communication interface is present in the following device version:
Order code for "Output", option **L**: PROFIBUS DP



- 1 Automation system
- 2 Computer with PROFIBUS network card
- 3 PROFIBUS DP network
- 4 Measuring device

Via Ethernet-based fieldbus

This communication interface is present in the following device version:
Order code for "Output", option **N**: EtherNet/IP



- 1 Ethernet network
- 2 Automation system, e.g. "RSLogix" (Rockwell Automation)
- 3 Workstation for measuring device operation: with Add-on Profile Level 3 for "RSLogix 5000" (Rockwell Automation) or with Electronic Data Sheet (EDS)
- 4 Computer with Web browser (e.g. Internet Explorer) for accessing the integrated device Web server or with "FieldCare" operating tool with COM DTM "CDI Communication TCP/IP"
- 5 Ethernet switch
- 6 Measuring device


Service interface

Service interface (CDI-RJ45)

This communication interface is present in the following device version:


- Order code for "Output", option **H**: 4-20/0-20 mA HART, pulse/frequency/switch output
- Order code for "Output", option **I**: 4-20/0-20 mA HART, pulse/frequency/switch output, status input
- Order code for "Output", option **L**: PROFIBUS DP
- Order code for "Output", option **N**: EtherNet/IP
- Order code for "Output", option **M**: Modbus RS485

HART



- 1 Computer with Web browser (e.g. Internet Explorer) for accessing the integrated device Web server or with "FieldCare" operating tool with COM DTM "CDI Communication TCP/IP"
- 2 Standard Ethernet connecting cable with RJ45 plug
- 3 Service interface (CDI -RJ45) of the measuring device with access to the integrated Web server


PROFIBUS DP



A0023114


- 1 Computer with Web browser (e.g. Internet Explorer) for accessing the integrated device Web server or with "FieldCare" operating tool with COM DTM "CDI Communication TCP/IP"
- 2 Standard Ethernet connecting cable with RJ45 plug
- 3 Service interface (CDI -RJ45) of the measuring device with access to the integrated Web server

EtherNet/IP



A0023113

- 1 Computer with Web browser (e.g. Internet Explorer) for accessing the integrated device Web server or with "FieldCare" operating tool with COM DTM "CDI Communication TCP/IP"
- 2 Standard Ethernet connecting cable with RJ45 plug
- 3 Service interface (CDI -RJ45) of the measuring device with access to the integrated Web server

Modbus RS485

A0023114

- 1 Computer with Web browser (e.g. Internet Explorer) for accessing the integrated device Web server or with "FieldCare" operating tool with COM DTM "CDI Communication TCP/IP"
- 2 Standard Ethernet connecting cable with RJ45 plug
- 3 Service interface (CDI -RJ45) of the measuring device with access to the integrated Web server

Certificates and approvals

CE mark	The measuring system is in conformity with the statutory requirements of the applicable EC Directives. These are listed in the corresponding EC Declaration of Conformity along with the standards applied. Endress+Hauser confirms successful testing of the device by affixing to it the CE mark.
C-Tick symbol	The measuring system meets the EMC requirements of the "Australian Communications and Media Authority (ACMA)".
Drinking water approval	<ul style="list-style-type: none"> ■ ACS ■ KTW/W270 ■ NSF 61 ■ WRAS BS 6920
Certification PROFIBUS	PROFIBUS interface The measuring device is certified and registered by the PROFIBUS User Organization (PNO). The measuring system meets all the requirements of the following specifications: <ul style="list-style-type: none"> ■ Certified in accordance with PROFIBUS PA Profile 3.02 ■ The device can also be operated with certified devices of other manufacturers (interoperability)
Modbus RS485 certification	The measuring device meets all the requirements of the MODBUS/TCP conformity test and has the "MODBUS/TCP Conformance Test Policy, Version 2.0". The measuring device has successfully passed all the test procedures carried out and is certified by the "MODBUS/TCP Conformance Test Laboratory" of the University of Michigan.
EtherNet/IP certification	The measuring device is certified and registered by the ODVA (Open Device Vendor Association). The measuring system meets all the requirements of the following specifications: <ul style="list-style-type: none"> ■ Certified in accordance with the ODVA Conformance Test ■ EtherNet/IP Performance Test ■ EtherNet/IP PlugFest compliance ■ The device can also be operated with certified devices of other manufacturers (interoperability)
Measuring instrument approval	Promag W 400 is (optionally) approved as a cold water meter (MI-001) for volume measurement in service subject to legal metrological control in accordance with the European Measuring Instruments Directive 2004/22/EC (MID).

Promag W 400 is qualified to OIML R49 and has an OIML Certificate of Conformity (optional).

Other standards and guidelines

- EN 60529
Degrees of protection provided by enclosures (IP code)
- EN 61010-1
Safety requirements for electrical equipment for measurement, control and laboratory use
- IEC/EN 61326
Emission in accordance with Class A requirements. Electromagnetic compatibility (EMC requirements).
- ANSI/ISA-61010-1 (82.02.01): 2004
Safety Requirements for Electrical Equipment for Measurement, Control and Laboratory Use - Part 1 General Requirements
- CAN/CSA-C22.2 No. 61010-1-04
Safety Requirements for Electrical Equipment for Measurement, Control and Laboratory Use - Part 1 General Requirements
- NAMUR NE 21
Electromagnetic compatibility (EMC) of industrial process and laboratory control equipment
- NAMUR NE 32
Data retention in the event of a power failure in field and control instruments with microprocessors
- NAMUR NE 43
Standardization of the signal level for the breakdown information of digital transmitters with analog output signal.
- NAMUR NE 53
Software of field devices and signal-processing devices with digital electronics
- NAMUR NE 105
Specifications for integrating fieldbus devices in engineering tools for field devices
- NAMUR NE 107
Self-monitoring and diagnosis of field devices
- NAMUR NE 131
Requirements for field devices for standard applications

Ordering information

Detailed ordering information is available from the following sources:

- In the Product Configurator on the Endress+Hauser web site: www.endress.com → Choose your country → Products → Select measuring technology, software or components → Select product (picklists: measurement method, product family etc.) → Device support (right-hand column): Configure the selected product → The Product Configurator for the selected product is opened.
- From your Endress+Hauser Sales Center: www.addresses.endress.com

Product Configurator - the tool for individual product configuration

- Up-to-the-minute configuration data
- Depending on the device: Direct input of measuring point-specific information such as measuring range or operating language
- Automatic verification of exclusion criteria
- Automatic creation of the order code and its breakdown in PDF or Excel output format
- Ability to order directly in the Endress+Hauser Online Shop

Application packages

Many different application packages are available to enhance the functionality of the device. Such packages might be needed to address safety aspects or specific application requirements.

The application packages can be ordered from Endress+Hauser either directly with the device or subsequently. Detailed information on the order code in question is available from your local Endress+Hauser sales center or on the product page of the Endress+Hauser website: www.endress.com.

Cleaning	Package	Description
	Electrode cleaning circuit (ECC)	The electrode cleaning circuit (ECC) function has been developed to have a solution for applications where magnetite (Fe_3O_4) deposits frequently occur (e.g. hot water). Since magnetite is highly conductive this build up leads to measuring errors and ultimately to the loss of signal. The application package is designed to AVOID build up of highly conductive matter and thin layers (typical of magnetite).
Diagnostics functions	Package	Description
	HistoROM extended function	<p>Comprises extended functions concerning the event log and the activation of the measured value memory.</p> <p>Event log: Memory volume is extended from 20 message entries (basic version) to up to 100 entries.</p> <p>Data logging (line recorder):</p> <ul style="list-style-type: none"> ▪ Memory capacity for up to 1000 measured values is activated. ▪ 250 measured values can be output via each of the 4 memory channels. The recording interval can be defined and configured by the user. ▪ Data logging is visualized via the local display or FieldCare.
Heartbeat Technology	Package	Description
	Heartbeat Verification +Monitoring	<p>Heartbeat Monitoring: Continuously supplies monitoring data, which are characteristic of the measuring principle, for an external condition monitoring system. This makes it possible to:</p> <ul style="list-style-type: none"> ▪ Draw conclusions - using these data and other information - about the impact the measuring application has on the measuring performance over time. ▪ Schedule servicing in time. ▪ Monitor the product quality, e.g. gas pockets. <p>Heartbeat Verification: Makes it possible to check the device functionality on demand when the device is installed, without having to interrupt the process.</p> <ul style="list-style-type: none"> ▪ Access via onsite operation or other operating interfaces, such as FieldCare for instance. ▪ End-to-end, traceable documentation of the verification results, including report. ▪ Makes it possible to extend calibration intervals in accordance with operator's risk assessment.

Accessories

Various accessories, which can be ordered with the device or subsequently from Endress+Hauser, are available for the device. Detailed information on the order code in question is available from your local Endress+Hauser sales center or on the product page of the Endress+Hauser website: www.endress.com.

Device-specific accessories	For the transmitter
	Accessories
	Description
	Display protection
	Is used to protect the display against impact or scoring from sand in desert areas.  For details, see Special Documentation SD00333F
	Connecting cable for remote version
	Coil current and electrode cables, various lengths, reinforced cables available on request.
	Ground cable
	Set, consisting of two ground cables for potential equalization.
	Post mounting kit
	Post mounting kit for transmitter.

Compact → remote conversion kit	For converting a compact device version to a remote device version.
Promag 50/53 → Promag 400 conversion kit	For converting a Promag with transmitter 50/53 to a Promag 400.

For the sensor

Accessories	Description
Ground disks	Are used to ground the fluid in lined measuring tubes to ensure proper measurement.  For details, see Installation Instructions EA00070D

Communication-specific accessories

Accessories	Description
Commubox FXA195 HART	For intrinsically safe HART communication with FieldCare via the USB interface.  For details, see "Technical Information" TI00404F
HART Loop Converter HMX50	Is used to evaluate and convert dynamic HART process variables to analog current signals or limit values.  For details, see "Technical Information" TI00429F and Operating Instructions BA00371F
Wireless HART adapter SWA70	Is used for the wireless connection of field devices. The WirelessHART adapter can be easily integrated into field devices and existing infrastructures, offers data protection and transmission safety and can be operated in parallel with other wireless networks with minimum cabling complexity.  For details, see Operating Instructions BA00061S
Fieldgate FXA320	Gateway for the remote monitoring of connected 4-20 mA measuring devices via a Web browser.  For details, see "Technical Information" TI00025S and Operating Instructions BA00053S
Fieldgate FXA520	Gateway for the remote diagnostics and remote configuration of connected HART measuring devices via a Web browser.  For details, see "Technical Information" TI00025S and Operating Instructions BA00051S
Field Xpert SFX350	Field Xpert SFX350 is a mobile computer for commissioning and maintenance. It enables efficient device configuration and diagnostics for HART and FOUNDATION Fieldbus devices in the non-Ex area .  For details, see Operating Instructions BA01202S
Field Xpert SFX370	Field Xpert SFX370 is a mobile computer for commissioning and maintenance. It enables efficient device configuration and diagnostics for HART and FOUNDATION Fieldbus devices in the non-Ex area and the Ex area .  For details, see Operating Instructions BA01202S

Service-specific accessories

Accessories	Description
Applicator	Software for selecting and sizing Endress+Hauser measuring devices: <ul style="list-style-type: none"> ▪ Calculation of all the necessary data for identifying the optimum flowmeter: e.g. nominal diameter, pressure loss, accuracy or process connections. ▪ Graphic illustration of the calculation results <p>Administration, documentation and access to all project-related data and parameters throughout the entire life cycle of a project.</p> <p>Applicator is available:</p> <ul style="list-style-type: none"> ▪ Via the Internet: https://wapps.endress.com/applicator ▪ On CD-ROM for local PC installation.

W@M	<p>Life cycle management for your plant W@M supports you with a wide range of software applications over the entire process: from planning and procurement, to the installation, commissioning and operation of the measuring devices. All the relevant device information, such as the device status, spare parts and device-specific documentation, is available for every device over the entire life cycle. The application already contains the data of your Endress+Hauser device. Endress+Hauser also takes care of maintaining and updating the data records.</p> <p>W@M is available:</p> <ul style="list-style-type: none"> ▪ Via the Internet: www.endress.com/lifecyclemanagement ▪ On CD-ROM for local PC installation.
FieldCare	<p>FDT-based plant asset management tool from Endress+Hauser. It can configure all smart field units in your system and helps you manage them. By using the status information, it is also a simple but effective way of checking their status and condition.</p> <p> For details, see Operating Instructions BA00027S and BA00059S</p>
Commubox FXA291	<p>Connects Endress+Hauser field devices with a CDI interface (= Endress+Hauser Common Data Interface) and the USB port of a computer or laptop.</p> <p> For details, see "Technical Information" TI00405C</p>

System components	Accessories	Description
	Memograph M graphic display recorder	<p>The Memograph M graphic display recorder provides information on all relevant measured variables. Measured values are recorded correctly, limit values are monitored and measuring points analyzed. The data are stored in the 256 MB internal memory and also on a SD card or USB stick.</p> <p> For details, see "Technical Information" TI00133R and Operating Instructions BA00247R</p>

Supplementary documentation

-  For an overview of the scope of the associated Technical Documentation, refer to the following:
- The CD-ROM provided for the device (depending on the device version, the CD-ROM might not be part of the delivery!)
 - The *W@M Device Viewer* : Enter the serial number from the nameplate (www.endress.com/deviceviewer)
 - The *Endress+Hauser Operations App*: Enter the serial number from the nameplate or scan the 2-D matrix code (QR code) on the nameplate.

Standard documentation	Brief Operating Instructions				
	<table border="1"> <tr> <th>Measuring device</th> <th>Documentation code</th> </tr> <tr> <td>Promag W 400</td> <td>KA01114D</td> </tr> </table>	Measuring device	Documentation code	Promag W 400	KA01114D
Measuring device	Documentation code				
Promag W 400	KA01114D				

Operating Instructions

Measuring device	Documentation code			
	HART	PROFIBUS DP	Modbus RS485	EtherNet/IP
Promag W 400	BA01063D	BA01234D	BA01231D	BA01214D

Supplementary device-dependent documentation**Special Documentation**

Contents	Documentation code
Modbus RS485 Register Information	SD01379D
Heartbeat Technology	SD01183D
Information on Custody Transfer Measurement	SD01230D

Installation Instructions

Contents	Documentation code
Installation Instructions for spare part sets	Specified for each individual accessory (→ 101)

Registered trademarks**HART®**

Registered trademark of the HART Communication Foundation, Austin, USA

PROFIBUS®

Registered trademark of the PROFIBUS User Organization, Karlsruhe, Germany

Modbus®

Registered trademark of SCHNEIDER AUTOMATION, INC.

EtherNet/IP™

Trademark of ODVA, Inc.

Microsoft®

Registered trademark of the Microsoft Corporation, Redmond, Washington, USA

Applicator®, FieldCare®, Field Xpert™, HistoROM®, Heartbeat Technology™

Registered or registration-pending trademarks of the Endress+Hauser Group

www.addresses.endress.com