

# Technical data sheet · LÜTZE ELECTRONIC LiY (C) Y TP

## Shielded electronic cable, paired



PVC electronic cables · shielded

<b>Identification</b>	Type	LIY(C)Y TP(10×2×0,14)
	Part-No.	110606

<b>Use/Application/Characteristics</b>		
Application	<ul style="list-style-type: none"> <li>• For interference-free transmission in all areas of electronics, measuring, monitoring and control technology</li> <li>• In low voltage switchgear, communications engineering</li> <li>• In dry and damp rooms</li> <li>• For flexible use with free movement without tensile load</li> </ul>	
Characteristics	<ul style="list-style-type: none"> <li>• PVC Flame-retardant, self-extinguishing</li> <li>• High active and passive interference resistance (EMC)</li> <li>• High crosstalk attenuation due to twisted pairs</li> <li>• Resistant to most oils, greases, acids and alkalis</li> <li>• Silicone free</li> <li>• RoHS-compliant</li> </ul>	

<b>Construction</b>	
Description	ELETRONIC LiY (C) Y TP
Number of conductors/cross-section	(10×2×0.14)
Jacket material	Special PVC
Jacket color	grey RAL 7032
Outer Ø	8.7 mm
Surface	adhesion-free matt

27.01.2017 – Subject to technical modification

Part-No. 110606

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
 www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
 www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE ELECTRONIC LiY (C) Y TP

## Shielded electronic cable, paired

---

Weight 11.5 kg/100 m  
Cu-Index 7.1 kg/100 m

### Element 1

Element construction (10×2×0,14)  
Conductor CU-wire bare  
Conductor category IEC 60228, Class 5  
Finely stranded DIN VDE 0295  
DIN EN 13602  
Conductor marking Colour coded  
Conductor marking standard DIN 47100  
Conductor insulation Special PVC

### overall construction

Overall stranding stranded pairs  
Overall wrapping Foil taping  
Overall shield Braid shield  
Tinned copper wires  
optical cover approx. 80%  
Jacket characteristics Flame-retardant  
self-extinguishing  
Oil resistant  
grease-resistant  
acid-resistant.  
alkali-resistant  
Silicone-free

---

### Technical data

---

Rated voltage  $U_0/U$  300 V  
Test voltage type AC 1200 V  
Temperature range moving -5 °C ... +70 °C  
Temperature range fixed -30 °C ... +70 °C  
Minimum bending radius moving 15×D  
Minimum bending radius fixed 6×D

### Element 1

Element construction (10×2×0,14)  
Insulation resistance at 20°C 20.0 MΩ×km  
Operating capacitance wire-shield 160 pF/m

---

### Approvals/Standards

---

27.01.2017 – Subject to technical modification

Part-No. 110606

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE ELECTRONIC LiY (C) Y TP

## Shielded electronic cable, paired

---

Conformity	CE RoHS
Burning behavior	IEC 60332-1-2 DIN EN 60332-1-2 VDE 0482 322-1-2

---

### General

Note CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

---

### Symbols



27.01.2017 – Subject to technical modification

Part-No. 110606

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY