

Technical data sheet · LÜTZE SUPERFLEX® PLUS (C) PUR FEEDBACK

Encoder cables for Siemens and other systems

For highest requirements in drive technology



PUR feedback cables · C-track compatible

Identification	Type	SU+(C)P SE(2×2×0,18)UL 30V GN
	Part-No.	111452
SIEMENS designation*	1BD71	

Use/Application/Characteristics

Application	<ul style="list-style-type: none"> • Incremental encoder cable, connection cable for tachometer, brake sensor, speed sensor • Due to Full PUR jacket and TPE conductor insulation optimally suited for c-tracks, extremely rough operating conditions and aggressive coolants and lubricants • Especially for industrial environments in mechanical and system engineering
Characteristics	<ul style="list-style-type: none"> • High active and passive interference resistance (EMC) • Braided shield optimised for continuous flexible use • Very good alternating bending strength • Low adhesion, abrasion-resistant, nick-resistant, tear-propagation-resistant • Hydrolysis-resistant, microbe-resistant, and rot-resistant • Weatherproof, ozone and UV resistant (normal lighting conditions) • Good ruggedness and salt water resistance • Excellent coolant and lubricant resistance • Resistant to most oils, greases, alcohol-free benzines and kerosene • Silicone free • RoHS compliant

Construction

28.04.2017 – Subject to technical modification

Part-No. 111452

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SUPERFLEX® PLUS (C) PUR FEEDBACK

Encoder cables for Siemens and other systems

For highest requirements in drive technology

Description	SUPERFLEX (C) PUR FEEDBACK SIEMENS
Number of conductors/cross-section	(2×2×0.18)
Jacket material	PUR
Jacket color	green RAL 6018
Outer Ø	5.1 mm
Outer Ø	0.201 inches
Surface	adhesion-free matt
Weight	4.2 kg/100 m
Weight	28 Lbs/Mft
Cu-Index	2.2 kg/100 m
Cu-Index	15 Lbs/Mft

Element 1

Element construction	(2×2×0.18)
Conductor	CU-wire tin-plated
Conductor category	IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 class 6
Conductor marking	brown red black orange
Conductor insulation	Polyolefin

overall construction

Overall stranding	Star quad stranding
Overall wrapping	Non-woven material
Overall shield	Braid shield Tinned copper wires optical cover approx. 85%
Jacket characteristics	Flame-retardant Oil resistant grease-resistant petrol-resistant (alcohol-free) kerosene-resistant Silicone-free Halogen free

Technical data

Test voltage type	AC 1000 V
-------------------	-----------

28.04.2017 – Subject to technical modification

Part-No. 111452

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SUPERFLEX® PLUS (C) PUR FEEDBACK

Encoder cables for Siemens and other systems

For highest requirements in drive technology

Temperature range moving	-25 °C ... +80 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	12×D
Minimum bending radius fixed	6×D
Travel distance	≤15 m
Speed	5 m/s
Acceleration	50 m/s ²

Element 1

Element construction	(2×2×0.18)
Insulation resistance at 20°C	200 MΩ×km


Approvals/Standards

Approvals	cURus AWM II A/B
UL style	AWM 20236
Conformity	CE RoHS REACH
Burning behavior according to	IEC 60332-1 DIN EN 60332-1-2 VDE 0482 322-1-2 UL 1581 Part 1080 VW-1 UL FT1
Oil resistant according to	UL 1581 HD 22.10
Halogen free according to	DIN EN 60754-1 IEC 60754-1

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--

Symbols



28.04.2017 – Subject to technical modification

Part-No. 111452

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SUPERFLEX® PLUS (C) PUR FEEDBACK
Encoder cables for Siemens and other systems
For highest requirements in drive technology



28.04.2017 – Subject to technical modification

Part-No. 111452

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk