

Technical data sheet · LÜTZE SUPERFLEX® PLUS M (C) PUR SERVO 0.6/1 kV

Supply line for Bosch Rexroth and other systems

For highest requirements



PVC servo cables · C-track compatible · shielded

| | | |
|-----------------------|----------|--|
| Identification | Type | SU+M(C)P SE(4G0,75+2×(2×0,34))UL 1KV OR |
| | Part-No. | 111719 |

Use/Application/Characteristics

| | |
|-----------------|--|
| Application | <ul style="list-style-type: none"> • For Indramat* system (and similar) • Connection cable motor/brake especially for frequency converters and SERVO drives in machine and plant construction, transport and conveyor technology • Due to Full PUR jacket and TPE / HGI conductor insulation optimally suited for c-tracks, extremely rough operating conditions and aggressive coolants and lubricants |
| Characteristics | <ul style="list-style-type: none"> • Especially for industrial environments in mechanical and system engineering • High active and passive interference resistance (EMC) • Braided shield optimised for continuous flexible use • Very good alternating bending strength • Low adhesion, abrasion-resistant, nick-resistant, tear-propagation-resistant • Hydrolysis-resistant, microbe-resistant, and rot-resistant • Weatherproof, ozone and UV resistant (normal lighting conditions) • Good ruggedness and salt water resistance • Excellent coolant and lubricant resistance • Resistant to most oils, greases, alcohol-free benzines and kerosene • Silicone free • RoHS compliant |

17.02.2017 – Subject to technical modification

Part-No. 111719

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SUPERFLEX® PLUS M (C) PUR SERVO 0.6/1 kV

Supply line for Bosch Rexroth and other systems

For highest requirements

Construction

| | |
|------------------------------------|--|
| Description | SUPERFLEX+ M (C) PUR SERVO BOSCH-REXROTH |
| Number of conductors/cross-section | (4G0.75+2×(2×0.34)) |
| Jacket material | PUR |
| Jacket color | orange RAL 2003 |
| Outer Ø | 11.2 mm |
| Outer Ø | 0.441 inches |
| Surface | adhesion-free matt |
| Weight | 17.7 kg/100 m |
| Cu-Index | 9.5 kg/100 m |
| Cu-Index | 9.5 Lbs/Mft |

Element 1

| | |
|----------------------------|---|
| Element construction | 4G0.75 |
| Conductor | CU-wire bare |
| Conductor category | IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 Klasse 6 |
| Conductor marking | black with white number print green/yellow |
| Conductor marking standard | DIN EN 50334 |
| Conductor insulation | Special TPE |

Element 2

| | |
|----------------------|---|
| Element construction | 2×(2×0.34) |
| Conductor | CU-wire bare |
| Conductor category | IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 Klasse 6 |
| Conductor marking | black with white number print |
| Conductor insulation | Special TPE |
| Stranding | Conductors stranded in pairs layer pitch optimised Conductors twisted without mechanical stress |
| Wrapping | Foil taping |
| Element shielding | Braid shield |

17.02.2017 – Subject to technical modification

Part-No. 111719

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SUPERFLEX® PLUS M (C) PUR SERVO 0.6/1 kV

Supply line for Bosch Rexroth and other systems

For highest requirements

overall construction

| | |
|------------------------|---------------------------------|
| Overall stranding | Elements stranded together |
| Overall wrapping | Non-woven material |
| Overall shield | Braid shield |
| | Tinned copper wires |
| | optical cover approx. 85% |
| Jacket characteristics | Flame-retardant |
| | Oil resistant |
| | grease-resistant |
| | petrol-resistant (alcohol-free) |
| | kerosene-resistant |
| | Silicone-free |
| | Halogen free |

Technical data

| | |
|-------------------------------|-------------------|
| Rated voltage U_0/U | 600/1000 V |
| Rated voltage UL | 1000 V |
| Test voltage type | AC 4000 V |
| Temperature range moving | -25 °C ... +80 °C |
| Temperature range fixed | -40 °C ... +80 °C |
| Minimum bending radius moving | 10×D |
| Minimum bending radius fixed | 6×D |

Element 1

| | |
|-------------------------------|-------------|
| Element construction | 4G0.75 |
| Insulation resistance at 20°C | 500.0 MΩ×km |

Element 2

| | |
|----------------------|------------|
| Element construction | 2×(2×0.34) |
|----------------------|------------|

Approvals/Standards

| | |
|------------|-----------|
| Approvals | UR |
| UL style | AWM 21223 |
| Conformity | CE |
| | RoHS |
| | REACH |

17.02.2017 – Subject to technical modification

Part-No. 111719

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SUPERFLEX® PLUS M (C) PUR SERVO 0.6/1 kV Supply line for Bosch Rexroth and other systems For highest requirements

| | |
|---------------------------|--|
| Burning behavior | IEC 60332-1-2 DIN EN 60332-1-2 UL 1581 UL C22.2 No. 210.2 Flame Rating FT1 |
| Halogen free according to | DIN EN 60754-1 IEC 60754-1 |

General

Note CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

Symbols



17.02.2017 – Subject to technical modification

Part-No. 111719

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY