

# Technical data sheet · LÜTZE SUPERFLEX<sup>®</sup> PLUS N (C) PUR 300 V

## For highest requirements



PUR control cables · C-track compatible · shielded

<b>Identification</b>	Type	SU+N(C)PUR(5G0,75)UL 300V
	Part-No.	113307

### Use/Application/Characteristics

#### Application

- Machine and device construction, transport and conveyor technology, HVAC technology
- In areas with high concentrations of people or material assets, where corrosive gases need to be avoided in the event of fire
- As a monitoring, measurement and control cable for industrial applications
- Especially for rough environments
- For installation in energy chains with constant linear movement
- Anywhere where electrical interference fields can influence the signal transmission

17.02.2017 – Subject to technical modification

Part-No. 113307

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 · Fax +1 (704) 504-0223

www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2

www.lutze.com · sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE SUPERFLEX<sup>®</sup> PLUS N (C) PUR 300 V

## For highest requirements

Characteristics	<ul style="list-style-type: none"> <li>• Reduced friction due to very smooth conductor insulation (HGI) for high mechanical loads</li> <li>• High active and passive interference resistance (EMC)</li> <li>• Braided shield optimized for continuous flexing applications</li> <li>• Low capacitance, very good electrical properties</li> <li>• Flame-retardant, self-extinguishing</li> <li>• Halogen-free, no corrosive gases</li> <li>• Very good flexing strength</li> <li>• Low adhesion, Abrasion-resistant, Tear resistant</li> <li>• Hydrolysis-resistant, microbe-resistant, and rot-resistant</li> <li>• Weathering, ozone and UV resistant (normal lighting conditions)</li> <li>• Good resistance to wear and salt water</li> <li>• Excellent coolant and lubricant resistance</li> <li>• Largely resistant to oils, greases, alcohol-free benzines and kerosene</li> <li>• Silicone free</li> <li>• RoHS-compliant</li> </ul>
-----------------	--

---

### Construction

Description	SUPERFLEX PLUS N (C) PUR 300 V
Number of conductors/cross-section	(5G0,75)
Jacket material	PUR
Jacket color	grey RAL 7001
Outer Ø	8.3 mm
Weight	9.7 kg/100 m
Cu-Index	5.3 kg/100 m

### Element 1

Element construction	(5G0,75)
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 Klasse 6
Conductor marking	black with white number print green/yellow
Conductor insulation	Special TPE

### overall construction

Overall stranding	Conductors stranded layers schlaglängenoptimiert Conductors twisted without mechanical stress
Overall wrapping	Non-woven material
Inner jacket	TPE

17.02.2017 – Subject to technical modification

Part-No. 113307

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE SUPERFLEX<sup>®</sup> PLUS N (C) PUR 300 V

## For highest requirements

---

Overall shield	Braid shield Tinned copper wires optical cover approx. 85%
Jacket characteristics	Flame-retardant self-extinguishing Oil resistant grease-resistant petrol-resistant (alcohol-free) kerosene-resistant Silicone-free Halogen free

---

### Technical data

---

Rated voltage $U_0/U$	300/500 V
Rated voltage UL	300 V
Test voltage type	AC 3000 V
Temperature range moving	-25 °C ... +80 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	10×D
Minimum bending radius fixed	6×D

### Element 1

Element construction	(5G0,75)
Insulation resistance at 20°C	1000.0 MΩ×km
Operating capacitance Ader-Ader	75 pF/m
Operating capacitance wire-shield	108 pF/m

---

### Approvals/Standards

---

Approvals	cURus
UL style	AWM 20233
Conformity	CE RoHS REACH
Burning behavior	IEC 60332-1 DIN EN 60332-1-2 VDE 0482 322-1-2
Halogen free according to	DIN EN 60754-1 IEC 60754-1

---

### General

---

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--

---

17.02.2017 – Subject to technical modification

Part-No. 113307

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk




SYSTEMATIC TECHNOLOGY

# Technical data sheet · LÜTZE SUPERFLEX® PLUS N (C) PUR 300 V

## For highest requirements

### Symbols



17.02.2017 – Subject to technical modification

Part-No. 113307

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk