

Technical data sheet · LÜTZE SUPERFLEX® PLUS N PUR 300 V

For highest requirements



PUR control cables · C-track compatible · unshielded

Identification	Type	SU+N PUR 2×0,75 UL 300V
	Part-No.	113432

Use/Application/Characteristics

Application	<ul style="list-style-type: none"> • Machine and device construction, transport and conveyor technology, HVAC technology • In areas with high concentrations of people or material assets, where corrosive gases need to be avoided in the event of fire • As a monitoring, measurement and control cable for industrial applications • Especially for rough environments • For installation in energy chains with constant linear movement
Characteristics	<ul style="list-style-type: none"> • Reduced friction due to high glide conductor insulation (HGI) for high mechanical loads • Low capacitance, very good electrical properties • Flame-retardant, self-extinguishing • Halogen-free, no corrosive gases • Very good flexing strength • Low adhesion, abrasion-resistant, nick-resistant, tear resistant • Hydrolysis-resistant, microbe-resistant, and rot-resistant • Weatherproof, ozone and UV resistant (normal lighting conditions) • Good ruggedness and salt water resistance • Excellent coolant and lubricant resistance • Resistant to most oils, greases, alcohol-free benzines and kerosene • Silicone free • RoHS-compliant

17.02.2017 – Subject to technical modification

Part-No. 113432

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
 www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
 www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SUPERFLEX[®] PLUS N PUR 300 V

For highest requirements

Construction

Description	SUPERFLEX+ N PUR 300V
Number of conductors/cross-section	2×0.75
Jacket material	PUR
Jacket color	grey RAL 7001
Outer Ø	5.2 mm
Weight	3.7 kg/100 m
Cu-Index	1.5 kg/100 m

Element 1

Element construction	2×0,75
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 Klasse 6
Conductor marking	black with white number print
Conductor insulation	Special TPE

overall construction

Overall stranding	Conductors stranded layers schlaglängenoptimiert Conductors twisted without mechanical stress
Overall wrapping	Non-woven material
Jacket characteristics	Flame-retardant self-extinguishing Oil resistant grease-resistant petrol-resistant (alcohol-free) kerosene-resistant Silicone-free Halogen free

Technical data

Rated voltage U_0/U	300/500 V
Rated voltage UL	300 V
Test voltage type	AC 3000 V
Temperature range moving	-25 °C ... +80 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	7.5×D
Minimum bending radius fixed	4×D

17.02.2017 – Subject to technical modification

Part-No. 113432

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet · LÜTZE SUPERFLEX[®] PLUS N PUR 300 V

For highest requirements

Travel distance ≤100 m

Element 1

Element construction 2×0,75
 Insulation resistance at 20°C 1000.0 MΩ×km
 Operating capacitance Ader-Ader 75 pF/m
 Operating capacitance wire-shield 108 pF/m

Approvals/Standards

Approvals cURus
 UL style AWM 20233
 Conformity CE
 RoHS
 REACH
 Burning behavior IEC 60332-1
 DIN EN 60332-1-2
 VDE 0482 322-1-2
 UL 1581 Part VW-1 Flame Test
 UL FT1
 Oil resistant according to Oil Res II
 Halogen free according to DIN EN 60754-1

General

Note CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

Symbols



17.02.2017 – Subject to technical modification

Part-No. 113432

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
 www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
 www.lutze.com • sales.gb@lutze.co.uk